## **Extension Cords**

Only round jacketed extension cords should be used, and we recommend that they be listed by Underwriters Laboratories (U.L.). An extension cord must have adequate wire size (AWG or American Wire Gauge) for safety, and to prevent loss of power and overheating. The smaller the gauge number of the wire, the greater the capacity of the cable, that is 16 gauge has more capacity than 18 gauge. When using more than one extension cord to make up the total length, be sure each individual extension contains at least the minimum wire size.

To determine the minimum wire size required, refer to the chart below:

CH	ART FC	RMIN	IMUM'	WIRE S	IZE (AV	(G) OF	EXTENS	SIONC	ORDS	
		TOT	AL EXT	ENSION	CORD	LENGTH	1 - FEET			-
	25	50	75	100	125	150	175	200		i di
Wire Size	18	18	16	16	14	14	12	12		JAN.

Before using an extension cord, inspect it for loose or exposed wires, damaged insulation, and defective fittings. Make any needed repairs or replace the cord if necessary. Black & Decker has extension cords available that are U.L. listed.

Black & Decker's Full Two Year Home Use Warranty states that, in case of a defect, you may return the tool to the place of purchase for a free replacement (if it is a participating retailer) or you may take it to a Black & Decker Service Center.

# **Home Use Warranty (A Full Two Year Warranty)**

Black & Decker (U.S.) Inc. warrants this product for two years against any defects that are due to faulty material or workmanship. Please return the complete unit, transportation prepaid, to the seller (if a participating retailer) for free replacement (proof of purchase may be required). The unit may also be returned to a Black & Decker Service Center or Authorized Service Station listed under "Tools Electric" in the Yellow Pages for free replacement or repair at our option. This warranty does not apply to accessories. This warranty gives you specific legal rights and you may have other rights which vary from state to state. Should you have any questions, contact your nearest Black & Decker Service Center Manager.

Like all Black & Decker tools, your Glue Gun is listed by Underwriters' Laboratories to ensure that it meets stringent safety requirements.

> This symbol on the nameplate means the product is Listed by Underwriters' Laboratories, Inc.





See 'Tools-Electric' -Yellow Pagesfor Service & Sales



€ 1985 Printed in U.S.A.

Form No. 741238





# **Instruction Manual**

Heavy Duty Trigger Feed Glue Gun



If you already own a Black & Decker Power Tool you know the pleasures a quality, high performance tool can deliver.

Your new 9737 Trigger Feed Glue Gun is designed to carry on the tradition of value that has made Black & Decker the name to trust for over 70 years. Engineered to apply hot melt adhesive to practically any surface, your new glue gun is clean, silent, durable and big enough for professional type production tasks.

A handy fold away stand is included to hold the tool while you

bring the work to it. If you need to hand hold the gun to reach tight spots, just fold the stand away.

So take a few minutes to read this informative instruction manual. Pay particular attention to the safety rules we've provided for your protection.

We want you to enjoy your Black & Decker tool and the more you know about it, the happier you'll be with it.

Thank you for selecting Black & Decker

And don't forget to send in your owner's registration card.



## **Accessories**

The accessories listed in this manual are available at extra cost from your local dealer or Black & Decker Service Center. A complete listing of service centers is included on the owner's registration card packed with your tool.

If you need assistance in locating any accessory, please contact: User Services, Black & Decker (U.S.) Inc., User Services Dept., 10 North Park Drive, P.O. 857, Hunt Valley, MD 21030-0857.

Recommended accessories for use with your tool are listed below **CAUTION**: The use of any other accessory or attachment might be hazardous or cause damage to the tool

All Black & Decker glue sets in 30 to 60 seconds.

Sticks/Pkg.	Length	Description	Color
12	2"	Wood/Repair	Wood tone
12	2"	General Purpose	Clear
12	2"	Caulk/Sealer	White
6	4"	Wood/Repair	Wood tone
6	4"	General Purpose	Clear
6	4"	Caulk/Sealer	White
12	10"	General Purpose	Clear
Pkg of 2		Spreader Nozzle	(For filling wide gaps)
Nozzles		Hypodermic Nozzle	(For extremely close work)

To install a new nozzle, plug the gun in, allow it to reach operating temperature and aim the gun straight up to prevent glue leakage. Unscrew the nozzle (use care when handling hot parts) and screw the new nozzle in.

## **Suggested Uses of Hot Melt Glue**

WOOD/REPAIR GLUE: (Wood Tone in color)

For general repairs. Set time long enough to permit final positioning. Provides strong bonding of wood, plastics and metal.

iding of wood, plastics are	o metal.	
Upholstery	Carpet Repair	Paper Products
Fabric Repair	Carton Sealing	Wood to Wood
Picture Framing	Leather Repair	

#### CAULK/SEALER: (White in color)

For use as a repair sealant. Provides fast bonding and is electrically insulative and waterproof

waterproof			
Replacing Tile Tile Grouting	Gutter Sealing Plugging Holes	Rubber, Plastic Steel to Steel	

#### CRAFT GLUE: (Clear in appearance)

For general purpose applications, Provides fast, strong bonding to plastics, foam, fabric and ceramics

and ceramics.		
Dry Flower Arrangements Model Making	School Projects Paper to Wood	Plexiglass to Wood Paper Cartons

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com