

Material Safety Data Sheet



Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 1/7

1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK Alkaline Battery KAA, KAA-P

Product code: 1078419

Supplier: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York 14650; KODAK CANADA INC., 6 Monogram Place Suite 200 Toronto, Ontario M9R 0A1

For Emergency Health, Safety & Environmental Information, call (585) 722-5151 (USA)

For other information or to request an MSDS, call (800) 242-2424.

Synonyms: None.

Product Use: Battery, For consumer and industrial use.

2. Hazards identification

CONTAINS: Manganese dioxide (1313-13-9), Zinc (7440-66-6), Potassium hydroxide (1310-58-3), Graphite (7782-42-5)

WARNING!

MAY FLAME OR LEAK IF OPENED, SHORT CIRCUITED, RECHARGED, CONNECTED IMPROPERLY, OR EXPOSED TO FIRE OR HIGH TEMPERATURES.

HARMFUL IF SWALLOWED

**VAPORS/FUMES FROM DAMAGED BATTERIES MAY CAUSE RESPIRATORY TRACT IRRITATION
DAMAGED BATTERIES MAY CAUSE SKIN AND EYE BURNS**

3. Composition/information on ingredients

Weight %	Components - (CAS-No.)
30 - 40	Manganese dioxide (1313-13-9)
10 - 20	Zinc (7440-66-6)
5 - 10	Potassium hydroxide (1310-58-3)
1 - 5	Graphite (7782-42-5)

Weight % listed is based on approximate percent of the average weight of the battery (38 grams).

The components in this section may only represent a hazard if the integrity of the battery is compromised.

4. First aid measures

The routine handling and use of intact, non-damaged batteries is not expected to result in situations that require first-aid measures. If battery is damaged due to opening, cutting, crushing, overheating, improper installation, exposure to fire or high temperatures, or recharging, battery contents may be released.

Inhalation: If vapours or fumes from vented or leaking battery are irritating to respiratory tract, move to fresh air. Get medical attention if symptoms occur.

Material Safety Data Sheet

Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 2/7



Eyes: In case of contact with battery contents (liquid or metal), immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin: In case of contact with battery contents (liquid or metal), immediately remove metal fragments and flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes. Get medical attention immediately.

Ingestion: All batteries may be harmful if swallowed. Call a physician or poison control center immediately for any actual or suspected ingestion. If swallowed, DO NOT induce vomiting. Batteries may lodge in the throat or digestive tract and fragment. If battery was leaking or was chewed, rinse mouth thoroughly with water.

Notes to physician:

Hazards: Battery ingestions should not be managed in the same way as other small metallic object ingestions, eg., coins. The position and integrity of the battery in the gastrointestinal tract should be assessed and monitored by x-ray. Leaking batteries may cause necrosis and tissue damage. Larger batteries or batteries that lodge in the gastrointestinal tract may have to be removed endoscopically or surgically.

5. Fire-fighting measures

Extinguishing Media: Use appropriate agent for adjacent fire.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: Carbon oxides, oxides of manganese, oxides of zinc, (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: Fire or high temperatures may cause battery to flame or leak flammable and hazardous vapours. Damaged or opened batteries can result in rapid heating and the release of flammable and hazardous vapours.

6. Accidental release measures

Dispose of in accordance with local regulations (see Section 13. Disposal considerations).

For Large Spills: None should be needed.

7. Handling and storage

Personal precautions: If battery has been damaged, do not breathe fumes or vapours. Do not get battery contents in eyes, on skin, on clothing. Wash thoroughly after handling.

Prevention of Fire and Explosion: DO NOT DISASSEMBLE. Keep away from heat and flame. Do not short circuit. Avoid the use of old and new batteries or batteries of varying sizes and types in the same battery assembly. The batteries electrical characteristics and capabilities may vary and damage may

Material Safety Data Sheet



Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 3/7

result to the batteries or electrical equipment. DO NOT RECHARGE. Charging may result in electrolyte leakage, explosion and/or cause the battery to flame. Avoid reversing polarity within a device or a battery assembly. To do so may cause leakage, explosion, and/or flame.

Storage: Do not store in a manner that allows terminals to short circuit. Keep in a dry, cool place. Keep away from direct sunlight. Storage above 21°C (70°F) may affect product quality. Do not freeze. Keep away from water. Short circuiting may reduce battery service life. Extended short circuiting creates high temperatures in the battery. High temperatures can cause leakage, explosion, and/or flame. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

Occupational exposure controls

Chemical Name	Regulatory List	Value Type	Value
Manganese dioxide	OSHA Z1	Ceiling Limit Value: <i>Expressed as Mn</i>	5 mg/m3
	ACGIH	time weighted average <i>Expressed as Mn</i>	0.2 mg/m3
Potassium hydroxide Graphite	ACGIH	Ceiling Limit Value:	2 mg/m3
	ACGIH	time weighted average <i>Form of exposure: Respirable fraction.</i>	2 mg/m3
	Z3	<i>Remarks: Listed</i>	
	OSHA Z1	time weighted average <i>Form of exposure: Respirable fraction.</i>	5 mg/m3
	OSHA Z1	time weighted average <i>Form of exposure: Total dust.</i>	15 mg/m3
	Z3	time weighted average	15 millions of particles per cubic foot of air
	OSHA Z1A	time weighted average <i>Form of exposure: Respirable dust.</i>	2.5 mg/m3

Ventilation: Supplemental ventilation may be needed in special circumstances to control fumes/vapours to an acceptable level.

Respiratory protection: None should be needed.

Eye protection: When handling a damaged battery, wear safety glasses with side shields (or goggles).

Hand protection: When handling a damaged battery, wear impervious gloves.

9. Physical and chemical properties

Physical form: solid

Colour: not applicable

Odour: odourless

Specific gravity: not applicable

Material Safety Data Sheet



Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 4/7

Vapour pressure: negligible

Vapour density: not applicable

Volatile fraction by weight: not applicable

Melting point/range: not applicable

Water solubility: insoluble

pH: not applicable

Flash point: not applicable

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: no data available.

Hazardous decomposition products: None under normal conditions of use.

Hazardous Polymerization: Hazardous polymerisation does not occur.

11. Toxicological information

Effects of Exposure

General advice: Since the materials in this battery are sealed in the battery case, the potential for exposure to the components of the battery is negligible when the battery is used as directed. However, technical or electrical abuse of the battery may result in the release of battery contents.

Contains: Manganese dioxide. Can cause nervous system damage.

Inhalation: Intact battery: Expected to be a low hazard for recommended handling. Damaged battery: Harmful if inhaled. May cause irritation to the mucous membranes and upper respiratory tract.

Eyes: Intact battery: Expected to be a low hazard for recommended handling. Damaged battery: Contact with electrolyte (liquid) causes burns. Airborne dust/mist/vapor irritating. Contact with metal fragments may cause burns or mechanical injury.

Skin: Intact battery: Expected to be a low hazard for recommended handling. Damaged battery: Contact with electrolyte (liquid) causes burns. Contact with metal fragments may cause burns or mechanical injury. Harmful if absorbed through skin. Vapors or fumes may cause irritation.

Ingestion: All batteries may be harmful if swallowed. May cause burns of the gastrointestinal tract if swallowed.

Data for Potassium hydroxide (CAS 1310-58-3):

Material Safety Data Sheet



Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 5/7

Acute Toxicity Data:

- Oral LD50 (rat): 273 mg/kg
- Skin irritation: severe

12. Ecological information

This material is not expected to be harmful to aquatic life.

13. Disposal considerations

DO NOT INCINERATE or expose to fire. Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws.

14. Transport information

For transportation information, go to: www.kodak.com/go/ship.

15. Regulatory information

Notification status

Regulatory List	Notification status
EINECS	y (positive listing)
TSCA	y (positive listing)
AICS	y (positive listing)
DSL	y (positive listing)
ENCS (JP)	n (Negative listing)
KECI (KR)	y (positive listing)
PICCS (PH)	y (positive listing)
INV (CN)	y (positive listing)

A N (Negative listing) indicates one or more component is either not on the public Inventory or is subject to exemption requirements. If additional information is needed contact Kodak.

Other regulations

American Conference of Governmental Industrial Hygienists (ACGIH):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
International Agency for Research on Cancer (IARC):	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
U.S. National Toxicology Program (NTP):	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated

Material Safety Data Sheet



Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 6/7

	carcinogen by NTP.
U.S. Occupational Safety and Health Administration (OSHA):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
California Prop. 65:	none
US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required:	Manganese dioxide, Zinc
US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A):	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323):	Manganese dioxide, Zinc, Potassium hydroxide, Water, Graphite
US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000):	Zinc, Graphite
US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5):	Manganese dioxide, Zinc, Potassium hydroxide, Water, Graphite

16. Other information

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

US/Canadian Label Statements:

CONTAINS: Manganese dioxide (1313-13-9), Zinc (7440-66-6), Potassium hydroxide (1310-58-3), Graphite (7782-42-5)

WARNING!

MAY FLAME OR LEAK IF OPENED, SHORT CIRCUITED, RECHARGED, CONNECTED IMPROPERLY, OR EXPOSED TO FIRE OR HIGH TEMPERATURES.

HARMFUL IF SWALLOWED

VAPORS/FUMES FROM DAMAGED BATTERIES MAY CAUSE RESPIRATORY TRACT IRRITATION

DAMAGED BATTERIES MAY CAUSE SKIN AND EYE BURNS

FIRST AID: If vapours or fumes from vented or leaking battery are irritating to respiratory tract, move to fresh air. Get medical attention if symptoms occur. In case of contact with battery contents (liquid or metal), immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately. In case of contact with battery contents (liquid or metal), immediately remove metal fragments and flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes. Get medical attention immediately. All batteries may be harmful if swallowed. Call a physician or poison control center immediately for any actual or suspected ingestion. If swallowed, DO NOT induce vomiting. Batteries may lodge in the throat or digestive tract and fragment. If battery was leaking or was chewed, rinse mouth thoroughly with water.

Material Safety Data Sheet

Revision Date: 10/08/2007
000000023093/Version: 1.2
Print Date: 02/13/2009
Page: 7/7



Keep out of reach of children.

Do not handle or use until safety precautions in Material Safety Data Sheet (MSDS) have been read and understood.

Since emptied containers retain product residue, follow label warnings even after container is emptied.

IN CASE OF FIRE: Use appropriate agent for adjacent fire.

IN CASE OF SPILL: Dispose of in accordance with local regulations (see Section 13. Disposal considerations). For Large Spills: None should be needed.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>