

JBL

HOME THEATER
IN-WALL SERIES

HTI6, HTI8, HTI55 and
HTI6C

OWNER'S GUIDE

THANK YOU FOR CHOOSING JBL

For more than 50 years, JBL has been involved in every aspect of music and film recording and reproduction, from live performances to monitoring the recordings you play in your home, car or office.


We're confident that the JBL loudspeakers you have chosen will provide every note of enjoyment that you expected – and that when you think about purchasing additional audio equipment for your home, car or office, you will once again choose JBL.

Please take a moment to register your product on our Web site at www.jbl.com. It enables us to keep you posted on our latest advancements, and helps us to better understand our customers and build products that meet their needs and expectations.


JBL Consumer Products

INCLUDED

HTI6, HTI8




One pair of speakers with grilles.




Template/paint shield
(punch out at perforation).

HTI55




One loudspeaker with grille.
Logo to be attached to grille depending on vertical or horizontal installation.




Template/paint shield
(punch out at perforation).

HTI6C





One pair of speakers with grilles.





Template/paint shield
(punch out at perforation).

SPEAKER PLACEMENT


Front Speakers (HTI6, HTI8, HTI55)



Models HTI6, HTI8 and HTI55 as Rear Speakers



Model HTI6C in Ceiling



Proper placement of the speakers is an important step in obtaining the most realistic soundstage possible. These recommendations are for the optimum placement of the loudspeakers. Use these placement recommendations as a guide. Slight variations will not diminish your listening pleasure.

The front speakers should be placed the same distance from each other as they are from the listening position. They should

be placed at about the same height from the floor as the listeners' ears will be, with the tweeters aimed toward the listening position at ear-level height.


Model HTI55 is suitable for the front left, center and right positions, and it may also be used as a side surround or surround back speaker. It may be mounted horizontally or vertically, but make sure to position it so that the tweeters for all of the front speakers are at the same height (or differ by no more than 2 feet). You may rotate the tweeter to correctly orient the JBL logo.

In a home theater configuration, the two surround speakers should be placed slightly behind the listening position and, ideally, should face each


other and be at a level higher than the listeners' ears. If that is not possible, they may be placed in a wall behind the listening position, facing forward. The rear wall is the required mounting position for the surround back speakers in 6.1- and 7.1-channel systems. The surround speakers should not call attention to themselves. They should provide a diffuse, ambient sound accompanying the main program material heard in the front speakers. In Dolby* Digital and DTS® systems, aim the tweeters toward the listening position at ear-level height.

SPEAKER CONNECTIONS

Connection Tips



The wires for both speakers should be the same length. If one speaker is placed closer to the amplifier than the other, hide the excess wire behind the wall.



Speakers and electronics terminals have corresponding (+) and (-) terminals. Most manufacturers of speakers and electronics, including JBL, use red to denote the (+) terminal and black for the (-) terminal. It is important to connect both speakers identically: (+) on the speaker to (+) on the amplifier and (-) on the speaker to (-) on the amplifier. Wiring "out of phase" results in thin sound, weak bass and a poor stereo image. With the advent of multi-channel surround-sound systems, connecting all of the speakers in your system with the correct polarity remains equally important in order to preserve the proper ambience and directionality of the program material.

Wire Length

Up to 20 ft.

Up to 30 ft.

Greater than 30 ft.

Recommended Size

16 gauge

12 gauge

10 gauge

INSTALLATION

The JBL HTI Series in-wall speakers were designed to be easily installed. However, if you are unsure of your ability to properly install these loudspeakers, please contact your dealer or a qualified installer.

Tools Needed




Pencil




Phillips #2 screwdriver




Measuring tape



Utility knife




Carpenter's level




Awl

EXISTING CONSTRUCTION


HTI16, HTI8, HTI55




Remove the grille from the speaker frame by pulling on the paper tab. If the tab is missing, to avoid scratching the grille or baffle you may unfold a paper clip, insert the straight end through one of the holes in the grille, and gently pull up.




Determine the correct speaker location.
NOTE: Remove the inner template, which is the paint shield, at the perforation. Use the outer template when cutting the drywall. Although the HTI55 may be oriented either horizontally or vertically, the installation procedure is the same.




NOTE: Always allow at least one-half inch between a wall stud and the speaker cutout or the locking tabs will not be able to swivel into place.




Cut the drywall.



Connect the speaker wires to the speaker.




Place the frame assembly in the wall.



Screw down each of the four (six for HTI55) Phillips head screws. The locking tabs will swivel into place and secure the unit to the rear surface of the drywall.


The HTI speakers feature unique swivel mounts for the tweeters that enable you to aim the very directional high frequencies toward the listening position, at ear-level height. Before installing the speaker grille, gently press on the outer edge of the tweeter mount to adjust the position of the tweeter. The tweeter will not swivel more than 15 degrees in any direction; do not attempt to force it to move further. You may also rotate the tweeter to orient the JBL logo as desired.




Replace the metal grille. For the HTI55 only, attach the JBL logo to the grille to correspond to vertical or horizontal installation.

EXISTING CONSTRUCTION


HTI6C




Remove the grille from the speaker frame by pulling on the paper tab. If the tab is missing, to avoid scratching the grille or baffle you may unfold a paper clip, insert the straight end through one of the holes in the grille, and gently pull up.




Determine the correct speaker location. **Note:** Remove the inner template, which is the paint shield, at the perforation. Use the outer template when cutting the drywall.




Cut the drywall. **Note:** Always allow at least one-half inch between a wall stud and the speaker cutout or the locking tabs will not be able to swivel into place.



Connect the speaker wires to the speaker.




Place the frame assembly in the wall.



Screw down each of the three Phillips head screws. The locking tabs will swivel into place and secure the unit to the rear surface of the drywall.

The HTI speakers feature unique swivel mounts for the tweeters that enable you to aim the very directional high frequencies toward the listening position, at ear-level height. Before installing the speaker grille, gently press on the outer edge of the tweeter mount to adjust the position of the tweeter. The tweeter will not swivel more than 15 degrees in any direction; do not attempt to force it to move further. You may also rotate the tweeter to orient the JBL logo as desired.



Replace the metal grille.

NEW CONSTRUCTION

You will need to purchase the correct rough-in frame kit for your model:

Speaker Model	Rough-in Frame Kit
HTI6	RIF6
HTI8	RIF8
HTI55	RIF55
HTI6C	RIF6C

Detailed installation instructions are supplied with the rough-in kit.

PAINTING THE SPEAKER FRAME AND GRILLE

JBL HTI Series loudspeakers can be painted to match any decor. If you wish to change their color, the satin finish on the grille and frame will function as a primer coat. Before painting, install the paint shield (in the assembly kit) securely into the recess in the baffle. This will

protect the speaker components and baffle from paint residue. Use a high-quality spray paint, and apply a thin coat of color. Be certain the grille perforations remain free of paint. Filling them with paint will diminish the sound quality.

Note: Gently remove the acoustical foam blanket from the grille before painting. Reattach the blanket after the paint has dried.

TROUBLESHOOTING

If there is no sound from any of the speakers:

- Check that receiver/amplifier is on and a source is playing.
- Check all wires and connections between receiver/amplifier and speakers. Make sure all wires are connected. Make sure none of the speaker wires are frayed, cut or punctured.
- Review proper operation of your receiver/amplifier.

If there is no sound coming from one speaker:

- Check the "Balance" control on your receiver/amplifier.
- Check all wires and connections between receiver/amplifier and speakers. Make sure all wires are connected. Make sure none of the speaker wires are frayed, cut or punctured.

In multichannel applications, make sure that your receiver or processor has been configured to enable all channels that you are using.

If there is low (or no) bass output:

- Make sure the connections to the left and right "Speaker Inputs" have the correct polarity (+ and -).
- Consider adding a powered subwoofer to your system.
- In Dolby Digital or DTS modes, make sure your receiver/processor is correctly configured. When using a subwoofer, make sure the subwoofer output of the receiver/processor has been enabled. If no subwoofer is being used, make sure the left and right front and rear speakers have been configured as "LARGE." See your

receiver/processor's owner's manual for further information on correct speaker configuration in Dolby Digital, DTS and other surround-sound modes.

If the system plays at low volumes but shuts off as volume is increased:

- Check all wires and connections between receiver/amplifier and speakers. Make sure all wires are connected. Make sure none of the speaker wires are frayed, cut or punctured.
- If more than one pair of main speakers is being used, check the minimum-impedance requirements of your receiver/amplifier.

SPECIFICATIONS

HTI6

Frequency Response
38Hz – 20kHz (-10dB)
Recommended
Maximum Amplifier
Power †
100 watts
Impedance
8 ohms nominal
Sensitivity
88dB (2.83V/1m)
Crossover Frequency
2,500Hz
Woofer
6-1/2" Polymer-coated aluminum
cone w/rubber surround
Tweeter
1" Pure-titanium dome,
w/Elliptical Oblate Spheroidal™
(EOS) waveguide, and swivel mount
Plate Size (W x H)
8-1/2" x 11" (216mm x 279mm)
Mounting Cutout Size
(W x H)
7-1/8" x 9-11/16" (181mm x 246mm)
Mounting Depth
3-7/8" (98mm)
Weight per Speaker
11 lb (5kg)

HTI8

Frequency Response
30Hz – 20kHz (-10dB)
Recommended
Maximum Amplifier
Power †
120 watts
Impedance
8 ohms nominal
Sensitivity
90dB (2.83V/1m)
Crossover Frequency
2,500Hz
Woofer
8" Polymer-coated aluminum
cone w/rubber surround
Tweeter
1" Pure-titanium dome,
w/Elliptical Oblate Spheroidal™
(EOS) waveguide, and swivel mount
Plate Size (W x H)
10-1/8" x 13-1/8" (257mm x 333mm)
Mounting Cutout Size
(W x H)
8-7/8" x 11-13/16" (225mm x 300mm)
Mounting Depth
4" (102mm)
Weight per Speaker
13.5 lb (6.1kg)

HTI55

Frequency Response
40Hz – 20kHz (-10dB)
Recommended
Maximum Amplifier
Power †
120 watts
Impedance
8 ohms nominal
Sensitivity
88dB (2.83V/1m)
Crossover Frequency
2,000Hz
Woofer
Dual 5" polymer-coated aluminum
cone w/rubber surround
Tweeter
1" Pure-titanium dome,
w/Elliptical Oblate Spheroidal™
(EOS) waveguide, and swivel mount
Plate Size
15-3/8" x 7-1/2" (391mm x 191mm)
Mounting Cutout Size
14" x 6" (356mm x 152mm)
Mounting Depth
3-7/8" (98mm)
Weight per Speaker
5.7 lb (2.6kg)

HTI6C

Frequency Response
40Hz – 20kHz (-10dB)
Recommended
Maximum Amplifier
Power †
100 watts
Impedance
8 ohms nominal
Sensitivity
88dB (2.83V/1m)
Crossover Frequency
2,000Hz
Woofer
6-1/2" Polymer-coated aluminum
cone w/rubber surround
Tweeter
1" Pure-titanium dome,
w/swivel mount
Plate Size (Diameter)
9-3/16" (233mm)
Mounting Cutout Size
(Diameter)
7-7/8" (200mm)
Mounting Depth
4-1/4" (108mm)
Weight per Speaker
10 lb (4.5kg)

All features and specifications are subject to change without notice.

† The maximum recommended amplifier power rating will ensure proper system headroom to allow for occasional peaks. We do not recommend sustained operation at these maximum power levels.

* Dolby is a trademark of Dolby Laboratories.

DTS is a registered trademark of Digital Theater Systems, Inc.

Declaration of Conformity



We, Harman Consumer International
2, route de Tours
72500 Chateau-du-Loir
France

declare in own responsibility that the products described in this owner's manual are in compliance with technical standards:

EN 61000-6-3:2001
EN 61000-6-1:2001

Gary Marell
Harman Consumer International
Chateau-du-Loir, France 4/04

OWNER'S GUIDE		JBL	PRO SOUND COMES HOME™
PRODUCT LINE: JBL Home Theater In-Wall Series		JBL Consumer Products 250 Crossways Park Drive, Woodbury, NY 11797 8500 Balboa Boulevard, Northridge, CA 91329 516.255.4JBL (4525) www.jbl.com	
MODELS: HTI6, HTI8, HTI55 and HTI6C		NOTE: For new-construction applications, be sure to purchase the correct rough-in frame kit.	
DESIGN GOAL: Combine the superior performance of traditional JBL loudspeakers with the convenience of in-wall installation.		© 2004 Harman International Industries, Incorporated	
TWEETER TYPE: Pure-titanium dome with EOS™ waveguide, and swivel mount		JBL is a registered trademark of Harman International Industries, Incorporated.	
WOOFER TYPE: Polymer-coated aluminum cone with rubber surround		Part No. 406-000-05033	
CROSSOVER NETWORK: Straight-Line Signal Path™ (SSP)		H A Harman International Company	
PROFESSIONAL REFERENCE: Studio Monitor			

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>