



Style of product may vary from picture

PRODUCT DIMENSIONS

| | INCHES | CENTIMETERS |
|----------------|---------------|-------------|
| A | 30 in | 76.2 in |
| B | 24 in | 61.0 in |
| C | 51 7/8 ± 1/16 | 131.8 ± 0.1 |
| D | 24 in | 61.0 in |
| E | 28 1/2 ± 1/16 | 72.4 ± 0.1 |
| F | 52 15/16 | 134.5 |
| G | 29 3/4 | 75.6 |
| H ¹ | 25 1/2 | 64.8 |
| J | 4 - 10 | 10.2 - 25.4 |

MODEL SKUs

JMW8530DAB
 JMW8530DAQ
 JMW8530DAS
 JMW8530DAW

NOTES:

1. Excluding door handle.
2. 1 1/4" Diameter Conduit Access Hole. Hole must be cut as close to corner of cabinet as possible.
3. 5/8" plywood floor (must support 310 pounds).
4. Do not block air intake slots along bottom of oven.
5. Installed combo wall oven overlaps the cut out 15/16" (2.4 cm) at the top and 1/8" (.3 cm) at the bottom. This must be taken into consideration when locating cutout if installed unit is to be centered in the cabinet.
6. These appliances have been designed in accordance with the requirements of various safety agencies and comply with the maximum allowable wood cabinet temperatures of 194° F. If these appliances are installed with cabinets that have a lower working temperature than 194° F, discoloration, delamination or melting may occur.

Electrical requirements: Provide for 120/240 or 120/208 VAC, 60 Hz.

Seeserial plate on front of unit for power requirements

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>