

KM-5050 Specifications

BASIC SPECIFICATIONS:

| | |
|----------------------------------|--|
| Configuration: System Plus | Workgroup Multifunctional with Standard Network Print/Color Scan and optional Fax/Network Fax/IFax. Standard 500 x 2 Paper Drawers 200 Sheet Multi-Purpose Tray. Standard Duplex. Optional Dual Scan Document Processor. Optional Finishing and Paper Handling. |
| Resolution: | 600 x 600 DPI Resolution / 256 Levels, Fast 1200 Print Mode |
| System Memory: | Standard 512MB RAM, upgradeable to 1GB; Standard 80GB HDD |
| Magnification: | Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom |
| Electrical Requirements: | 120V, 60Hz, 11.5A |
| Dimensions: | 23.6"W x 25.4"D x 29.3"H |
| Weight: | 188 lbs |
| Max Monthly Volume: | 200,000 Pages Per Month |

OUTPUT SPEEDS:

| | |
|-------------------|--|
| Warm-Up Time: | Within 30 Seconds, Program During Warmup, Auto Start |
| First Copy Out: | 3.5 Seconds |
| Pages Per Minute: | 50 Letter, 26 Legal, 26 Ledger |

PAPER SUPPLY:

| | |
|---------------------------|---|
| Standard Paper Sources: | Dual 500 Sheet Drawers, 200 Sheet MPT, Auto Tray Selection / Switching, Add Paper While Running |
| Drawer Paper Size: | 5.5" x 8.5" - 11" x 17" |
| MPT Paper Size: | 5.5" x 8.5" - 11" x 17" |
| Std / Max Paper Capacity: | 1,200 / 4,200 |
| Paper Weight: | 13-28 lb Bond via Paper Drawers, 13 lb Bond -110 lb Index via MPT |
| Input Materials: | Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes |

DUPLEX UNIT:

| | |
|--------------------------|---------------------------------|
| Duplex Type ¹ | Standard Embedded Stackless |
| Paper Size: | 5.5" x 8.5" - 11" x 17" |
| Paper Weight: | 17 - 20 lb Bond |
| Duplex Modes: | Standard 1:2, 2:2, Book: 2, 2:1 |

COPY FUNCTIONS:

| | |
|----------------------|--|
| Control Panel: | Color Wide Touch Screen Interface |
| Imaging Modes: | Text, Photo, Text / Photo, Auto, Manual, ECO |
| Continuous Copy: | Up to 999, Auto Reset to 1 |
| Document Box: | Custom Box, Job Box, Media Box, Fax Box (with optional Fax System) |
| Additional Features: | Network/Local Authentication, Auto Magnification and Paper Select, Job Build, Job Finish Notice, Status Queue, Continuous Scan, Booklet Mode, Book Mode, Combine Image, Covers, Erase Mode, Image Rotate, Image Reverse, Interrupt, 50 Job Programs, Margin Shift, Mirror Image, Page Numbering, Memo Mode, 1,000 Management Codes, XY Zoom, Auto Centering, Help Guidance |

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: DP-710

| | |
|-----------------------|---|
| Type: | Dual Scan Document Processor (DSDP) |
| Acceptable Originals: | 5.5" x 8.5" - 11" x 17", Mixed Size Processing |
| Capacity: | 100 Sheet DSDP / 50 Letter Size Originals Per Minute (Monochrome) |
| Paper Weight: | 13 - 42 lb Bond |
| Dimensions / Weight: | 22.4"W x 20.7"D x 5.9"H / 29 lbs |

FINISHER: DF-710

| | |
|-----------------------|---|
| Stack Capacity: | Main Tray (A): 3,000 Sheets; Sub Tray (B): 200 Sheets, Sub Tray (C): 50 Sheets |
| Paper Size: | Main Tray (A): 8.5" x 11" - 11" x 17"; Sub Tray (B): 5.5" x 8.5" - 11" x 17"; Sub Tray (C): 8.5" x 11", 5.5" x 8.5" |
| Paper Weight: | 12 lb Bond - 110 lb Index |
| Staple Capacity: | 50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 3 Positions: Top Left, Bottom Left, Center |
| Saddle Stitch/Fold: | Optional Booklet Folder |
| Punch: | Optional 2 and 3 Hole |
| Dimensions / Weight: | 26.9"W x 22.2"D x 42.8"H / 121 lbs |

MULTI-TRAY: MT-710

| | |
|----------------------|---|
| Number of Trays: | 7 |
| Tray Capacity: | 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17" |
| Paper Weight: | 17 - 20 lb Bond |
| Dimensions / Weight: | 20.1"W x 15.7"D x 18.5"H / 22 lbs |

PUNCH UNIT: PH-5A

| | |
|------------------|---------------------------|
| Paper Size: | 8.5" x 11" - 11" x 17" |
| Paper Weight: | 17 lb Bond - 110 lb Index |
| Number of Holes: | 2 and 3 |
| Weight: | 6.6 lbs |

BOOKLET FOLDER: BF-710

| | |
|----------------------|--|
| Folding Capacity: | 1 - 16 Sheets |
| Stack Capacity: | 1-3 Sheets - 30 Booklets; 4-6 Sheets - 20 Booklets; 7-16 Sheets - 10 Booklets |
| Paper Size: | 8.5" x 11", 8.5" x 14", 11" x 17" |
| Paper Weight: | 16 lb Bond - 110 lb Index, Over 20 lb is one sheet only |
| Dimensions / Weight: | 25.9"W x 17.9"D x 10.5"H / 53 lbs |

SIMPLE FINISHER: DF-730

| | |
|-----------------------|---|
| Stack Capacity: | 8.5" x 11" - 1,000 Sheets; 8.5" x 14", 11" x 17" - 500 Sheets |
| Paper Size: | 8.5" x 11" - 11" x 17" |
| Paper Weight: | 17 - 34 lb Bond |
| Staple Capacity: | 30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 1 Position: Top Left |
| Dimensions / Weight: | 22.0"W x 20.7"D x 36.0"H / 55 lbs |

INTERNAL FINISHER: DF-720

| | |
|-----------------------|---|
| Stack Capacity: | 8.5" x 11" - 500 Sheets; 8.5" x 14", 11" x 17" - 250 Sheets |
| Paper Size: | 8.5" x 11" - 11" x 17" |
| Paper Weight: | 16 lb - 28 lb Bond |
| Staple Capacity: | 30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17" |
| Edge Staple Position: | 1 Position |
| Dimensions / Weight: | 12.2"W x 16.1"D x 6.3"H / 19.8 lbs |

LARGE CAPACITY TRAY: PF-750

| | |
|----------------------|-------------------------------------|
| Paper Capacity: | 3,000 Sheets |
| Paper Weight: | 16 - 28 lb Bond |
| Paper Size: | 8.5" x 11" |
| Dimensions / Weight: | 23.0"W x 23.6"D x 12.4"H / 50.7 lbs |

DUAL PAPER DRAWERS: PF-700

| | |
|----------------------|-------------------------------------|
| Paper Capacity: | 500 x 2 Sheets |
| Paper Weight: | 16 - 28 lb Bond |
| Paper Size: | 5.5" x 8.5" - 11" x 17" |
| Dimensions / Weight: | 23.0"W x 23.2"D x 12.4"H / 57.3 lbs |

CONNECTIVITY:

STANDARD NETWORK PRINT:

| | |
|-----------------------------|---|
| Controller: | Embedded PowerPC750 / 600 MHz Controller |
| Printer Memory: | Shared System Memory, Standard CF Card Slot (Type 1) |
| Supported PDL/Emulations: | PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer |
| Fonts: | 80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 1 Bitmap Font |
| Windows® OS Compatibility: | Windows® 95/98/Me/NT4.x/2000/XP/2003/Vista |
| Novell® OS Compatibility: | Novell NetWare® 3.x/4.x/5.x/6.x |
| Mac OS Compatibility: | OS 8.x/9.x/10.x |
| UNIX OS Compatibility: | Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) |
| Connectivity / Interface: | Standard 10/100BaseTX, Parallel IEEE1284, High Speed USB 2.0 |
| Host Interface: | Full Speed USB 2.0 |
| KUIO LV Expansion Slot (2): | Optional Fax System, IB-11 Serial Interface |
| Supported Protocols: | TCP/IP, IPX/SPX, AppleTalk, NetBEUI |
| Drivers: | KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers |
| Utilities: | KMnet Admin, KM-NET Viewer, KM-NET for Clients, PDF Direct Print, |
| Web Interface: | Kyocera Command Center |
| Additional Print Features: | Secure Printing, Print Job Storage, Box Printing |

STANDARD COLOR NETWORK SCAN:

| | |
|---------------------------|--|
| Scan Mode: | Color and Monochrome Scanning |
| Resolution: | 200, 300, 400, 600 DPI |
| Scan Speed: | 50 Originals per Minute (Monochrome); 25 Originals per Minute (Color) |
| File Formats: | Monochrome: PDF, TIFF; Color: PDF, JPG |
| Connectivity: | 10/100BaseTX |
| Supported Protocols: | TCP/IP |
| Scanning Functions: | Scan to Folder, Scan to E-Mail, Scan to FTP, TWAIN |
| Driver: | TWAIN Driver |
| Utilities: | Consolidated Address Book |
| Additional Scan Features: | Multi-Send, LDAP, Job Finish Notice, File Separation, File Name Entry, e-Mail Subject/Body Entry, Send and Print, Send and Store |

FAX/NETWORK FAX/IFAX: FAX SYSTEM (M)

| | |
|--------------------------|---|
| Compatibility: | Super G3 |
| Quick Scan Speed: | 1.2 SPP |
| Transmission Speed: | Approximately 3 Seconds per page |
| Modem Speed: | 33.6 Kbps with Auto Fallback |
| Data Compression: | JBIG, MMR, MR, MH |
| Fax Memory: | Shared System Memory |
| Driver: | KM Network Fax Driver |
| Utilities: | Consolidated Address Book |
| Additional Fax Features: | Multi-Send, Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax |

DOCUMENT CAPTURE AND MANAGEMENT OPTIONS

iTag; KYOCapture powered by AutoStore, KYOCapture Express

ADDITIONAL OPTIONS:

Data Security Kit (C), Job Separator (JS-710), Fax Backup Kit (BU-10), PDF Enhancement Kit (UG-30), Attachment Kit, 512MB Memory Board, Stand

Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2007 Kyocera Mita America, Inc.

Download from www.Somanuals.com. All Manuals Search And Download.



www.kyoceramita.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>