

SCARIFIERS

SF25 SERIES

25 - 50 HP — 66" 77"

- Cat. 1 hitch
- Four ripping depths
- Heat treated steel shanks
- Replaceable shank tips
- Rear hitch with floating top link for second implement



All Land Pride Scarifiers feature a 5/16" wall thickness on the shank tube for high tensile strength, and a 5/16" x 1" full length reinforcement bar.

The Land Pride Scarifier can work in unison with our 3-point 15 and 25 Series Landscape Rakes and Rear Blades.

www.landpride.com

Scarifier Specifications

Model/Number	SF2566	SF2577
Width (cm)	66" (168)	77" (196)
Working Width (cm)	60" (152)	72" (183)
Approximate Weight - lbs. (kg)	208 lbs.(94)	235 lbs.(107)
Horsepower Rating - engine	Up to 50 (37)	
Hitch Type	Cat. I	
No. of Shanks	6	7
Shank Type (mm)	3/4" x 2 1/2" (19 x 63.5) Heat Treated, Spring Steel Dimpled-On Tips	

Maximum HP Rating based on 2WD specifications.

Landscape Rake Specifications

Model/Series	LR0548	LR0560	LR0572	LR1560	LR1572	LR1584	LR1596	LR2572	LR2584	LR2596	LR3584	LR3596
Rake Width (cm)	48" (122)	60" (152)	72" (183)	60" (152)	72" (183)	84" (213)	96" (244)	72" (183)	84" (213)	96" (244)	84" (213)	96" (244)
Maximum HP Rating	25 HP			35 HP				50 HP			65 HP	
Hitch Type	Cat. 0 w/Cat. I Pins or Pull Type			Cat. I				Cat. I			Cat. I, II	
Angle/Position	5 Forward Up to 30°			5 Forward Up to 30°, 7 Rev. up to 45°				7 Forward Up to 45°, 5 Rev. up to 45°			9 Forward Up to 60°, 5 Rev. up to 60°	
Offset (cm)	N/A			N/A				N/A			45° Swing 24" (61) Offset Manual or Hydraulic	
No. of Teeth	26	34	40	30	36	42	48	36	42	48	42	48
Teeth Spacing (mm)	1 3/4" (44.45) Centers			2" (50.8) Centers				2" (50.8) Centers			2" (50.8) Centers	
Teeth Material	High Carbon Spring Steel			High Carbon Spring Steel				High Carbon Spring Steel			High Carbon Spring Steel	
Tooth Size (cm)	1/4" x 3/4" (0.64 x 1.91)			5/16" x 1" (0.79 x 2.54)				5/16" x 1" (0.79 x 2.54)			5/16" x 1" (0.79 x 2.54)	
Rake Height (cm)	12" (30.48)			16 1/2" (41.91)				16 1/2" (41.91)			16 1/2" (41.91)	
Appx. Wt.-3 Pt. lb (kg)	98 (44)	113 (51)	123 (56)	241 (109)	270 (122)	291 (132)	316 (143)	328 (149)	352 (160)	377 (171)	460 (209)	483 (219)
Options	98 (44)	115 (52)	123 (56)	Dual Gauge Wheels 13" x 4" x 6" and 13" x 6.5" x 6" *Flip-Down Grader Blade				Single Gauge Wheel 8" x 4" x 4.8" Dual Gauge Wheels 13" x 4" x 6" and 13" x 6.5" x 6", *Flip-Down Grader Blade Hydraulic Angle Cylinder			Single Gauge Wheel 8" x 4" x 4.8" Dual Gauge Wheels 13" x 4" x 6" and 13" x 6.5" x 6" *Flip-Down Grader Blade	

*Flip-down grader blade must be used in conjunction with dual gauge wheels. Maximum HP Rating based on 2WD specifications.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>