

INSTALLATION INSTRUCTIONS FOR PART 95-8904B

INSTALLATION INSTRUCTIONS FOR PART 95-8904B

APPLICATIONS
SUBARU
LEGACY & OUTBACK
2010
(non-NAV models)

95-8904B

KIT FEATURES


- DDIN radio provision
- ISO stacked provision
- Painted scratch resistant matte black

Note: Minor sub-dash modifications required. Part # 95-8903B does not require these modifications.



KIT COMPONENTS

• A) DDIN Trim Plate • B) DDIN Brackets



METRA. THE WORLD'S BEST KITS.™



1-800-221-0932



METRA. THE WORLD'S BEST KITS.™



1-800-221-0932



metraonline.com





95-8904B 95-8904B **NOTES TABLE OF CONTENTS DASH DISASSEMBLY** • 2010 SUBARU LEGACY/OUTBACK 1 **KIT ASSEMBLY** • 2010 SUBARU LEGACY/OUTBACK • DDIN / STACKED ISO HEAD UNIT PROVISION. . 2 *NOTE: Refer Also to the instructions included with the aftermarket radio. **KNOWLEDGE IS POWER** Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry. Log onto www.installerinstitute.com or call 800-354-6782 for more information and take steps toward a better tomorrow. Metra recommends MECP certified technicians certification program





95-8904B


95-8904B DASH DISASSEMBLY

2010 SUBARU LEGACY / OUTBACK

NOTES

1 Disconnect the negative battery terminal to prevent an accidental short circuit.

- Unclip and remove the radio trim panel including the a/c vents. (Fig. A)
- Remove (4) Phillips screws securing the factory radio.



Continue to Kit Assembly






95-8904B KIT ASSEMBLY


95-8904B


2010 SUBARU LEGACY / OUTBACK DDIN / STACKED ISO HEAD UNIT PROVISION

Locate the factory wiring harness in the dash. Metra recommends using the proper mating adapters from Metra and AXXESS to integrate your new radio. Re-connect the negative battery terminal and test the unit for proper operation.

- Attach the Double DIN brackets to the Double DIN trim plate. (Fig. A)
- Slide the Double DIN head unit or stacked ISO head units into the bracket/radio housing assembly and secure the Double DIN head unit or stacked ISO head units to the assembly using the screws supplied with the radio. (Fig. B)
- 4 Using an air saw, hacksaw, or similar cutting tool, cut to the inside of the radio's lower mounting holes, through the plastic and metal bracket. (Cut on the inside of each hole as close to the hole as you can get. If cut properly you may reuse two bottom factory screws, if not use self tapping screws on the bottom.) (Fig. C)
- Reassemble dash in reverse order of disassembly.







N		T	ES
	_		

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com