

800iX

Infrared Wireless Microphone System

The 800iX receiver features two wireless infrared channels to integrate with existing amplifiers in the classroom. With its alternate frequency group, it can also be added to our popular 850iR or 880iR systems to create a four-channel system.



< REAR VIEW

Specifications

Standard Carrier Frequencies (IR)	2.06/2.54 MHz
Signal-to-Noise Ratio	>73 dB
Frequency Response	100 Hz - 10 kHz
Output Level	500 mV
Individual Channel Outputs	Two (2) XLR
Mixed Channel Output	¼"
Dimensions (W x D x H)	17.3" x 8.5" x 1.75"

Features

- REDMIKE — small, lightweight, easy-to-use microphone
- Two-channel infrared receiver
- Alternate frequency group available – 4 compatible channels
- Independent microphone channel outputs
- Rack-mountable receiver

Contact us:

LIGHTSPEED TECHNOLOGIES

11509 SW HERMAN ROAD / TUALATIN, OREGON 97062

TOLL FREE: 1.800.732.8999 / PHONE: 503.684.5538 / FAX: 503.684.3197

WWW.LIGHTSPEED-TEK.COM

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>