

15" COLOR FLAT SCREEN CRT SURVEILLANCE SYSTEM

WITH INTERNET REMOTE VIEWING – VIEW UP TO 8 CAMERAS



The Lorex 15" Color Flat Screen CRT Dual Quad Observation system with Internet Remote Security Viewing provides flexibility and peace of mind. The system allows you to view up to 8 camera locations from across the hall or around the world. Utilize the 2-Page Quad option to view all 8 Cameras.



Network interface provides Remote Viewing and Recording without the requirement for a dedicated PC



Dual Quad Processor allows you to easily view 8 camera locations, 4 cameras simultaneously



Professional Grade, Weather Resistant Cameras with Day/Night IR Illumination

Features

- **Monitor:**
 - 15" TRUE FLAT Monitor with Network Interface for Remote Viewing over the internet*
 - Dual Quad Technology allows for viewing of up to 8 cameras
 - Convenient operation using remote control
 - 8 camera inputs (8 DIN, 8 BNC and Audio RCA)
 - Pixel-based Motion Detection
 - Multiple Viewing Modes (Full Screen, Sequencing, Quad & PIP)
 - Freeze-frame & digital Zoom
 - Sturdy Metal Cabinet
- **Cameras:**
 - Color Night Vision** camera with listen-in audio
 - 1/4" advanced CCD image sensor
 - 12 IR LEDs provide illumination up to 15 ft (4.5M)
 - Color video by day, automatically switches to B&W at night
 - Excellent low light sensitivity with built-in infrared LED
 - Professional Grade Weatherproof*** camera

Product Information

Model#:	SG15F6584
Description:	15" Color Flat Screen CRT Surveillance System with 4 Night Vision Cameras
UPC:	7-78597-56584-3
Package Weight:	44 lbs
Package Dimensions:	20.4in x 19.4in x 22in (W x D x H)
Package Cube:	4.19



IP SURVEILLANCE

SG15F6584

www.lorexcctv.com

15" COLOR FLAT SCREEN CRT SURVEILLANCE SYSTEM WITH INTERNET REMOTE VIEWING – VIEW UP TO 8 CAMERAS

Specifications

MONITOR:

Picture Tube	15" Full Flat Color CRT
Horizontal resolution	400 lines at center
Camera Capable	Up to 8
Quad Speed	30 fps
Camera Input	8 DIN / 8 BNC
Alarm Inputs / Outputs	8 / 1
Input signal	1V p-p at 75 ohms terminated
Power Source	Multi-voltage 100 ~ 240 V AC
Power Consumption	45 Watts
Operating Temperature	32° F - 104° F (0° C - 40° C)
Color	Metallic Gray



FRONT





BACK PANEL

CAMERA:



Image Sensor	1/4" Interline transfer type color CCD
Effective Pixels	512 H x 492 V (252k PIXELS)
Scanning System	525 Lines 2:1 Interlace
Resolution Horizontal	350 TV lines
Shutter Speed	1/60 ~ 1/10,000 sec
S/N Ratio	More than 48dB (AGC off)
Sync. System	Internal/Line Lock Mode
Min. Illumination	1.0 Lux (without LED) / 0.1 Lux (with LED)
White Balance	AWB
Video Output	VBS 1.0 Vp-p (75 ohms load)
Lens	Fixed Lens (6mm)
Power Supply	DC12V ±10% (from the monitor)
Power Consumption	100mA (without LED) / 180mA (with LED)
Operating Temp	14° F - 113° F (-10° C - +45° C)
Weather Proof Rating	IP44
Operating Humidity	90% RH max.

Dimensions

MONITOR:



CAMERA:



- * Broadband router is required
- ** Night Vision function designed to provide B&W video images in low light conditions. Object at our above the stated range may be partially obscured.
- *** Indoor/Outdoor cameras not recommended for direct exposure to rain, snow or water

Lorex Technology Inc.

300 Alden Road, Markham,
Ontario L3R 4C1
Canada.

3700 Koppers Street, Suite 100
Baltimore, Maryland 21227,
USA.

©2006 Lorex Technology Inc.
As our product is subject to continuous improvement, Lorex & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>