

BUSINESS AND HOME SECURITY

COLOR WIRELESS SURVEILLANCE SYSTEM WITH 2 INDOOR/OUTDOOR NIGHT VISION CAMERAS

EWT Enhanced Wireless Technology



WiFi
friendly

FEATURES

- 'EWT' Eliminates Interference From Most Household Devices
- Fast & Easy Installation - Plug Into any AC Outlet
- Receiver Connects to any TV/VCR/DVD Recorder
- Indoor / Outdoor Night Vision Camera
- Built-in Microphone for Listening Ability
- Camera Can be Battery Operated for True Portable Wireless Operation
- Up to 300ft Wireless Transmission Range*
- Night Vision Allows for Low Light Viewing up to 23ft (7m) from Cameras**
- Receiver Automatically Switches View Between Cameras
- Desktop, Wall and Ceiling Mountable

CONNECTS TO ANY TV



*Maximum open space transmission range. Actual range dependent upon building materials and other obstructions in path of wireless signal.

**IR illumination range of 23ft (7m) under ideal conditions. Objects at or beyond this range may be partially or completely obscured, depending on the camera application.

This product broadcasts over public airways and its video and audio signals may be intercepted without your consent.

 **LOREX**[®]

LW1012 Series

www.lorexctv.com

COLOR WIRELESS SURVEILLANCE SYSTEM WITH 2 INDOOR/OUTDOOR NIGHT VISION CAMERAS

SPECIFICATIONS

Camera

| | |
|--------------------------------------|---------------------------------------|
| Imaging Sensor: | 1/3" CMOS |
| CMOS Total Pixels: | 510 x 492 (NTSC) |
| View Angle: | 62° Diagonal |
| Minimum Illumination: | 3.0 Lux F1.5 (IR off) / 0 Lux (IR on) |
| Transmission Frequency: | 910 MHz - CH1, 920 MHz - CH2 (2CH) |
| Transmission Power: | 10 dBm |
| Modulation Type: | FM |
| Bandwidth: | 6.0 MHz |
| Power Source: | + 9V (DC) |
| Unobstructed Effective Range: | 330 ft. / 100 meters |
| Night Vision Range: | Up to 26 ft. / 8 meters |
| Dimensions: | 45x115x160mm / 1.8x4.6x6.3" |
| Weight: | 0.3lbs / 140 g |
| Operating Temperature Range: | 14° F ~ 104° F -10° C ~ 40° C |

Receiver

| | |
|--------------------------------------|------------------------------|
| Receiving Frequency: | 910-920 MHz - 2CH |
| Intermediate Frequency: | 32 MHz |
| Demodulation Type: | FM |
| Receiving Sensitivity: | -85 dBm |
| Power Supply: | 9V (DC) |
| Consumption Current: | 180 mA |
| Unobstructed Effective Range: | Up to 330 ft. / 100 m |
| Dimensions: | 70x120x83mm / 2.8x4.7x3.3" |
| Weight: | 0.3lbs / 120 g |
| Operating Temperature: | 14 F to 104 F/- 10 C to 40 C |
| Operating Humidity: | 85% RH |



PRODUCT INFORMATION

| | |
|----------------------------|---|
| UPC: | LW1012 - 7-78597-10120-1 LW1012F - 7-78597-10121-8 |
| Package Weight: | 1.3kg / 2.8lbs |
| Package Dimensions: | 298mm/11.73"(w) x 81mm/3.19"(d) x 235mm/9.25"(h) |
| Package Cube: | 0.005cbm / 0.20cft |

CONTENTS

| | |
|-----------------------|--|
| LW1012/LW1012F | 1 x Wireless Receiver 2 x Wireless Camera 3 x 9V DC Power Adapters 1 x RCA Video Output Cable 2 x Camera Battery Adapter Cable |
|-----------------------|--|



Lorex Technology Inc.

300 Alden Road, Markham,
Ontario L3R 4C1
Canada.

3700 Koppers Street
Baltimore, Maryland 21227,
USA.

©2008 Lorex Technology Inc.
As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE

2-18062008

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>