

Triple Input/Output Module

55000-588

- **ADM loop technology with Apollo/Discovery protocol**
- **3 line-monitored inputs and 3 dry relay outputs**
- **Setting of module address by means of address switch**
- **Integrated dual-isolator**
- **Status LED for each input and output**



Description

The addressable Module 55000-588 serves for the line-monitored integration of three contact detectors, such as manual call points, sprinkler system contacts or supervising contacts, into the bidirectional communication on the ADM loop with Apollo/Discovery protocol. Furthermore, it can be used to actuate external devices

by means of three relay outputs, each with a single-pole dry change-over contact, via the ADM loop.

The address is easily selected by means of a built-in DIL switch. Individual status LEDs indicate the condition of every input and output. The module has an integrated dual-isolator and is fitted into a plastic case.

Specifications

Operating voltage	Supply through loop voltage
Current consumption	approx. 3mA (quiescent)
Contact rating	1A/30VDC or AC
Ambient temperature	-20°C to +70°C
Dimensions L × W × H	250 × 175 × 75 (mm)
Colour	white
Weight	621g
Approval	VdS G202052
Order number	249077
Order name	Module 3xSurv.In 3xRel.Out/Apo 55000-588



Building Safety. Building Security.

LST

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>