

8x4 HD/SDI Video Router w/ AES Audio Follow

Model 862-XL804HD/2A



- ◆ **8 X 4, HD/SDI, With AES Audio Follow**
- ◆ **Local or Remote Control Panel**
- ◆ **AFV, breakaway, or X-Y Control**
- ◆ **Maximum of 256 Remote Panels**
- ◆ **RS-232 Serial Control, Standard**

The 800 Series Routing Switchers are wide bandwidth vertical interval switchers designed for professional video production facilities. The compact design of Link's routing switchers makes them an essential part of any facility.

Packaged in a 19" rack mountable chassis, the switchers are supplied with a single front-loaded power supply. An optional redundant power supply is available. High quality front panel push buttons are used for selection of inputs and outputs.

Remote control panels are interconnected with standard Ethernet 10Base2 single coax connections. RS-232 is provided through a standard D-sub connector. Panels can be set to control a single output bus or the entire matrix.

The 862-XL804HD is a high definition video router that supports HD/SDI and SDI.

The Link Switcher's flexibility is unmatched in the industry. Modular construction offers unique flexibility to the user, and provides an easy means of adding additional features or upgrading to digital modules. Power supplies are accessible from the front of the unit and may be easily installed or removed. Analog switchers can easily be upgraded to digital by adding field installable modules.

Industry standard BNC connectors are used for video inputs and removable 3-Pin connectors are used for stereo audio inputs and outputs.

Routers are available for analog video only, analog video with stereo audio follow, digital video only, and digital video with two-stream AES/EBU audio follow. **SUPPLIED WITH CONTROL PANEL WITH AUDIO BREAK-AWAY.**

The Link 8 x 4 HD/SDI routing system features:

- Modular Design – plug-in modules for video & audio. No active components on the frame.
- Two power supply slots are accessible from the front panel. One power supply is standard.
- A redundant power supply is available as an option.
- Detachable X-Y front panel control with Ethernet 10Base2 coax connection.
- HD/SDI video only models are available with analog or AES audio follow video.
- RS-232 control is standard.
- The 8X4 Video switcher is in a 1 RU and the audio follow in a 1 RU
-

Remote Mounting Kits for Control Panels

The supplied control panel for all switchers is shipped installed into the front of the main electronics chassis. The control panel can be removed from the electronics chassis in the field and installed into a remote mounting kit. The mounting kit hardware includes rack-mounting hardware for the control panel, a blank panel(s) that is installed onto the front of the electronics chassis, and a power supply. Order the appropriate rack mounting kit from the list below:

862-XL804HD/1A	8 x8 HD/SDI Video Only Routing Switcher	One Rack
862-XL804HD/3A	8 x8 HD/SDI Video Routing Switcher with Stereo Audio Follow Control Panel	One Rack
862-XL804HD/2A	8 x8 HD/SDI Video Routing Switcher with AES Audio Follow Control Panel	One Rack

8X8 HD/SDI Routing Switching Systems

Model 862-XL804HD/2A

SDI VIDEO INPUT:

Data Rate: 270,Mbps 360Mbps, 540Mbps, 1.4835 Gbps
 Data Type: SMPTE 259M, SMPTE 292M, SMPTE 344M, DVB-ASI
 Number Inputs: 8
 Input Cable Equalization: Automatic up to 300 meters@270 Mbps, 100 meters @ 1.485Gbps
 Video Level: 800 mV +/- 10%
 Impedance: 75 Ω Looping
 Coupling: DC
 Connector: BNC

AES AUDIO INPUT:

Connector Type: 110 Ohms balanced, AC coupled; Weco, 3-Pin Disconnect
 Impedance: 20K Ω
 Level: 0.5 to 10 V p-p
 CMR: \pm 25 V
 Return Loss: >15 dB @ 1.485Gbps

SDI VIDEO OUTPUTS:

Number: 4
 Connector: BNC
 Level: Unity Gain, \pm 0.1 dB
 Character Video: 90 IRE Units
 Return Loss: >15dB @ 1.485Gbps
 Impedance: 75 Ω \pm 1%
 Vertical Interval Switching: Line 6, NTSC
 Differential Gain: 0.10%, 10% to 90% APL
 Differential Phase: 0.10 $^\circ$, 10% to 90% APL
 Crosstalk: 62dB
 Propagation Delay: 5 nS, typical
 Hum and Noise: >60dB to 5 Hz
 DC Offset: <25mV
 Line Rate Tilt: <0.1%
 Field Rate Tilt: <0.1%
 SNR: -73dB
 Output Jitter: <25 ps

AES AUDIO OUTPUTS:

Signal Type: Balanced 110 Ohms , AC coupled
 Connector Type: Weco, 3-Pin Disconnect
 Impedance: 110 Ohms
 Level: 4 V p-p
 Jitter: \pm 0.5ns p-p (+input jitter)

ENVIRONMENTAL:

Temperature: 0 $^\circ$ to 50 $^\circ$ C ambient
 Humidity: 10%/90% non-condensing
 Power: 9.5 VAR
 AC Voltage: 120/240 VAC \pm 10%, 50/60Hz

MECHANICAL:

Height: 1.75 inches
 Width: 19 inches
 Depth: 9.25 inches
 Weight: 9lbs



LINK ELECTRONICS, INC. 9 2137 Rust Avenue 9 Cape Girardeau, MO 63703-7668
 Phone 573 334 4433 9 FAX 573 334 9255

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>