

Input/Output Module

55000-847

- **ADM loop technology with Apollo/Discovery protocol**
- **One line-monitored input and one relay output with two dry contacts**
- **Setting of module address by means of address switch**
- **Integrated dual-isolator**
- **Status LEDs for input and output**



Description

The addressable Module 55000-847 serves for the line-monitored integration of contact detectors, such as manual call points, sprinkler system contacts or supervising contacts, into the bidirectional communication on the ADM loop with Apollo/Discovery protocol. Furthermore, it can be used to actuate external devices by means of a relay output with two dry change-over

contacts, via the ADM loop. In addition to the monitored input and the relay output, the module has an opto-coupled input for monitoring an external voltage.

The address is easily selected by means of a built-in DIL switch. Status LEDs indicate the condition of input and output. The module has an integrated dual-isolator and is fitted into a plastic case.

Specifications

Operating voltage	Supply through loop voltage
Current consumption	approx. 1.5mA (quiescent)
Contact rating	1A/30VDC or AC
Ambient temperature	-20°C to +70°C
Dimensions L x W x H	150 x 90 x 48 (mm)
Colour	white
Weight	240g
Approval	VdS G201032
Order number	249076
Order name	Module 1xSurv.In 1xRel.Out/Apo 55000-847



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>