

Thermal Max Detector

ECO1004T

- **Addressable conventional technology**
- **Alarm temperature 78°C**
- **Individual detector addressing by means of optional address module**
- **Optional connection of remote indicator**
- **Function testable with Remote Test Unit ECO1000RTU**



Description

The Thermal Max Detector ECO1004T recognises a maximum temperature of 78°C as sign of fire. It complies with Class BS and can be used up to a room height of 6m.

Addressable conventional technology is used for alarm transmission to the fire detection control panel. By

means of the Address Module NG58-1, each detector can be addressed individually.

A test activation of the detector can be carried out using the Remote Test Unit ECO1000RTU. The detector can be attached to various detector bases and it can be protected against theft.

Specifications

Operating voltage	Supply through the detector line voltage
Current consumption	typ. 75µA (quiescent)
Alarm temperature	typ. 78°C
Operating temperature	max. +60°C
Ambient temperature	-30°C to +70°C (continuous operation)
Relative humidity	5 – 95% (no condensation)
Dimensions ø × H	102 × 40.5 (mm)
Colour	white
Weight	70g
Approval	VdS G202042
Order number	242047
Order name	Thermal Max Detector/Conv./1000/SS ECO1004T



Building Safety. Building Security.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>