

Ionisation Smoke Detector

GI-55000-217

- **Addressable conventional technology**
- **Individual detector addressing by means of optional address module**
- **Optional connection of remote indicator**
- **Flat design**
- **Sealed electronics**



Description

The Ionisation Smoke Detector GI-55000-217 was developed for the safe detection of a wide range of smoke aerosols. The modern design of the ionisation chamber allows to reliably evaluate the characteristics of fire. The dual chamber principle with measurement and reference chamber ensures the automatic compensation of environmental impact.

Addressable conventional technology is used for alarm

transmission to the fire detection control panel. By means of the optional Address Module NG60-1, each detector can be addressed individually. With that, the activated detector can also be safely identified directly on the control panel.

The detector can be attached to various bases and it can be protected against theft.

Specifications

Operating voltage	Supply through the detector line voltage
Current consumption	typ. 28µA (quiescent)
Ambient temperature	-20°C to +60°C
Relative humidity	0 – 95% (no condensation)
Radioactive compound	Am241
Dimensions ø × H	100 × 42 (mm)
Colour	white
Weight	102g
Approval	VdS G200075
Order number	240027
Order name	Ionisation Smoke Detector/Conv./65/Apo GI-55000-217



Building Safety. Building Security.

LST

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>