


Micro Stick Switches

Type: **EVQWH**




■ Features

- External dimensions: 6.1 mm×6.5 mm, height 2.05 mm
- High operability: Tactile feedback ensured in all five operating directions
- Ready for embossed taping and reflow soldering.

■ Recommended Applications

- Operation switches for menu scrolling and confirmation for portable electronic equipment (Mobile phones, Digital cameras, and PDAs)

■ Explanation of Part Numbers




■ Specifications

Electrical	Rating	20 mA 15 Vdc	
Mechanical	Operating force	Push	2.7 N±1.0 N
		Leaning	1.4 N±0.8 N *Note1
	Travel	0.15 mm ^{+0.2} / _{-0.1} mm	
	Leaning operation angle	5 °±2 °	
Endurance	Operating life	300000 cycles min.	
Temperature range	-20 °C to +70 °C		
Minimum Quantity/Packing Unit	1200 pcs. Embossed Taping (Reel Pack)		
Quantity / Carton	6000 pcs.		

* Note1 : Leaning operation is that attach switch with ø8 knob and push edge of knob from upper side.


■ Dimensions in mm (not to scale)




Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

Mar. 2008

■ Dimensions in mm (not to scale)



■ Circuit Diagram



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>