

EXECUTIVE™



Withstanding The Test Of Time!

- Finds satellites on its own
- Works with ALL receivers.
- No Data Port required.
- Comes with dual-output LNB.
- Available with either an 18" or 24" dish face.



- Operational Temperature Range of -40°F to 145°F.
- Rugged design and all-aluminum construction.
- Fast, quiet two-axis motion (Elevation & Azimuth).
- Simple, two-button "Find and Stow" operation via the Nomad 2™ Controller.

MotoSAT's™ flagship satellite television system is available with either an 18-inch or 24-inch reflector to deliver performance you can count on!

The Executive™ stationary automatic satellite system holds the industry record for providing continuous service, for the most years, of any automatic satellite system in the industry today. It has set a benchmark that has been unsurpassed. Its ability to remain the leader speaks for itself. When coupled with the Nomad 2™ controller, it truly is the most sought after combination. The Executive™ system has the ability to provide service to DirecTV™, Dish Network™ or Bell ExpressVu™. It can be ordered with either an 18-inch dish, or a 24-inch dish for extended range. It offers the highest gain of any system available today. Stowing to a mere 10 inches in height for traveling, it is hardly noticeable on top of your RV. MotoSAT's™ trademark soft blue glow is proudly displayed on this remarkable system. For the user wanting reliability, style and performance, the Executive™ is the system to have. It truly has withstood the test of time!



www.MotoSAT.com || 800.247.7486 || Sales@MotoSAT.com

THE EXECUTIVE™ IS POWERED BY
NOMAD 2



UNIVERSAL DVB CONTROLLER

INTERFACE:

Two-button "Find and Stow"

TUNER:

DVB [Digital Video Broadcast] Tuner

DIMENSIONS:

10" long, 7" wide, 1.25" tall

WEIGHT:

2.5 lbs.

CONTROLLER VOLTAGE:

12 volt 4 amp DC

EXECUTIVE™ TECHNICAL SPECIFICATIONS

CABLING

SUPPLIED INSTALLATION CABLE:

30' 9-conductor 22 AWG control cable
30' RG6 coaxial signal cable

MOUNT CABLING:

Mount comes pre-wired for two line outputs

ENVIRONMENT

ON SATELLITE WIND OPERATIVE RANGE:

45 mph

STOWED WIND SURVIVABILITY:

140 mph

OPERATIONAL TEMPERATURE RANGE:

-40 F° to 150 F°

MAINTENANCE PORT

PROGRAM I/O:

Serial Interface for software upgrades
Optional program module available upon request

Ask Your Local **MotoSAT** Dealer:



MOTORS

MOVEMENT FUNCTION:

Elevation, Azimuth

MOTOR VOLTAGE:

12 volt 1.2 amp DC maximum draw at search

REFLECTOR SPECIFICATIONS

MOVEMENT:

2 axis motor drive [elevation, azimuth]

ANTENNA DIMENSIONS:

18" x 20" or
24" x 26.5" effective area (elliptical)

DIMENSIONS

18" DIMENSIONS

STOWED

10" tall, 19" wide, 35" long

WEIGHT

35 lbs.

24" DIMENSIONS

STOWED

10" tall, 25" wide, 38" long

WEIGHT

35 lbs

 **MotoSAT™**
MOBILE SATELLITE SYSTEMS

www.MotoSAT.com || 800.247.7486 || Sales@MotoSAT.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>