

New Holland LM5000 Series Telehandler Specifications



LM5040 LM5060 LM5080

| MODEL | LM5040 | LM5060 | LM5080 |
|---|---------------------------------------|-----------------------|--|
| PERFORMANCE | | | |
| Max. lift height, ft. (m) | 20.0 (6.1) | 23.0 (7.0) | 31.5 (9.6) |
| Max. lift capacity, lbs. (kg) | 7700 (3500) | 8800 (4000) | 7250 (3300) |
| Lift capacity to full height, lbs. (kg) | 7700 (3500) | 6600 (3000) | 4400 (2000) |
| ENGINE | | | |
| Model | CNH NEF Tier III-F4BE0484F | | |
| Engine power, HP (kW) | 120 (88) | 120 (88) | 120 (88) |
| Displacement, cu. in. (L) | 275 (4.5) | 275 (4.5) | 275 (4.5) |
| Aspiration | Turbocharged / intercooled | | |
| DRIVELINE | | | |
| Powershift transmission, F/R | 4 / 3 | 4 / 3 | 4 / 3 |
| Max speeds in gears: | | | |
| 1 - mph, (kph) | 3.1 (5.0) | 3.1 (5.0) | 3.1 (5.0) |
| 2 - mph, (kph) | 6.6 (10.7) | 6.6 (10.7) | 6.6 (10.7) |
| 3 - mph, (kph) | 13.2 (21.3) | 13.2 (21.3) | 13.2 (21.3) |
| 4 - mph, (kph) | 23.0 (37.2) | 23.0 (37.2) | 23.0 (37.2) |
| Service brakes | Hydraulic wet disc, 4 discs per wheel | | |
| Parking brake | Mechanical driveline disc | | |
| Selectable 3-mode steering | Front wheel, crab, 4-wheel | | |
| HYDRAULICS | | | |
| Cab models | Load sensing piston pump, 37 GPM | | |
| ROPS model | | | Gear pump, 34 GPM |
| Pressure, PSI (Bar) | 3550 (245) | 3550 (245) | 3550 (245) |
| Aux. boom hydraulic circuit | Standard | Standard | Standard |
| TIRES AVAILABLE | | | |
| | 17.5LR 24 15.5R 25 | 17.5LR 24 15.5R 25 | 17.5LR 24 15.5R 25 (cab only) 13.00 x 24 (ROPS only) |
| DIMENSIONS w/ 17.5 tires | | | |
| Length, no attachment, ft. (m) | 15.7 (4.79) | 16.2 (4.95) | 16.7 (5.08) |
| Overall width, in. (mm) | 95 (2400) | 95 (2400) | 95 (2400) |
| Overall height, in. (mm) | 97 (2470) | 97 (2470) | 97 (2470) |
| Ground clearance, in. (mm) | 16.5 (420) | 16.5 (420) | 16.5 (420) |
| Wheelbase, in. (mm) | 117.7 (2990) | 117.7 (2990) | 118.5 (3010) |
| Turn radius over tires, ft. (m) | 11.3 (3.4) | 11.3 (3.4) | 11.3 (3.4) |
| Cab width, inside, in. (mm) | 39 (985) | 39 (985) | 39 (985) |
| Weight, approx., lbs. (kg) | 15,875 (7200) | 16,300 (7400) | 17,500 (7950) |

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>