

New Holland MZ-H Zero-Turn-Radius Mower Specifications



MZ16H MZ17H MZ18H MZ19H

MODEL	MZ16H	MZ17H	MZ18H	MZ19H
ENGINE				
Horsepower, hp (kW)	16 (11.9)	18 (13.4)	18 (13.4)	19 (14.2)
Make	Briggs & Stratton	Kohler Command	Briggs & Stratton	Kawasaki
No. of cylinders	1	1	1	2
Cooling system	Air			
Fuel capacity, gal. (L)	2 (7.6)	5 (18.9)	2 (7.6)	5 (18.9)
Full pressure lubrication	Standard			
Starter key w/safety interlock	Standard			
Air cleaner, dual element	Standard			

DRIVE SYSTEM

Type	Dual Hydrostatic: Two pumps each drive a separate motor at each wheel			
Max speed, forward, mph (kph)	6.0 (9.6)	7.0 (11.3)	6.0 (9.6)	7.0 (11.3)
Max speed, reverse, mph (kph)	3.0 (4.8)	3.4 (5.5)	3.0 (4.8)	3.4 (5.5)
Implement clutch	Electric			

BRAKES

Service Brake	Hydrostatic Dynamic Braking			
Parking Brake Lock	Automatic Engagement with steering levers in neutral			Manual, LH lever

ELECTRICAL

Voltage	12			
Charging System (amps)	9	15	16	13
Battery	260 cca			
Headlights	N/A	Optional	Optional	Optional

OPERATOR STATION AND CONTROLS

Steering	Dual padded lever hydrostatic with hydraulic dampening			
Front Casters	Double yoke			
Armrests	Standard			
Cup Holder	Standard			
Storage Bin	Standard			
Seat Type	Contoured, high back, adjustable fore and aft			
Footrest	Adjustable	N/A	Adjustable	N/A

WHEELS AND TIRES

Front Casters	10 x 4, 4-ply			
Rear	18 x 7.5-8, 4-ply	18 x 7.5-8, 4-ply	18 x 8.5-8, 4-ply	18 x 10.5-10, 4-ply

DIMENSIONS, in. (cm)

Length, overall	72.6 (184.4)	77.5 (196.9)	72.6 (184.4)	77.5 (196.9)
Width, overall				
with deck deflector down	50.7 (128.8)	60 (152.4)	55 (139.7)	65 (165.1)
with deck deflector up	46.0 (116.8)	49 (124.4)	46.6 (118.4)	58 (147.3)
Height, overall	39 (99.1)	40 (101.6)	39 (99.1)	41 (104.1)
Wheelbase	47.6 (120.9)	52.1 (132.3)	47 (119.4)	52.1 (132.3)
Turning Radius, inside rear wheel	Zero degrees			
Net weight, estimated, lb. (kg)	516 (234)	641 (290)	535 (243)	680 (309)

MOWER DECKS (optional mulching kits available)

42 in. side discharge	Standard	—	—	—
44 in. side discharge	—	Standard	—	—
48 in. side discharge	—	—	Standard	—
52 in. side discharge	—	—	—	Standard
Spindles	2	3	3	3
Anti-scalp gauge wheels	Standard			

New Holland MZ-H Zero-Turn-Radius Mower Specifications



MZ16H MZ17H MZ18H MZ19H

MODEL	MZ16H	MZ17H	MZ18H	MZ19H
ATTACHMENTS & ACCESSORIES				
2-bag grass catcher (6 cu. ft.)	Optional	—	—	—
2-bag vacuum grass catcher	—	Optional	Optional	—
48-inch front blade	Optional	—	Optional	—
56-inch front blade	—	Optional	—	Optional
Front lights	—	Optional	Optional	Optional
Smooth-tread front tires			Optional	

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>