

New Holland P1000 Series Air Cart Specifications



P1030 P1040 P1050 P1060

MODEL	P1030	P1040
Capacity, bu. (l)	280 (9866)	330 (11628)
Compartments	Two	
Splits, bu. (l)	169/118 (5955/4158)	186/142 (6554/5004)

DIMENSIONS

Ground clearance, in. (m)	.25 (0.64)	
Height, ft. in. (m)	14' 11" (4.3)	15' 3" (4.65)
Overall width, ft. in. (m)		
Single wheels	12' 6" (3.81)	
Dual wheels	16' 8" (5.08)	
Tow-behind length, ft. in. (m)	25' 4" (7.72)	
Tow-behind weight (empty), lb. (kg)	10,013 (4546)	10,052 (4569)
Tow-between length, ft. in. (m)	26' 4" (8)	
Tow-between weight (empty), lb. (kg)	10,013 (4546)	10,052 (4569)

TIRES

Front caster	Dual	
(on tow-behind model only)	22.5 L x 16.1 STII tires	
Rear axle, in. (m)	30.5L x 32, 12 ply AWT single tire @ 120 (3.05) tracking width	
Valves	Single-/double-shoot	
Primary lines	Up to 8	
Fan drive	Hydraulic dual fan	
Meter drive system	Mechanical ground drive	
Fill auger, in. (cm) x ft. (m)	10" (25.4) x 19' (5.8)	
	Steel cupped flighting	

MODEL	P1050	P1060
Capacity, bu. (l)	380 (13390)	430 (15153)
Compartments	Three	
Splits (tow between), bu. (l)	169/93/118 (5955/3277/4158)	186/102/142 (6554/3594/5004)
Splits (tow behind), bu. (l)	118/93/169 (4158/3277/5955)	142/102/186 (5004/3594/6554)

DIMENSIONS

Ground clearance, in. (m)	.25 (0.64)	
Height, ft. in. (m)	14' 11" (4.55)	15' 3" (4.65)
Overall width, ft. in. (m)		
Single wheels	12' 8" (3.86)	
Dual wheels	16' 2" (4.93)	
Tow-behind length, ft. in. (m)	28' 3" (8.61)	
Tow-behind weight (empty), lb. (kg)	10,900 (4955)	11,090 (5040)
Tow-between length, ft. in. (m)	29' 4" (8.94)	
Tow-between weight (empty), lb. (kg) est.	10,900 (4955)	11,090 (5040)

TIRES

Front caster	Dual	
(on tow-behind model only)	22.5 x 16.1 STII tires	
Rear axle, in. (m)	30.5L x 32, 12 ply AWT single tire @ 120 (3.05) tracking width	
Valves	Single-/double-/triple-shoot	
Primary lines	Up to 8	
Fan drive	Hydraulic dual fan	
Meter drive system	Mechanical ground drive	
Fill auger, in. (cm) x ft. (m)	10" (25.4) x 19' (5.8) steel cupped flighting	

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>