

New Holland T7000 Series Tractor Specifications



T7030 T7040 T7050 T7060

MODEL	T7030	T7040	T7050	T7060
ENGINE				
Gross engine horsepower, hp (kW)	165 (123)	180 (134.2)	195 (145.4)	210 (156.6)
Rated PTO, hp (kW)	135 (100.7)	150 (111.9)	165 (123)	180 (134.2)
Rated speed, rpm	2200			
Power boost @ 1900 rpm				
(PTO & transport modes), hp (kW)	35 (26)	35 (26)	35 (26)	25 (19)
Cylinders/displacement, cu. in. (L)	6 / 411 (6.75)			
Number of valves	24			
Aspiration	Turbocharged/intercooled			

ELECTRICAL

Standard alternator, amp/volt	150/12
Battery capacity (1 battery), CCA	1300

TRANSMISSION

18x6 Power Command™ full powershift	Standard
Creeper with additional 10F/6R	Optional
19x6 Power Command, 31 mph (50 kph) max speed	Optional
19x6 Power Command economy transmission	Optional
PTO – standard (reversible shaft), in. (mm)	540/1000 rpm, 1-3/8 (35)
PTO – optional, in. (mm)	1000 rpm, 1-3/4 (45)

AXLES

Standard rear diameter, in. (mm)	4-1/8 (105)
Rear axle length – standard, in. (mm)	112 (2485)
Rear axle length – optional, in. (mm)	98 (2489) or 119 (3023)
Standard FWD axle w/ TerraLock™	Standard
SuperSteer™ FWD axle w/ TerraLock	Optional
TerraGlide™ active suspended axle w/ TerraLock	Optional
FWD tread adjustability, in. (mm)	60-88 (1524-2235)
Wheelbase (MFD), in. (mm)	113.6 (2884)

HYDRAULICS

Hydraulic type	Closed center load sensing
Rear remote options	3 or 4 mechanical, 3 to 5 electrohydraulic
Main/implement pump flow – std./opt., gpm (L/min)	32.0 (120) / 39.6 (150)
Steering and services pump flow, gpm (L/min)	17 (66)
Total tractor hydraulic flow – std./opt., gpm (L/min)	49.0 (186) / 56.6 (216)
3-point hitch category	Cat. II / IIIN
3-point hitch lift capacity, lb. (kg)	12,787 (5800) / 15,873 (7200)

CAPACITIES

Fuel tank, U.S. gal. (L)	116 (440)
Engine oil, U.S. qt. (L)	16 (15)
Hydraulic fluid, U.S. gal. (L)	26.5 (100)

HORIZON™ CAB W/ HI-VISIBILITY PANEL

Glass area including hi-visibility panel, sq. ft. (m²)	63 (5.85)
Sound level, dBA	70

SHIPPING WEIGHT

Std MFD w/ 18.4R42 & front weight bracket, lb. (kg)	15,708 (7125)
Height to top of cab, 18.4R42, in. (mm)	119.7 (3040)
Height to top of exhaust, 18.4R42, in. (mm)	122.6 (3114)

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>