

PYLE[®] PRO

PYD2400U 4 channel professional mixer



OWNER'S
MANUAL

owner's manual

IMPORTANT SAFETY INSTRUCTIONS

1. **Read Instructions** — All the safety and operating instructions should be read before the appliance is operated.
2. **Retain Instructions** — The safety and operating instructions should be retained for future reference.
3. **Heed Warnings** — All warnings on the appliance and in the operating instructions should be adhered to.
4. **Follow Instructions** — All operating and use instructions should be followed.
5. **Water and Moisture** — The appliance should not be used near water -for example, near a bathtub, washbowl, kitchen sink, laundry tub, swimming pool, or a wet basement.
6. **Ventilation** — The appliance should be situated so that its location or position does not interfere with its proper ventilation. For example, the appliance should not be situated on a bed, sofa, rug, or similar surface that may block the ventilation openings: or placed in a built-in installation, such as a bookcase or cabinet that may impede the flow of air through the ventilation openings.
7. **Heat** — The appliance should be situated away from heat sources such as radiators, heat registers, stoves, or other appliances (including amplifiers) that produce heat.
8. **Power Sources** — The appliance should be connected to a power supply only of the type described in the operating instructions or as marked on the appliance.
9. **Grounding or Polarization** — Precaution should be taken to insure that the grounding or polarization means of an appliance is not defeated.
10. **Power-Cord Protection** — Power supply cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them, paying particular attention to cords at plugs, convenience receptacles, and the point at which they exit from the appliance.
11. **Cleaning** — The appliance should be cleaned only as recommended by the manufacturer.
12. **Power Lines** — An outside antenna system should not be located in the vicinity of overhead power lines or other electric light or power circuits, or where it can fall into such power lines or circuits. When installing an outside antenna system, extreme care should be taken to keep from touching such power lines or circuits as contact with them might be fatal.
13. **Nonuse Periods** — The power cord of the appliance should be unplugged from the outlet when the appliance is to be left unused for a long period of time.
14. **Object and Liquid Entry** — Care should be taken so that objects do not fall and liquids are not spilled into the enclosure through openings.
15. **Carts and Stands** — If the appliance is used with a cart or stand, the cart or stand should be a type recommended by the manufacturer.
An appliance and cart combination should be moved with care. Quick stops, excessive force, and uneven surfaces cause the appliance and cart combination to overturn.
16. **Mounting** — The appliance should be mounted only as recommended by the manufacturer.
17. **Damage Requiring Service** — The appliance should be serviced by qualified service personnel when:
 - A. The power-supply cord or plug has been damaged.
 - B. Objects have fallen into, or liquid has been spilled into the appliance enclosure.
 - C. The appliance has been exposed to rain.
 - D. The appliance has been dropped, or the enclosure damaged.
 - E. The appliance does not appear to operate normally or exhibits a marked change in performance.
18. **Service** — The user should not attempt to service the appliance beyond that described in the user's operating instructions. All other servicing should be referred to qualified personnel.
19. **Overloading** — Do not overload wall outlets and extension cords as this can result in a risk of fire or electric shock.
20. **Replacement Parts** — When replacement parts are required, be sure the service technician has used replacement parts specified by the manufacturer or have the same characteristics as the original part. Unauthorized substitutions may result in fire, electric shock or other hazards.
21. **Safety Check** — Upon completion of any service or repairs to this appliance, ask the service technician to perform safety checks to determine that the appliance is in proper operating condition.



<p>WARNING: To reduce the risk of fire or shock hazard, do not expose this product to rain or moisture.</p>	<p>This symbol is intended to alert you to the presence of un-insulated dangerous voltage within the products enclosure that might be of sufficient magnitude to constitute a risk of electric shock. Do not open the products case.</p>
<div style="display: inline-block; text-align: center; background-color: black; color: white; padding: 2px 10px;">CAUTION</div> <p>RISK OF ELECTRIC SHOCK DO NOT OPEN</p>	<p>This symbol is intended to inform you that important operating and maintenance instructions are included in the literature accompanying this product.</p>
<p>CAUTION: To reduce the risk of electric shock, do not remove cover or back. No user-serviceable parts inside. Refer servicing to qualified personnel.</p>	

Your PYLE PRO Series Performance Mixer

is a sophisticated control center, perfect for mixing sound from multiple playback sources such as microphones tuners, CD players, turntables or the audio outputs from a VCR.

This mixer is ruggedly constructed for home or professional use.

Wide range volume controls, permit you to adjust sound levels accurately to achieve just the right mix for playing through your speakers system or for recording.

Please read this manual thoroughly before you attempt to set up and use the mixer.

It contains a range of suggestions and instructions to insure safe usage.

Set up and used properly, you can expect years of trouble-free service from this product.

Input/Output Features

Power Supply

Plug the included power cord into the mixer first while the power is switched off, then plug the AC power cord into a proper power outlet.

Voltage Switch

This mixer has selectable input voltage from 110V/60Hz (the standard in USA and CANADA) to 220V/50Hz (for EUROPEAN operation). Please make sure the switch is in the proper position before operating, otherwise severe damage will result not cover by the warranty. Please also replace the fuse with proper rating in this situation (see the fuse rating of F 500mA 250V printed at power Inlet).

Output Jacks


To connect mixer to a receiver or amplifier - choose to use cables with either XLR-type or RCA plugs.

Booth Output Jacks

To connect the mixer to a second receiver or amplifier powering speakers in the DJ booth or in a remote location.

Record Output Jacks

To connect the mixer to a tape deck for recording the mixed program.



PHONO Stereo Inputs

For using a turntable with a magnetic cartridge.

Ground Screw

To connect ground wire from turntable, to eliminate the system hum.

MIC 2-MIC 5 Microphone connectors

Permits you to connect balanced or unbalanced low impedance microphone with 1/4" plug.

Stereo Line Inputs

Let you connect most high-level audio sources, such as CD players, tape deck, tuner or VCR.

Channel Input Selector
Lets you choose the input source to play for each channel.

Channel Gain Controls
Lets you adjust the gain of each input source.

MIC 1 Combo Input Jack
For connecting a balanced or unbalanced low impedance microphone with XLR-type or 1/4" plug.

MIC 1 Level Control
Lets you Control the MIC level as they enter the mix.

Effect Assign
Allows you to choose which channel (MIC, Line or phono) will be sent to the effects section, either one or all channels can be selected at once.

3-Band Equalizer
Allows you to tailor the mixer output to suit your taste or performance environment. Each frequency range can be cut or boost by up to 10 dB.

MIC 1 Tone Controls
Permit adjustment of the high and low of MIC 1 signal.

MIC Talkover Switch
Allows you to lower the level of the input sources so you can talk them using the DJ MIC.

Channel Assign Switch
Lets you select the Input source to be mixed by the Crossfade Slider Control.

Crossfader Slider Control
Allows you to smoothly switch between the input sources assigned to channel A and Channel B, it is replaceable.

Channel Level Slider Controls
Allow fingertip control of all sound mixing and fading.

Channel CUE Switch
Allows you to monitor the selected audio input source and prepare it prior to mixing it in.

EFX On/Off Selector
To select the effect section on or off.

DRY/WET Control
Adjusts the mix between the signal being sent from the effect assigned channel (DRY) and the signal coming from the effect section (WET).

Power Switch
Power off the mixer before making any connections.

Dual VU Meter
Indicates the levels of Left and Right Master Channels.

Master Balance Control

Master Level Control
Lets you control mixer's overall volume level.

Booth Level Control
Lets you control mixer's overall BOOTH volume level. If you set up remote speaker or DJ booth monitors.


Headphone Level Control

CUE EFX On/Off Switch
Allows you to monitor the effect in headphones before to mix it in using DRY/WET control.


Headphones Jack
Accepts headphones with 1/4" plug.

Headphone CUE/PGM Control
Allows you to listen simultaneously or separately to the CUE material or the active program.

EFFECT Selector
Let you to choose between the 16 different built in effects.



Connection Diagram:



This mixer permits connection of up to thirteen (13) audio input sources, including five microphones. Such a system might include, for examples:

Five Microphones
 Three Turntables
 Five CD players

Five Microphones
 Three Turntables
 Two CD Players
 Three Cassette Decks

Effects:

This mixer features 10-effect DSP module with 16 presets that including multiple kinds of reverb, flanger, chorus/room, rotary speaker, and vocal cancel (allowing you to remove the lead vocals from the song).

PLATE REVERB

Allows you to simulate a highly reflective reverb room sound, it is an artificial reverb that uses a plate of metal.

HALL REVERB

Allows you to simulate a longer reverb in a concert hall.

ROOM REVERB

Allows you to simulate a short reverb in a medium studio room.

VOCAL CANCEL

Allows to remove lead vocals from many stereo recordings.

ECHO

Allows you to simulate a 125ms delay effect for vocals and guitars (DELAY 1) and/or a 190ms delay effect for percussive arpeggios (DELAY 2).

CHORUS STEREO

Allows you to simulate layers of true stereo chorus.

FLANGER

Allows you to simulate a tunnel or jet plane type of sound that similar to the CHROUS effect except it modulates the delayed signal over s shorter period.

AUTO WAH

Allows to add automatically opens and close a “wah-wah” effect similar to a guitar “wah” pedal.

CHORUS REVERB

Allows you to simulate layers of true stereo chorus with room reverb.

AUTO PAN

Allows to simulate automatically pan the sound from the left speaker to the right speaker at a pre-determined tempo.

Limited Warranty

All PYLE PRO products are carefully constructed and tested before shipment. Units purchased in the USA are warranted to be free of defects in material and workmanship for one (1) year from the date of purchase. This warranty is limited to the original retail purchaser of the mixer.

Should the unit fail due to factory defects in material or workmanship, your unit will be repaired or replaced at the sole discretion of PYLE.

To obtain warranty service, you must first call our Consumer Return Hotline at (718) 236-6948 to obtain a Return Authorization Number. This R.A. # must appear on the outside of your package and on all paperwork relating to your return.

When returning the unit to us for warranty service, it must be carefully packed and shipped, prepaid, to:

R.A.#: _____
PYLE PRO Service Center
1600 63rd Street
Brooklyn, NY 11204

You must also include the following items with your return:

- A copy of your sales receipt or other proof of purchase
- A brief letter, indicating the problem you are experiencing with the product
- Include in your letter your return address, daytime phone number and R.A. number
- Also include a check or money order for \$20.00 for return shipping, handling and insurance, or provide your Visa/MC number with expiration date.

Our obligation under this warranty is limited to the repair or replacement of the defective unit when it is returned to us prepaid. This warranty will be considered void if the unit was tampered with, improperly serviced or subject to misuse, neglect or accidental damage.

▼ Please complete warranty card, detach and return ▼

Place
Stamp
Here



Specifications

PYD2400U

Input Sensitivity/Impedance

MIC 1.5 mV/600 Ohms Balanced
Phono 1-3 3.0mV/50K Ohms
Line 1-5 150 mV/27K Ohms

Output Level

Master 2.0 V/10K Ohms
Booth 2.0 V/10K Ohms
Record 150 mV/10K Ohms

Frequency Response 20Hz - 20kHz +/- 3 dB

S/N Ratio (at 1 kHz)

Mic 55 dB/1.5mV input
Phono 65 dB/3.0mV input
Line 70 dB/150.0mV input

Distortion

Mic 0.50%
Phono 0.13%
Line 0.05%

Tone Control

Treble 10kHz; +10/-10dB
Mid 1KHz; +10/-10dB
Bass 100Hz; +10/-10dB

Talkover Attenuation .. -16dB

Power Source AC 115V/230V, 50/60Hz

Dimensions, inches (mm)

WxHxD 19 x 3 x 7 (482 x 76.8 x 178)

Weight, lbs (kg) 8.38 (3.8)

**Specifications are typical; individual units might vary.
Specifications are subject to change and improvement without notice.**

▼ Please complete warranty card, detach and return ▼

Thank you for purchasing this PYLE product. To activate your warranty, please mail this card within 10 days.

warranty registration card

PYLE PRO MIXERS

Name _____

Address _____

City, State ZIP _____

Model No. _____

Serial # (if available) _____

Date of Purchase _____

Purchased at:

- Music Products Store Sound Contractor/Installer Mail Order
 Catalog Merchandiser Other _____

www.pyleaudio.com

**7 - Pyle Pro Mixer PYD2400U
Owner's Manual**

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>