

Philips
RG6 coaxial cable

25 ft

F-Type Male to Male

SWV2239



Ensure a reliable connection

with this F type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

RG6 coaxial cable
25 ft F-Type Male to Male

Specifications

Packaging

- EAN/UPC/GTIN: 6 09585 12279 6
- Quantity: 1
- Gross Weight: 0.310 kg
- Tare Weight: 0.010 kg
- Net Weight: 0.300 kg
- Length: 26.70 cm
- Width: 15.90 cm
- Height: 4.50 cm

Inner Carton

- EAN/UPC/GTIN: 1 06 09585 12279 3
- Quantity: 6
- Gross Weight: 11.180 kg
- Tare Weight: 0.320 kg

- Net Weight: 10.860 kg
- Length (cm): 55.40 cm
- Width (cm): 46.50 cm
- Height (cm): 41.60 cm

Outer Carton

- EAN/UPC/GTIN: 2 06 09585 12279 0
- Quantity: 36
- Gross Weight: 1.860 kg
- Tare Weight: 0.050 kg
- Net Weight: 1.810 kg
- Length (cm): 34.60 cm
- Width (cm): 21.00 cm
- Height (cm): 15.90 cm

SWV2239/17

Product highlights

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Bare copper shielding

Bare copper shielding protects against signal loss.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.



Issue date 2007-11-30

Version: 1.0

12 NC: 8670 000 26027
UPC: 6 09585 12279 6

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>