

Philips
RG6 coaxial cable

12 ft

F-Type Male to Male

SWV2236



Ensure a reliable connection

with this F type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS
sense and simplicity

RG6 coaxial cable
12 ft F-Type Male to Male

Specifications

Packaging

- EAN/UPC/GTIN: 6 09585 12282 6
- Quantity: 1
- Gross Weight: 0.190 kg
- Tare Weight: 0.010 kg
- Net Weight: 0.180 kg
- Length: 17.10 cm
- Width: 14.60 cm
- Height: 6.10 cm

Inner Carton

- EAN/UPC/GTIN: 1 06 09585 12282 3
- Quantity: 6
- Gross Weight: 1.130 kg
- Tare Weight: 0.050 kg

- Net Weight: 1.080 kg
- Length (cm): 28.20 cm
- Width (cm): 19.00 cm
- Height (cm): 16.80 cm

Outer Carton

- EAN/UPC/GTIN: 2 06 09585 12282 0
- Quantity: 72
- Gross Weight: 13.610 kg
- Tare Weight: 0.650 kg
- Net Weight: 12.960 kg
- Length (cm): 60.30 cm
- Width (cm): 50.80 cm
- Height (cm): 40.60 cm

SWV2236/17

Product highlights

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Bare copper shielding

Bare copper shielding protects against signal loss.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-08-08

Version: 1.0.6

12 NC: 8670 000 26032
UPC: 6 09585 12282 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>