

Philips
Scart cable

1,5 m

Component Video / Stereo Audio

SWV6662



Enjoy the ultimate viewing experience

Take your components to optimum performance. This top of the line cable offers the best connection for transferring audio/video signals between components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimize signal
- 4-Cut connectors for secure connections
- Split center pin for better signal transfer
- 99.97% Oxygen-Free Copper (OFC)

Protects against signal loss

- 100% aluminum shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper braided reinforced aluminum shielding

Easy installation

- Color coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability

- Heavy-duty brass shell for extended durability
- Super pliable jackets for outstanding flexibility

PHILIPS
sense and simplicity

Scart cable
1,5 m Component Video / Stereo Audio

Specifications

Inner Carton

- EAN/UPC/GTIN: 87 12581 31460 6
- Quantity: 2
- Gross weight: 1.54 kg
- Tare weight: .28 kg
- Net weight: 1.26 kg
- Length (cm): 35 cm
- Width (cm): 24.5 cm
- Height (cm): 27.5 cm

Outer Carton

- EAN/UPC/GTIN: 87 12581 31461 3
- Quantity: 4
- Gross weight: 4 kg
- Tare weight: .94 kg

- Net weight: 3.06 kg
- Length (cm): 50 cm
- Width (cm): 37 cm
- Height (cm): 29 cm

Packaging

- EAN/UPC/GTIN: 87 12581 31459 0
- Quantity: 1
- Gross Weight: .62 kg
- Tare Weight: .1 kg
- Net Weight: .52 kg
- Height: 12 cm
- Length: 33 cm
- Width: 25 cm

SWV6662/10

Product highlights

Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

4-Cut connectors

4-Cut connectors ensure secure connections between your component and your cable.

Split center pin

The split center pin allows for better signal transfer and an improved connection to the component inputs.

99.97% OFC solid conductor

99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

100% aluminum shielding

This protective layer of aluminum guards against electromagnetic interference for improved signal quality.

Twisted high purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Braided shielding

Copper braided reinforced aluminum shielding protects against signal loss and interference.

Heavy-duty brass shell

The heavy-duty brass shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Super pliable jackets

Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.



Issue date 2008-04-18

Version: 1.0.3

12 NC: 8670 000 26831
EAN: 87 12581 31459 0

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>