

Ordering Information

Catalog No.	Finish	Mounting	Lamps	Reflectors
23C39T4AL 23C39T4BK 23C39T4WH	Aluminum Black White	For use with Lytespan Radius, Basic and Advent Track. Not compatible with extension wands or slope ceiling adapters. For monopoint applications refer to spec sheet 6172.	39W T4 GU6.5 Base Ceramic Metal Halide	23MHRF, 23MHRS, 23MHRNF 23MHRFCCZ, 23MHRSCCZ, 23MHRNFCCZ REFLECTORS SOLD SEPARATELY

Features

- Track Attachment Fitting:** Locking lever for mechanical/ electrical connection.
- Brass Contact:** Extends for connection to second circuit (Advent track only).
- Horizontal Pivot:** Wireless stem profile with 365° horizontal rotation. Position may be locked using an allen key.
- Vertical Pivot:** 0-90° vertical adjustment with aiming indicator. **Position may be locked using an allen key.**
- Fixture Housing:** Die cast aluminum
- Ballast Housing:** Molded polycarbonate
- Safety Lens:** Tempered 1/8" glass. Meets or exceeds UL safety requirement for metal halide lamps.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Accessory Cartridge:** Hinged and captive; retaining ring included. Inside painted black to reduce glare.
- Safety Locking Lever:** Locks ballast housing to track.

Finish

All Painted finishes are baked enamel.

Accessories

Accessory Holder: Integral

Accessories: Accepts 1 snoot plus 2 lenses or 1 louver plus 1 lens.

When using 2 accessories, remove safety lens provided.

Lens: AF25, ADF25 Series

Louver: AL25HC

Reflector

Interchangeable reflectors available to allow for desired beam spread.
REFLECTORS SOLD SEPARATELY.

Electrical

Electronic Ballast
Input Voltage: 120V, 50/60Hz
Power Factor: .9
Input Power: 45W
Max. Input Current: 0.40A
ANSI Code: C(M)130
Do not use on dimming circuit.

Labels

UL, cUL

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • B0908


Aiming Angle:

L Beam length
W Beam Width
C Distance to center beam
D Distance
A Aiming Angle
FC Footcandles

L and **W** are the outer points where the candle power drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.

Lamp data shown is typical. Consult lamp manufacturers for availability and performance.

CBCP = Center Beam Candle Power.



Lamp	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	D	FC	L	W	D	C	FC	L	W	D	C	FC	L	W	D	C	FC	L	W
39W T4, 23MHRS		23356	9000	10'	234	1.7'	1.7'	8'	4.6'	237	1.9'	1.6'	3'	5.2'	324	2.1'	1.0'	4'	4.0'	516	1.4'	1.0'
				12'	162	2.1'	2.1'	10'	5.8'	152	2.3'	2.0'	4'	6.9'	182	2.9'	1.4'	5'	5.0'	330	1.8'	1.2'
				14'	119	2.4'	2.4'	12'	6.9'	105	2.8'	2.4'	5'	8.7'	117	3.6'	1.7'	6'	6.0'	229	2.1'	1.5'
				16'	91	2.8'	2.8'	14'	8.1'	77	3.3'	2.8'	6'	10.4'	81	4.3'	2.1'	7'	7.0'	169	2.5'	1.7'
39W T4, 23MHRNF		5011	9000	6'	139	2.7'	2.7'	6'	3.5'	90	3.6'	3.1'	2'	3.5'	157	4.2'	1.8'	2'	2.0'	443	1.9'	1.3'
				8'	78	3.5'	3.5'	8'	4.6'	51	4.8'	4.1'	3'	5.2'	70	6.2'	2.7'	3'	3.0'	197	2.8'	1.9'
				10'	50	4.4'	4.4'	10'	5.8'	33	6.0'	5.1'	4'	6.9'	39	8.3'	3.5'	4'	4.0'	111	3.7'	2.5'
				12'	35	5.3'	5.3'	12'	6.9'	23	7.2'	6.1'	5'	8.7'	25	10.4'	4.4'	5'	5.0'	71	4.7'	3.1'
39W T4, 23MHRF		3883	9000	6'	108	3.8'	3.8'	6'	3.5'	70	5.2'	4.4'	2'	3.5'	121	7.2'	2.5'	2'	2.0'	343	2.8'	1.8'
				8'	61	5.0'	5.0'	8'	4.6'	39	7.0'	5.8'	3'	5.2'	54	10.8'	3.8'	3'	3.0'	153	4.2'	2.7'
				10'	39	6.3'	6.3'	10'	5.8'	25	8.7'	7.3'	4'	6.9'	30	14.4'	5.0'	4'	4.0'	86	5.6'	3.6'
				12'	27	7.6'	7.6'	12'	6.9'	18	10.4'	8.7'	5'	8.7'	19	18.0'	6.3'	5'	5.0'	55	7.0'	4.5'

Note: For Champagne Bronze (CCZ), multiply FC values by 0.64. CCZ Champagne Bronze reflector "warms" the beam to 2700K.

Job Information	Type:
------------------------	--------------

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • B0908

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>