

A Division of Pride Mobility Products® Corp.



Specifications

WHEELS	Drive: 14" pneumatic
	Casters: 9" pneumatic (standard)
	8" or 9" solid (optional)
	Anti-tips: 4" solid
SUSPENSION	Sport Trac
MAXIMUM SPEED 1	Up to 5 mph 2 / 6 mph 3 / 8 mph 4
BRAKES	Intelligent Braking
	(electronic, regenerative disc brakes)
GROUND CLEARANCE 5	2.625"
TURNING RADIUS 5	23.5"
OVERALL SIZE ⁵	Length: 33" Width: 25.5"
SEATING	Synergy [®] Seat Adjustable Width: 10"-24" Adjustable Depth: 10"-24" TRU-Balance [®] 2 Power Positioning System Adjustable Width: 14"-20" Adjustable Depth: 14"-20" High-back Seat (24" x 24")
DRIVE TRAIN	Two-motor, rear-wheel drive
BATTERIES	Group 24 or Group 34
RANGE PER CHARGE ¹	Up to 20 miles
BATTERY CHARGER	Off-board, 8 amp (standard)
AVAILABLE ELECTRONICS	70 amp, PG VR2 70 amp, Q-Logic 100 amp, Q-Logic
WEIGHT CAPACITY	300 lbs. maximum (user weight)
BASE WEIGHT	144 lbs.
BATTERY WEIGHT	Group 24: 53.5 lbs, Group 34: 43 lbs.
SEAT WEIGHT	37 lbs. (Specialty Seat)
WARRANTY	Lifetime limited warranty on frame 2-year warranty on electronics

Features

- Easy operation results in a short learning curve
- Narrow 25.5" width and compact 33" length
- · Outstanding tight-space maneuverability
- Sport-Trac Suspension
- Powerful motors for aggessive performance and terrain-gripping torque
- 3-point seat mount for ease of adjustment and addition of optional components
- Easy rear access to batteries

Options

- Q-Logic Drive Control System
- Contoured seating w/ solid seat pan
- Synergy[®] seating system
- TRU-Balance[®] 2 power positioning system
- TRU-ComfortTM seating system
- Lap belt
- Flat-free tires
- Cup holder
- · Weather cover

- 8 mph high-speed motor package
- 70° swingaway footrests
- Swing-away joystick mount
- 80° heavy-duty leg rests
- Elevating leg rests
- Heel loops
- Oxygen tank holder
- · Cane/crutch holder
- Rear basket
- · Walker holder
- Saddlebag

Shroud Colors



drive motors

18-months limited warranty on

FOOTNOTES:

- Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure
- 2) Standard on Group 3
- 3) Standard on Group 4, Optional on Group 3
- 4) Optional on Group 3 & 4
- 5) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or -3 %.

(US) 866-800-2002 (Canada) 888-570-1113 www.quantumrehab.com



A Division of Pride Mobility Products® Corp.

Code Coverage

R4000 3S - SS	(Code: K0848)
R4000 3S - C	(Code: K0849)
R4000 3SP - SS	(Code: K0856)
R4000 3SP - C	(Code: K0857)
R4000 3MP - SS	(Code: K0861)
R4000 4S - SS	(Code: K0868)
R4000 4S - C	(Code: K0869)
R4000 4SP - SS	(Code: K0877)
R4000 4MP - SS	(Code: K0884)

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com