



Gigabit Switch

GS-5105M:

5-Port Gigabit Ethernet Mini Switch

Key Features

- Conforms to IEEE 802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T and IEEE 802.3x flow control standards
- Supports 10/100Mbps auto-detect half/full duplex and 1000Mbps at full duplex
- Supports TP interface auto MDI/MDI-X function for auto TX/RX swap
- Supports 802.3x flow control pause packet for full duplex
- LEDs to indicate: 10/100/1000Mbps, Link/Act. and Power Status

Overview

GS-5105 meets the demand for bandwidth as 5 port Desktop Gigabit switch. This desktop switch seamlessly integrates with the rest of the network through its auto-negotiating, non-blocking design. To break through the bottlenecks at the core of network, GS-5105 provides up to 10Gbps aggregate bandwidth and seamless migration and the most cost effect method for bringing high speed networking to the desktop

Easy Installation and Configuration

GS-5105M conforms to plug and play for easy installation and use. With diagnostic LEDs, network and port status can be easily monitoring and trouble-shooting. GS-5105M also build in wiring crossover on all ports allows connection to server or PC without worrying about cabling.

Technical Specifications

- **Standard compliance :**
 - IEEE 802.3 10Base-T Ethernet (twisted-pair copper)
 - IEEE 802.3u 100Base-TX Ethernet (twisted-pair copper)
 - IEEE 802.3ab 1000Base-T Ethernet (twisted-pair copper)
 - ANSI/IEEE 802.3 Auto-negotiation
- **MAC Address :** 8K
- **Network Interface :** 5 10/100/1000Mbps RJ-45 ports
- **Flow control :**
 - IEEE802.3x compliant for full-duplex
 - Back pressure flow control for half-duplex
- **Media :**
 - 10BASE-T: UTP Cat. 3, 4, 5 or up
 - 100BASE-TX: UTP Cat. 5 or up
 - 1000BASE-T: UTP Cat. 5 or up
- **Transmission Mode:** 10/100Mbps, full/half-duplex (Auto-sensing)
- **Transfer Rate:**
 - 10Mbps: 14880pps (64 Bytes Package)
 - 100Mbps: 148800pps (64 Bytes Package)
 - 1000Mbps: 1488000pps (64 Bytes Package)
- **Buffer Memory:** 112KB per unit
- **Switching Method :** Store & forward
- **Power Supply:** External Switching Power (DC 5V/2A)
- **Operation Temperature:** 0 to 50 °C
- **Operation Humidity:** 0% to 90%
- **Dimensions:** 27(H) x 159(W) x 102(D) mm
- **Complies with FCC Class A, CE Mark Approval**

Ordering Information

GS-5105M: 5 Port 10/100/1000M Gigabit Ethernet Mini Switch

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>