Runco proudly unveils its largest LCD flat panel, the Crystal Portfolio™ CX-70DHD. The Runco CX-70DHD is a native 1080p HD LCD that is ideal for rooms of distinction where a large screen size is desired, but where ambient light makes front projection difficult and the glare of a plasma screen simply unacceptable. Beyond its exceptional contrast, the CX-70DHD features ISF™ calibration for an optimal picture in the most challenging lighting conditions and the display's elegant black bezel matches any room décor.

Native Resolution:	1920 x 1080
Screen Size:	70.3 in. (diagonal)
Screen Aspect Ratio:	4:3, Letterbox, 16:9 Anamorphic, VirtualWide™
Available Aspect Ratios:	See DHD Controller Specs below
Image Area (W x H inches):	61.56" W x 34.86"H
DTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Contrast Ratio:	1500:1
ISF Settings:	Yes
Data/Graphics Compatibility:	Up to 1366 x 768
Inputs (from DHD Controller):	(1) RGB/Component (15-pin D-sub); (1) DVI with HDCP (1) RS-232 (9-pin D-sub female)
Power Requirements:	100-240V AC, 50/60Hz
Power Consumption:	720 W (1.5 watts in standby), maximum
Operating Environment:	40 to 95ºF (5 to 35ºC); 20-80% humidity (non-condensing)
Dimensions (without stand):	Width: 66.6 in. (1691 mm) Height: 39.8 in. (1011 mm) Depth: 5.84 in. (148 mm)
Weight:	158 lbs. (71.66kg)
Limited Warranty:	(2) Two years parts and labor from the date of shipment from Runco. RuncoCare™ and Runco RedCarpet™ plans are also available.
CX-70DHD Ships with:	Power Cord (US only, 15ft.), remote control unit with (2) AAA batteries, (1) one 20 foot RJ-11 to RJ-45 serial cable, (1) DVI (male) to HDMI (Female) adapter, rack-mount hardware for DHD Controller, Manual, Quick Start guide, (4) Four cable ties.

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.

Runco proudly unveils its largest LCD flat panel, the Crystal Portfolio™ CX-70DHD. The Runco CX-70DHD is a native 1080p HD LCD that is ideal for rooms of distinction where a large screen size is desired, but where ambient light makes front projection difficult and the glare of a plasma screen simply unacceptable. Beyond its exceptional contrast, the CX-70DHD features ISF™ calibration for an optimal picture in the most challenging lighting conditions and the display's elegant black bezel matches any room décor.

Runco DHD 3 Controller Specifications:

Aspect Ratios:	4:3, 16:9, Anamorphic, Letterbox, VirtualWide™, Cinema, Virtual Cinema™, Native
Video Standards:	NTSC, PAL, SECAM, ATSC
Inputs:	(1) Composite; (2) S-Video; (1) HD Video/Computer, R (Pr), G (Y), B (Pb), H, V – RCA connectors; (2) HD Video/Computer, R (Pr), G (Y), B (Pb), H, V, – BNC's; (1) HD Video/Computer – 15-pin D-Sub connector; (2) HDMI with HDCP
Output Resolution:	1080p
Output:	(1) HDMI, (1) RS-232
Communication Control Ports:	Discrete infrared remote Serial commands via RS-232 Front-panel controls
Screen Trigger/Masking Outputs:	(3) +12 VDC, each rated at 250 mA with overcurrent protection
Bandwidth:	170 Mega Samples per Second (MSPS)
Power Requirements:	100 – 240V AC (auto-sensing), 50/60 Hz, 40 watts
Operating Environment:	41°F – 104°F (5°C – 40°C), 0% – 85% Humidity (non-condensing)
Dimensions:	Width = 17.50 inches (444.5 mm) Depth = 11.19 inches (284.1 mm) Height = 3.75 inches (95.3 mm)
Weight:	15.5 lbs. (7.0 kg)
Included Accessories:	Rack mounting brackets
Regulatory Approvals:	Complies with FCC, CE C-Tick
Limited Warranty:	Projector: (2) Two years parts and labor from the date of shipment from Runco. RuncoCare™ and Runco RedCarpet™ plans are also available

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com