

General Purpose Laboratory Refrigerators & Freezers



GENERAL PURPOSE LABORATORY REFRIGERATORS

The Ideal +4°C & -20°C General Purpose Laboratory Refrigeration in Capacities from 21 to 61 cu. ft.

Designed for general purpose storage applications in clinical, life science, pharmaceutical, biotechnology, and industrial laboratories, this series of products offer :

- Microprocessor temperature control with LED readout and alarm functions.
- Large interiors with greater flexibility in cold storage
- Reliable heavy duty refrigeration systems for frequent door openings

SRR-23FD-MED
SRR-49FD-MED
SRR-23GD-MED
SRR-49GD-MED
SRR-72GD-MED



SRF-23FD-MED
SRF-49FD-MED



innovation
performance
reliability
support

p r e s e r v a t i o n

REFRIGERATORS-SOLID SWING DOORS

SRR-23FD-MED & SRR-49FD-MED

FEATURES / BENEFITS

- Stainless steel exterior (400 series) and interior (304 series) for long life and durability
- Microprocessor Temperature Control with LED readout and alarm functions
- Microprocessor Temperature Control Range -3° to +10°C
- Forced air circulation refrigeration system with automatic evaporator defrost
- Uniform digital temperature control
- Automatic interior lighting
- Heavy duty epoxy coated shelves per section mounted on stainless steel pilasters
- Humidity/Pressure relief valve
- Top mounted refrigeration system for superior performance
- Automatic condensate evaporator
- 5 inch casters are standard

SRR-23FD-MED



+4°C
21 cu.ft.

REFRIGERATORS-SOLID SWING DOORS

- High efficiency refrigeration system
- Controls can be set to initiate heated defrost cycle as required
- Door locks are standard
- 115 volts power requirement
- Utilizes environmentally friendly R134A refrigerant

ACCESSORIES

- Access Port
- Duplex Power Outlet
- Additional Epoxy Coated Shelf

SRR-49FD-MED



+4°C
40 cu.ft.

REFRIGERATORS-GLASS SWING DOORS

SRR-23GD-MED, SRR-49GD-MED, SRR-72GD-MED

FEATURES / BENEFITS

- Energy efficient triple pane glass doors
- Stainless steel exterior (400 series) and interior (304 series) for long life and durability
- Microprocessor Temperature Control with LED readout and alarm functions
- Microprocessor Temperature Control Range -3° to +10°C
- Forced air circulation refrigeration system with automatic evaporator defrost
- Uniform digital temperature control
- Automatic interior lighting
- Heavy duty epoxy coated shelves per section mounted on stainless steel pilasters
- Humidity/Pressure relief valve
- Top mounted refrigeration system for superior performance

SRR-23GD-MED & SRR-49GD-MED



+4°C
21 cu.ft.

+4°C
40 cu.ft.



p r e s e r v a t i o n

REFRIGERATORS-GLASS SWING DOORS

- Automatic condensate evaporator
- Hinged panel allows for easy servicing
- High efficiency refrigeration system
- Controls can be set to initiate heated defrost cycle as required
- 115 volts power requirement
- Utilizes environmentally friendly R134A refrigerant

ACCESSORIES

- Access Port
- Duplex Power Outlet
- Additional Epoxy Coated Shelf

SRR-72GD-MED



+4°C
61 cu.ft.

FREEZERS-SOLID SWING DOORS

SRF-23FD-MED & SRF-49FD-MED

FEATURES / BENEFITS

- Stainless steel exterior (400 series) and interior (304 series) for long life and durability
- Microprocessor Temperature Control with LED readout and alarm functions
- Microprocessor Temperature Control Range -23° to +10°C
- Forced air circulation refrigeration system with automatic evaporator defrost
- Uniform digital temperature control
- Automatic interior lighting
- Heavy duty epoxy coated shelves per section mounted on stainless steel pilasters
- Humidity/Pressure relief valve
- Top mounted refrigeration system for superior performance
- Automatic condensate evaporator

SRF-23FD-MED



-20°C
21 cu.ft.

FREEZERS-SOLID SWING DOORS

- 5 inch casters are standard
- High efficiency refrigeration system
- Controls can be set to initiate heated defrost cycle as required
- Door locks are standard
- 115 volts power requirement
- Utilizes environmentally friendly R404A refrigerant

ACCESSORIES

- Access Port
- Duplex Power Outlet
- Additional Epoxy Coated Shelf

SRF-49FD-MED



-20°C
40 cu.ft.

Specifications

REFRIGERATORS - SOLID SWING DOORS

Model Number: SRR-23FD-MED
 Internal Capacity/Volume: 21 cu. ft. refrigerator
 Microprocessor Temperature Control Range: -3°C to +10°C
 Exterior Dimensions: 29.1"W x 31.7"D x 79.25"H
 5 inch casters are standard
 (739mm x 805mm x 2019mm)
 Interior Dimensions: 24.4"W x 27.6"D x 56.3"H
 (620mm x 700mm x 1430mm)
 Refrigeration System: 1/4 HP compressor,
 R134A HFC "Green" refrigerant
 Door: 1 stainless steel swing door
 Interior Storage: 4 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 4.6A, NEMA 5-15P Plug
 Net Weight: 209 lbs. (95kg)

Model Number: SRR-49FD-MED
 Internal Capacity/Volume: 40 cu. ft. refrigerator
 Microprocessor Temperature Control Range: -3°C to +10°C
 Exterior Dimensions: 49.6"W x 31.7"D x 79.5"H
 5 inch casters are standard
 (1260mm x 805mm x 2019mm)
 Interior Dimensions: 44.9"W x 27.6"D x 56.3"H
 (1140mm x 700mm x 1430mm)
 Refrigeration System: 1/3 HP compressor,
 R134A HFC "Green" refrigerant
 Doors: 2 stainless steel swing doors
 Interior Storage: 8 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 6.3A, NEMA 5-15P Plug
 Net Weight: 440 lbs. (200kg)

REFRIGERATORS - GLASS SWING DOORS

Model Number: SRR-23GD-MED
 Internal Capacity/Volume: 21 cu. ft. refrigerator
 Microprocessor Temperature Control Range: -3°C to +10°C
 Exterior Dimensions: 29.1"W x 31.7"D x 79.25"H
 5 inch casters are standard
 (739mm x 805mm x 2019mm)
 Interior Dimensions: 24.4"W x 27.6"D x 56.3"H
 (620mm x 700mm x 1430mm)
 Refrigeration System: 1/4 HP compressor,
 R134A HFC "Green" refrigerant
 Door: 1 triple-pane full glass swing door
 Interior Storage: 4 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 4.2A, NEMA 5-15P Plug
 Net Weight: 209 lbs. (95kg)

Model Number: SRR-49GD-MED
 Internal Capacity/Volume: 40 cu. ft. refrigerator
 Microprocessor Temperature Control Range: -3°C to +10°C
 Exterior Dimensions: 49.6"W x 31.7"D x 79.25"H
 5 inch casters are standard
 (1260mm x 805mm x 2019mm)
 Interior Dimensions: 44.9"W x 27.6"D x 56.3"H
 (1140mm x 700mm x 1430mm)
 Refrigeration System: 1/3 HP compressor,
 R134A HFC "Green" refrigerant
 Doors: 2 triple-pane full glass swing doors
 Interior Storage: 8 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 8.6A, NEMA 5-15P Plug
 Net Weight: 440 lbs. (200kg)

Model Number: SRR-72GD-MED
 Internal Capacity/Volume: 61 cu. ft. refrigerator
 Microprocessor Temperature Control Range: -3°C to +10°C
 Exterior Dimensions: 74.8"W x 31.7"D x 79.25"H
 5 inch casters are standard
 (1900mm x 805mm x 2019mm)
 Interior Dimensions: 66.3"W x 27.6"D x 56.3"H
 (1430mm x 27.6mm x 1430mm)
 Refrigeration System: 1/3 HP compressor,
 R134A HFC "Green" refrigerant
 Doors: 3 triple-pane full glass swing doors
 Interior Storage: 12 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 7.6A, NEMA 5-15P Plug
 Net Weight: 528 lbs. (240kg)

FREEZERS - SOLID SWING DOORS

Model Number: SRF-23FD-MED
 Internal Capacity/Volume: 21 cu. ft. freezer
 Microprocessor Temperature Control Range: -23°C to +10°C
 Exterior Dimensions: 29.1"W x 31.7"D x 79.5"H
 5 inch casters are standard
 (739mm x 805mm x 2013mm)
 Interior Dimensions: 24.4"W x 27.6"D x 56.3"H
 (620mm x 700mm x 1430mm)
 Refrigeration System: 1/2 HP compressor,
 R404A HFC "Green" refrigerant
 Door: 1 stainless steel swing door
 Interior Storage: 4 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 6.5A, NEMA 5-15P Plug
 Net Weight: 209 lbs. (95kg)

Model Number: SRF-49FD-MED
 Internal Capacity/Volume: 40 cu. ft. freezer
 Microprocessor Temperature Control Range: -23°C to +10°C
 Exterior Dimensions: 49.6"W x 31.7"D x 79.5"H
 5 inch casters are standard
 (1260mm x 805mm x 2019mm)
 Interior Dimensions: 44.9"W x 27.6"D x 56.3"H
 (1140mm x 700mm x 1430mm)
 Refrigeration System: 1/2 x 2 ea. HP compressor,
 R404A HFC "Green" refrigerant
 Doors: 2 stainless steel swing doors
 Interior Storage: 8 adjustable, epoxy-coated wire shelves
 Electrical requirements: 115V, 60Hz, 13.2A, NEMA 5-15P Plug
 Net Weight: 440 lbs. (200kg)



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>