

SDC 8000 D

Conference and Information Systems | SDC 8000

Cat. No. 009412

General Description

The digital SDC 8000 D delegate unit is an ideal choice for both mobile and fixed conference systems. Its compact and elegant design harmoniously blends in with any conference room. The unit features a high-quality built-in loudspeaker, providing excellent sound at a pleasant volume. By pressing the Mic key, the conference participants can either switch on the microphone or signal their request to speak.



Technical Data

Frequency response	100 – 14,000 Hz
Pick-up pattern	cardioid
Headphone connector.....	3.5 mm mono (> 32 Ω)
Power supply.....	48 V DC
Power consumption.....	max. 3.7 W
Operating temperature	0 – 50 °C
Standards.....	IEC 849
Colour.....	Pantone Black 7C
Housing	ABS
Dimensions.....	150 x 80 x 185 mm
Gooseneck length	380 mm
Weight	620 g

Features

- Built-in high-quality loudspeaker (automatically muted when the microphone is switched on)
- Microphone on/off (request) key
- Gooseneck microphone with red LED ring
- Two RJ 45 sockets for connecting up to 15 units in one cable line
- Two 3.5 mm headphone jacks for headphones or induction couplers for the hearing impaired
- Two separate headphone volume controls
- Delivery includes: 1 SDC 8000 D Delegate Unit

Accessories

- RJ 45 conference bus cables, type 24 AWG, available lengths: 2 m, 3 m, 5 m, 10 m, 20 m, 50 m (Please note: Do not use standard Ethernet-AWG 26 cables!)
- HD 410-D, HD 1029 headphones

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>