

MIP3F Form Feed Printer

MIP3F Fixed Mount Friction Feed Printer

MIP3F Fixed Mount Friction Feed Printer

For in-vehicle use, this compact printer can also be mounted in a variety of locations. Its compact size makes it suitable for use in law enforcement and other mobile applications where single sheet or individual multi-part forms are used.

Easy Ribbon Changing

The 2 Million character cassette utilizes a reinker to achieve a compact size and provides consistent print quality throughout its life. A precision ribbon shield makes loading easy, quick and convenient.

Easy Paper Loading

To make paper loading fast and simple, the print mechanisms used in the MIP3X tractor feed printers is moved out of the way during paper loading, providing direct access to the tractors. Paper loading in the MIP3F friction feed unit is made simple by use of a paper guide where the form is easily slid into its print position.



Product Highlights:

- In-vehicle use.
- Mounted in a variety of locations.
- Suitable for use in law enforcement
- Single sheet or individual multi-part forms

MIP3F Form Feed Printer

Print Speed	288 cps @ 12 cpi
Print Method	serial impact
Resolution	NA
Character Density	10, 12, 15, 17 cpi
Standard Connectivity	RS-232 and Bluetooth; or RS-232 and Wireless Ethernet 802.11b; or RS-232 and USB; or RS-232 and Centronics parallel
Standard Emulation	IBM® Proprinter with Epson® Commands
Fonts	Pica, Elite, Proportional, Prestige, Quadro, Brougham, Gothic

Consumables	(Black) 2 million characters ribbon
STD Paper Handling	Open mechanism for easy paper loading on tractor units; insertion slot for friction drive unit.
Number of Copies	Original plus three copies
Forms Thickness	max thickness 0.014"
Paper Type	Continuous forms
Paper Size	Width 3-8.5 (76-216mm); Length 4 in. or more (102mm)

Physical Weight	5.3 lbs (2.4 kg)
PhysicalSize	5.4" x 15" x 4.3"
Power Voltage	12/24 VDC Nominal, 10.5 - 30 VDC
Compliance	Energy Star; Ozone-free; Class A of FCC Part 15B
Drivers	Windows XP, 2000, 98, 95, NT 4.0. Use the Windows resident Epson Compatible 9 Pin driver (Epson FX equivalent)
Temperature	14° to 104° F (-10° to 40° C); Storage: -22° to 158° F (-30° to 70° C)
Acoustic	NA
Warranty	One Year Return To Depot

Option 1	Stand with paper tray and mount - for vehicle wall; Stand with paper tray and mount - for vehicle shelf
Option 3	Cigarette Lighter Adapter
Option 3	A/C Universal Power Supply, 100-240 VAC, 50-60 Hz.
Options 4	replacement 12 V DC Cable

Available Configuration	MIP3F - RS232, Bluetooth MIP3F - RS232, 802.11 MIP3F - RS232, Parallel MIP3F - RS232, USB
--------------------------------	--



Genicom Printer Outlet
1-866-430-6202
www.tgprinteroutlet.com

Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2007 TallyGenicom, L.P.

Genicom Printer Outlet.Com
1-866-430-6202

Fax for a Quick Quote
817-430-6250

Choose Model:

MIP3F Form Feed Printer

Organization _____

Name _____

Phone (_____) _____ Fax Number (_____) _____

E-Mail _____

Address _____

City _____ State _____ Zip _____

Please indicate your specifications or requirements:

Additional Comments:

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>