

SHIBAURA

Lawn & Garden Tractor **GT161**
11kW(16PS)



Features

- 11kW(16PS)Engine.
- 48 inch mower deck.
- HST, hydrostatic transmission standard.
One foot controls everything during driving, speed variations, drives forward and reverse freely without clutching and conventional lever shifting.
- Most suitable constant speed control is maintained with speed lock levers.
Easy driving by steering control in open areas or transfer travelling. Safety features include release of speed lock by pressing brake pedals.
- Power steering system is available on GT161, as standard, giving impressive light control for added versatility.
- Adapting tilt handles and easily adjustable seat ramp for the most comfortable seat position.
- Sub transmission ensures faster transfer travelling and well suited operations working purposes of this class.
- Forward cooling air flow serves operator comfortably without warm air blow.
Clogged cut grass and dirt particles are quickly removed from air inlets on radiator from operator s seat.
- Sharp turning angle allows tighter cutting on verges and around trees and buildings.
- For further safety, engines do not start unless HST pedals are at neutral, mower clutch levers are at off and brake pedals at press. Engines are automatically stopped when operator leaves seat in drive with parking brake off.
- Electric Circuits are all off when safety switches effected, preventing battery discharge.
- Hydraulically controlled mower lifting up and down are made easily with finger tip lever control.
- Easier mower setting on and off adopting new rear link systems.
- Shaft drive to mower is employed for durability and less power loss.
- Fuel gauges standard for all models.
- Three blade mower cuts various grasses effectively and discharges debris smoothly.
No left-over cuttings as blade circles overlap one another.
- 10 stage height adjustment, from 25 through 108mm, makes cutting selection easier and most efficient.
- Improvements on mower gearboxes, spindle shaft bearings and antiscalp rollers.
- Electric hour meters employed.



Wide and Flat Floor



One Foot Control



Tilt Handle:Up

Tilt Handle:Down



Slide Seat:Forward

Slide Seat:Reverse

SPECIFICATIONS

Model		GT161	
Driving System		2-Wheel Drive	
Dimensions	Overall Length	mm	1910
	Overall Width	mm	990
	Overall Height	mm	1210
	Wheel base	mm	1265
	Tred	mm	770
	Front	mm	666 or 713
	Rear	mm	
Min. Ground Clearance		mm	160
Weight (less Mower)		kg	382
Engine	Model	E673	
	Type	Vertical, Water-Cooled, 3 cylinder Diesel	
	Displacement	cm ³	676
	Max. Output	kW(PS)/rpm	11(16)/3200
	Fuel Tank Capacity	litre	16
	Starting System	Electric starting (with cell starter)	
Tire	Battery	12V-28AH	
	Front	16×6.50-8	
	Rear	2.3×10.50-12	
Chassis	PTO Clutch	Belt Tension	
	Braking System	Mechanical Disc	
	Transmission	Hydrostatic	
	Steering	Power Steering	
Min. Turning Radius		mm	810
Travel Speed Range Forward		km/h	Range1 : 0~6.6 Range2 : 0~12.8
Min.~Max. Revers		km/h	Range1 : 0~3.3 Range2 : 0~6.4
Rear PTO		Option	
Mower	Model/Weight	MM48/88kg	
	Type	Belt Tension	
	Cutting Width	mm	MM48 : 1220
	Number of Blades	3	
	Cutting Height	mm	25~108
Cutting Height Adjustment		13 Stages	
Attachment	Fuel Gauge	Attached to all models	
	Seat Adjustment	Easily adjustable seat ramp	
	Seat Mount	Spring	

※The specifications are subject to change without notice.

 **SHIBAURA**

Ishikawajima-Shibaura Machinery Co.,Ltd.

Head Office : Harmony -Tower 11F

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>