

Options

Roof and Protective Net



Grass Collector



Scraper



Specifications

Model	SR525		
Dimensions			
Length	(mm)	2700(2970)	
Width	Mowing	(mm)	2900
	Transport	(mm)	2240
Height	(mm)	2040(include ROPS)	
Wheel Base	(mm)	1510	
Tread Width	Front	(mm)	1730
	Rear	(mm)	1045
Ground Clearance	(mm)	160	
Tires	Front	24×13.00—12 4PR	
	Rear	20×8.00—10 4PR	
Weight	(kg)	1300	
Engine			
Model	Shibaura N843L		
Type	Water-cooled, 4 cycle, diesel		
Cylinders	3		
Displacement	(cc)	1662	
Horsepower	[kW(hp)/rpm]	27.9(38)/2850	
Fuel Tank Capacity	(ℓ)	41	
Battery	75D26L		
Transmission			
Drive	Hydrostatic Transmission, 2 range High/Low. Automatic Four- Wheel Drive or Permanent Four- Wheel Drive		
Brake	Wet Disc		
Steering	Hydraulic Power Steering		
Travelling Range	Forward	2	
	Reverse	2	
Travelling Speed	Forward	(km/h)	L : 0~10.0 H : 0~17.1
	Reverse	(km/h)	L : 0~7.0 H : 0~11.9
Reel Mower			
Total width of cut	(mm)	2500	
Reel diameter	(mm)	Ø178	
Number of reel	9 Blade-Standard (7/11 Blade-Optional)		
Height of cut	(mm)	7~32	
Mowing Rate	(a/h)	183 (Mowing Speed 9km/h, Efficiency 0.8)	

Important information

● Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

※We reserve the right to discontinue models or change specifications without notice.



SHIBAURA EUROPE BV  
 Begonialaan 7  
 NL - 6851 TE Huissen  
 T. (0031) 026 326 9999  
 F. (0031) 026 326 9990  
 E. info@shibaura.com  
 www.shibaura.com

Catalog No. 2674 Printed in Japan

Lightweight 5 fairway mower

# SR525



Lightweight, Compact and High-performance  
 Fairway Mower



Lightweight and compact styling, excellent operator comfort and superb cutting performance. Low centre of gravity ensures stable performance over undulating ground, mechanical 4WD ensures excellent climbing capabilities without loss of power.

# SR525

Width of cut : 2500mm

## Safety Features


- Mower revolution stops when lifting up reel mower
- Engine stops when operator leaves seat



## Operator Comfort

Adjustable seat suspension, reclining seat and a tilt steering wheel ensure operator comfort.

Excellent visibility to reel mower



Tilting Steering Wheel

Adjustable Seat Suspension



Reclining Seat

Sliding Seat

## Maintenance made easy - Reduced Service Time

Access to all major components is made simple with tilting operator seat / platform and full bonnet opening. Radiator can be cleaned easy by opening the front screen and retractable shutter.



Low Emission Shibaura Diesel Engine  
Equipped with Shibaura diesel engine, complying with Tier 2 U.S. emission regulation.




Easy Operation  
Ergonomically designed controls for ease of use.



Divertor Valve  
All cutting units are fitted with diverter valves enabling the back lap of individual units.



Cutting Unit Adjustment  
Centre cutting units can be easily rotated and moved sideways to adjust the roller bracket position, cutting height and grass discharge cover.



Easy adjustment of cutting height



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>