

speco technologies®

Triplex Digital Video Recorder Family with Network/DDNS Video Server



DVR-4TL/160* • DVR-8TL/160* • DVR-16TL/160*

4 Channel Triplex MPEG-4 DVR • 8 Channel Triplex MPEG-4 DVR • 16 Channel Triplex MPEG-4 DVR

Features

EZ Record: set the number of days you want to record and the DVR takes care of the rest
EZ Copy: auto copy what you are playing onto a USB flash drive
EZ Set-Up: for quick Installation

- Free DDNS server for use with dynamic IP addresses
- MPEG-4 high quality compression, 5~10 times smaller than MJPEG
- Triplex operation enabling simultaneous live view or playback while continuing to record & network transfer
- Remote monitoring, recording, playback, change system settings and dome camera control via Ethernet and/or Internet
- Recording Rate: Up to 60pps
- 1 Channel in/out for audio recording
- USB 2.0 port for video clip exporting, supports USB ThumbDrive®
- Easy software upgrade via USB ThumbDrive®
- Multiple built-in dome camera protocol (through RS485): including Pelco D, Pelco P, AD422, Fastrax, DynaColor, JVC, Panasonic
- Automatic camera detection (Plug & Play)
- Digital Zoom 2 x 2 in live mode, playback
- Covert camera operation provides enhanced security and administrator control
- Dynamically programmable recording priority, motion detection, alarms, and scheduling, continuous
- Programmable call-monitor switching sequence
- Multiple language on-screen menus
- Password to secure installation authorization
- Network software supports static IP, DHCP, PPPoE and DDNS
- Network hardware supports 10/100M bps
- Dimensions: 2" (H) X 17 1/4" (W) X 16 1/8" (D)
- Weight: 18 lbs. with 1 HDD (HDD weighs 1 lb.)
- Power Consumption: Start up @ 80 Watts, Running @ 50 Watts
- Heat Dissipation: 2.85 BTU/Minute
- HDD size: 160GB, 320GB, 750GB
- Operating temperature: 32° F to 104° F
- Web-based remote software
- Remote control, rack ears & I/O connect all included

* Standard DVR comes with a 160GB HDD. Other configurations available up to 1.5TB internal

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

MPEG-4 TRIPLEX DVR

Specifications: 4, 8 or 16 Channel MPEG-4 Triplex Digital Video Recorders with 160GB HDD

	MODEL NAME	DVR-4TL/160	DVR-8TL/160	DVR-16TL/160	
Video	Operation System	Embedded (Linux)			
	Video Standard	NTSC/PAL			
	Video Operation	Triplex+ (Live, Record, Playback , Remote, and Internet access)			
	Resolution – Live Video	NTSC: 720 x 240 pixels			
	Input	BNC x 4, 1.0Vp-p/75 ohm	BNC x 8, 1.0Vp-p/75 ohm	BNC x 16, 1.0Vp-p/75 ohm	
	Outputs	Main Monitor	BNC x 1, 1.0Vp-p/75 ohm		
		Call Monitor	BNC x 1, 1.0Vp-p/75 ohm		
	Live Picture Refresh Rate	NTSC: 60 PPS			
	Digital Zoom	2 x 2 (Live & Playback)			
Camera Installation	Plug & Play				
Audio	Input	RCA x 1, Line-In			
	Output	RCA x 1, Line-Out			
	Recording Mode	Always Real Time Record, Synchronized w/ Video			
	Compression Method	ADPCM, G.726			
	File Size	8KB/Sec			
	Operation	Remote + VCR mode			
	Playback	Only for Video Original Speed			
Recording	Compression Method	MPEG-4 Advanced Simple Profile			
	Recording Mode	Continuous, Schedule, Alarm, Motion Detection			
	Resolution & Rate	NTSC	720x480: 30 pps 720x240: 60 pps		
		PAL	720x576: 25 pps 720x288: 50 pps		
Playback	Recording Quality	5 levels presets, adjustable			
	Image Size	2K to 20K Byte/picture			
	Storage Mode	Linear/Circular			
	Playback	Play, Stop, Pause, Rewind, Forward, Search			
	Playback Speed Adjustment	Yes 1X, 2X...32X			
	Retrieve	Date/Time, Event			
Storage	Built-in Storage	X1 ATA 133 / UDMA 133 IDE, HDD			
	Export	USB 2.0 port (single port on front), supports ThumbDrive®			
Alarm	Alarm Input	X4, D-sub 15-pin	X8, D-sub 25-pin	X16, D-sub 25-pin	
	Alarm Detection	N.C./N.O., Programmable			
	Auditory Alert	Built-in Buzzer			
	Motion Detection	16 x 12(NTSC), Grid Array, Sensitivity, Trig Level Adjustable			
	Video Loss Detection	Programmable			
	Alarm Relay Output	X1, 1.0A/24V (Programmable)			
Communication	Network Connectivity	Ethernet RJ-45 connector, 10/100Mbps, supports DHCP/PPPoE/DDNS			
	Remote Control Software	Internet Explorer			
	Access Control	2 Level Password			
	Remote Operation	Monitoring, Playback, Recording, System Setup, Dome Camera Control			
	RS485	D-sub 15-pin	D-sub 25-pin	D-sub 25-pin	
	Dome Control Protocol	DynaColor, Pelco P, Pelco D, AD422, Fastrax, JVC, Panasonic			

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>