

## PARK





## Park Royal Stiga

Enjoy your mower all year round.

A Swan marked Front mower with a Honda 2-cyl. engine, silent and ecofriendly. The genuine articulated steering offers unsurpassed manoeuvrability. The back wheels follow the track of those up front. You no longer need to worry about the rear section bumping into obstacles and you can fully concentrate on mowing.

The front mounted deck is easy to use, clean and maintain. There is a full range of Combi decks with Multiclip and rear discharge between 95 cm to 110 cm to choose from. The Multiclip system cuts and fertilises the lawn at the same time. No need for raking or emptying a collector.

This front mower comes with a lot of features. Hydrostatic speed control, adjustable foot pedal, high comfort seat adjustable with one hand grip, adjustable steering wheel, hour meter, headlight and mechanical servo steering.

The Park Royal is an outstanding implement-carrier. You can easily change from a cutting deck, sweeper or edge cutter to a snow blade or snow thrower. The list of implements is long. Equipped with the patented quick connection for accessories.









13-6183-14

## Park Royal (13-6183-14)

Brand Honda   Power 16 bp GCV 530   Cylinders 2 cyl   FUEL Petrol   Tank volume 12 I   SPEED CONTROL Hydrostatic K46   Number of gears Infinitely variable 0-10 km/h + R   STEERING Genuine articulated steering   Type of steering Genuine articulated steering   Servo assisted steering wheel Yes   Articulated steering wheel Yes   Articulated steering wheel Yes   Articulated steering wheel Yes   WHEELS Type of wheels   Yupe of cutting system Front and rear 16 inches, wide   Parings Plain   Tyre pressure Front cutting Combi deck   Cutting heights 25 e85 mm in 10 steps   Cutting width 95-110 cm   Cutting width 95-110 cm   Cutting height adjustment Electric with 95 Combi EI, 105 Combi EI and 110 Core   Electric starter Yes   Head light Yes   Yes Goute connection   Deck connection Oulck connection   Deck lift Foot controlled   Electric with 95 Combi EI, 105 Combi EI and 110 Core Electric starter   Head light Yes   Head light			ENGINE
Type of fuel Tark volume   Petrol 121     SPEED CONTROL   121     SPEED CONTROL   Hydrostatic K46 Infinitely variable 0-10 km/h + R     STEERING   Genuine articulated steering Wechanical     Steering Servo assisted steering Steering ball   Yes     Adjustable steering wheel Articulated steering through chain/chain   Yes     WHEELS   Type of wheels Wheel size   Front and rear 16 inches, wide Plain     Type of wheels   Stiga special lawn tyre tread Wheel size   Front out of bar. Rear 0.4 bar Rear wheel drive     CUTTING INFORMATION   Type of cutting system Cutting heights   25-85 mm in 10 steps     Cutting heights   25-85 mm in 10 steps   95-110 cm     Cutting width   95-105 Combi EI, 105 Combi EI and 110 Cor EI   VIBRATIONS & SOUND LEVELS     Synchronized belt Free rotating blades   On 95-105 Combi On 110 Combi Pro   Combi EI and 110 Cor EI     OLOUR & MATERIAL   Coot controlled   Separate     COLOUR & MATERIAL   Yes   Yes     Head light   Yes   Yes     Head light   195 kg excl. cutting deck   Separate     COLOUR & MATERIAL   20x101x202 cm   2x101x202 cm     Colour Choke   Separate   Confort seat wit		16 hp GCV 530	Power
Taink volume 12 1   SPEED CONTROL Hydrostatic K46   Type of transmission Hydrostatic K46   Number of gears Infinitely variable 0-10 km/h + R   STEERING Genuine articulated steering   Steering ball Yes   Adjustable steering wheel Yes   Articulated steering wheel Yes   Articulated steering hydrogen of the steering wheel Yes   WHEELS Stiga special lawn tyre tread   Type of wheels Stiga special lawn tyre tread   Prior of steering wheel Yes   CUTTING INFORMATION Plain   Type of cutting system Front cutting Combi deck   Cutting width 25-85 mm in 10 steps   Cutting width 95-10 cm   Cutting width Plain   Cutting height adjustment Electric with 95 Combi El and 110 Core   Electric with 95 Combi El, 105 Combi El and 110 Core Electric with 95 Combi El and 110 Core   ViBRATIONS & SOUND LEVELS Synchronized belt On 95-105 Combi   Free totating blades On 95-105 Combi   Deck connection Oulck connection   Deck connection Oulck connection   Deck connection Separate   Colour & MATERIAL Yes   Hour meter Yes <t< td=""><td></td><td></td><td>FUEL</td></t<>			FUEL
Type of transmission Number of gears   Hydrostatic K46 Infinitely variable 0-10 km/h + R     STEERING   Genuine articulated steering Mechanical     Type of steering Steering ball   Genuine articulated steering Mechanical     Steering tail   Yes     Adjustable steering wheel   Yes     Articulated steering through chain/chain   Yes     WHEELS   Front and rear 16 inches, wide     Bearings   Plain     Type of wheels   Front of arear 0.4 bar     Whet size   Front 0.6 bar. Rear 0.4 bar     Driving   Rear wheel drive     CUTTING INFORMATION   Type of cutting system     Cutting heights   25-85 mm in 10 steps     Cutting height adjustment   Electric with 95 Combi El, 105 Combi El and 110 Core     Electric with 95 Combi Pro   CONTROLS     Deck connection   Quick connection     Deck connection   Quick connection     Deck connection   Quick connection     Deck connection   Yes     Gear lever   Foot pedal     Choke   Separate     COLUR & MATERIAL   Yellow / Grey     Colour & Weight   195 kg excl. cutting deck     Gross weig			
Number of gears   Infinitely variable 0-10 km/h + R     STEERING   Genuine articulated steering     Type of steering   Mechanical     Steering ball   Yes     Adjustable steering wheel   Yes     Articulated steering through chain/chain   Yes     WHEELS   Type of wheels     Type of wheels   Stiga special lawn tyre tread     Wheel size   Front and rear 16 inches, wide     Bearings   Plain     Type of cutting system   Front cutting Combi deck     CUTTING INFORMATION   25-85 mm in 10 steps     Type of cutting system   Front cutting Combi deck     Cutting width   95-110 cm     Cutting heights   25-85 mm in 10 steps     Cutting width   95-110 cm     Cutting height adjustment   Electric with 95 Combi El and 110 Core     VIBRATIONS & SOUND LEVELS   Synchronized belt     Synchronized belt   On 95-105 Combi     Free rotating blades   On 110 Combi Pro     CONTROLS   Ocick connection     Deck lift   Foot controlled     Electric starter   Yes     Head light   Yes     Hour meter			SPEED CONTROL
Type of steering Servo assisted steering ball Adjustable steering wheel Articulated steering through chain/chain YesGenuine articulated steering Mechanical YesWHELSYesWheels stee Bearings Tyre pressure DrivingStiga special lawn tyre tread Front and rear 16 inches, wide Plain Rear wheel driveCUTTING INFORMATIONFront cutting Combi deck 25-85 mm in 10 steps Qutting width Cutting height adjustmentCutting height adjustment Electric with 95 Combi El, 105 Combi El and 110 Con ElVIBRATIONS & SOUND LEVELSSynchronized belt Free rotating bladesOn 110 Combi ProCONTROLSDeck connection Deck liftDeck connection ControlledColour & MATERIAL Colour Material of chassisColour & MATERIAL Colour Material of chassisMechanical Steering blatesColour & MATERIAL Colour & MATERIALColour & MATERIAL Colour & MATERIALColour & MATERIAL Colour & MATERIALYellow / Grey SteelMechanical Package size WXHXLStear Gear lever ChosesMechanical Package size WXHXLStear Package size WXHXL <td< td=""><td></td><td></td><td></td></td<>			
Serior assisted steering Mechanical   Steering ball Yes   Adjustable steering wheel Yes   Articulated steering through chain/chain Yes   WHEELS Stiga special lawn tyre tread   Wheels with the steering steering Front and rear 16 inches, wide   Bearings Plain   Type of wheels Front and rear 16 inches, wide   Bearings Plain   Type pressure Front 0, 6 bar. Rear 0,4 bar   Driving Rear wheel drive   CUTTING INFORMATION Type of cutting system   Cutting width 25-85 mm in 10 steps   Cutting width 95-110 cm   Cutting heights 25-85 mm in 10 steps   Cutting width 95-105 Combi EI, 105 Combi EI and 110 Core   CONTROLS On 95-105 Combi On 100 Combi Pro   Deck connection Quick connection   Peck kilt Foot controlled   Electric starter Yes   Head light Yes   Hour meter Yes   Head light Yes   Hour meter Yes   Gear lever </td <td></td> <td></td> <td>STEERING</td>			STEERING
Type of wheels   Stiga special lawn tyre tread     Wheel size   Front and rear 16 inches, wide     Bearings   Plain     Tyre pressure   Front 0,6 bar. Rear 0,4 bar     Driving   Rear wheel drive     CUTTING INFORMATION     Type of cutting system   Front cutting Combi deck     Cutting width   25-85 mm in 10 steps     Cutting width   95-110 cm     Cutting width   95-105 Combi El, 105 Combi El and 110 Con     Cutting blades   On 95-105 Combi     Synchronized belt   On 95-105 Combi     Free rotating blades   On 110 Combi Pro     CONTROLS   Deck connection     Deck connection   Quick connection     Deck lift   Foot pedal     Electric starter   Yes     Head light   Yes     Head light   Yes     Gour   Yellow / Grey     Material of chassis   Steel     MEASURES & WEIGHT   195 kg excl. cutting deck     Meight   195 kg excl. cutting deck     Gross weight   235 kg excl. cutting deck     Package size WXHxL   235 kg excl. cutting deck     Ga		Mechanical Yes Yes	Servo assisted steering Steering ball Adjustable steering wheel
Wheel size   Front and rear 16 inches, wide     Bearings   Plain     Tyre pressure   Front 0,6 bar. Rear 0,4 bar     Driving   Rear wheel drive     CUTTING INFORMATION     Type of cutting system   Front cutting Combi deck     Cutting width   25-85 mm in 10 steps     Cutting width   95-110 cm     Cutting width   95-110 cm     Cutting blades   On 95-105 Combi El, 105 Combi El and 110 Come     VIBRATIONS & SOUND LEVELS   Synchronized belt     Synchronized belt   On 95-105 Combi     Free rotating blades   On 110 Combi Pro     CONTROLS   Deck connection     Deck connection   Quick connection     Deck lift   Foot pedal     Electric starter   Yes     Head light   Yes     Head light   Yes     Gar lever   Foot pedal     Choke   Separate     Colour   Yellow / Grey     Material of chassis   Steel     MEASURES & WEIGHT   195 kg excl. cutting deck     Gross weight   235 kg excl. cutting deck     Package size WXHxL   235 kg excl			WHEELS
Type of cutting system Cutting heightsFront cutting Combi deck 25-85 mm in 10 steps 95-110 cmCutting height adjustmentElectric with 95 Combi El, 105 Combi El and 110 Cor ElVIBRATIONS & SOUND LEVELSSynchronized belt Free rotating bladesOn 95-105 Combi On 110 Combi ProDeck connection Deck liftQuick connection Foot controlledBerler Head lightYes Yes Gear leverColour & MATERIALYellow / Grey SteelColour & MATERIALYellow / Grey 		Front and rear 16 inches, wide Plain Front 0,6 bar. Rear 0,4 bar	Wheel size Bearings Tyre pressure
Cutting heights25-85 mm in 10 stepsCutting width95-110 cmCutting height adjustmentElectric with 95 Combi El, 105 Combi El and 110 ComVIBRATIONS & SOUND LEVELSSynchronized beltOn 95-105 CombiFree rotating bladesOn 110 Combi ProCONTROLSDeck connectionQuick connectionDeck liftFoot controlledElectric starterYesHead lightYesHour meterYesGear leverFoot pedalChokeSeparateColourYellow / GreyMaterial of chassisSteelMEASURES & WEIGHT195 kg excl. cutting deckWeight195 kg excl. cutting deckSynswight235 kg excl. cutting deckSear lever State92x101x202 cmLargest measures WxHxL130x125x245 cm with deckSEATComfort seat with high back supportType of seatComfort seat with high back supportSeat adjustable horizontallyOr fort seat with high back support			CUTTING INFORMATION
Synchronized belt Free rotating bladesOn 95-105 Combi On 110 Combi ProCONTROLSOuck connection Foot controlled Electric starterDeck lift Electric starterFoot controlled YesHead light Hour meter ChokeYesGear lever ChokeFoot pedal SeparateColour & Material of chassisYellow / Grey SteelMEASURES & WEIGHT195 kg excl. cutting deck 	) Combi Pro	25-85 mm in 10 steps 95-110 cm Electric with 95 Combi El, 105 Combi El and 110 Co	Cutting heights Cutting width
Free rotating bladesOn 110 Combi ProCONTROLSQuick connectionDeck connectionQuick connectionDeck liftFoot controlledElectric starterYesHead lightYesHour meterYesGear leverFoot pedalChokeSeparateColour & MATERIALColourYellow / GreyMaterial of chassisSteelMEASURES & WEIGHT195 kg excl. cutting deckWeight195 kg excl. cutting deckPackage size WxHxL235 kg excl. cutting deckLargest measures WxHxL130x125x245 cm with deckSEATComfort seat with high back supportType of seat Seat adjustable horizontallyComfort seat with high back support			VIBRATIONS & SOUND LEVELS
Deck connection Deck liftQuick connection Foot controlledDeck liftFoot controlledElectric starter Head lightYesHead lightYesHour meter Gear leverYesGear lever ChokeFoot pedalChokeSeparateCOLOUR & MATERIALColour Material of chassisMEASURES & WEIGHTYellow / Grey 			
Deck liftFoot controlledElectric starterYesHead lightYesHour meterYesGear leverFoot pedalChokeSeparateCOLOUR & MATERIALColourYellow / GreyMaterial of chassisSteelMEASURES & WEIGHT195 kg excl. cutting deckGross weight235 kg excl. cutting deckPackage size WxHxL92x101x202 cmLargest measures WxHxL130x125x245 cm with deckSeat adjustable horizontallyComfort seat with high back support			CONTROLS
Colour Material of chassisYellow / Grey SteelMEASURES & WEIGHT195 kg excl. cutting deck 235 kg excl. cutting deckWeight Gross weight Package size WxHxL Largest measures WxHxL195 kg excl. cutting deck 92x101x202 cm 130x125x245 cm with deckSEATComfort seat with high back support One hand grip		Foot controlled Yes Yes Yes Foot pedal	Deck lift Electric starter Head light Hour meter Gear lever
Material of chassisSteelMEASURES & WEIGHT195 kg excl. cutting deckWeight195 kg excl. cutting deckGross weight235 kg excl. cutting deckPackage size WxHxL92x101x202 cmLargest measures WxHxL130x125x245 cm with deckSEATType of seat Seat adjustable horizontallyComfort seat with high back support One hand grip			COLOUR & MATERIAL
Weight195 kg excl. cutting deckGross weight235 kg excl. cutting deckPackage size WxHxL92x101x202 cmLargest measures WxHxL130x125x245 cm with deckSEATType of seat Seat adjustable horizontallyComfort seat with high back support One hand grip			
Gross weight235 kg excl. cutting deckPackage size WxHxL92x101x202 cmLargest measures WxHxL130x125x245 cm with deckSEATType of seat Seat adjustable horizontallyComfort seat with high back support One hand grip			MEASURES & WEIGHT
Type of seatComfort seat with high back supportSeat adjustable horizontallyOne hand grip		235 kg excl. cutting deck 92x101x202 cm	Gross weight Package size WxHxL
Seat adjustable horizontally One hand grip			SEAT
		Comfort seat with high back support One hand grip	
			OTHER FACTS
CE-markYesInstructions for use8211-0003-80EAN bar code7 313 321 303 617		8211-0003-80	Instructions for use

Other features

Carries the Svan label (340 008). Meets the Californian environmental laws, (CARB).

Free Manuals Download Website <u>http://myh66.com</u> <u>http://usermanuals.us</u> <u>http://www.somanuals.com</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.cc</u> <u>http://www.4manuals.com</u> <u>http://www.404manual.com</u> <u>http://www.luxmanual.com</u> <u>http://aubethermostatmanual.com</u> Golf course search by state

http://golfingnear.com Email search by domain

http://emailbydomain.com Auto manuals search

http://auto.somanuals.com TV manuals search

http://tv.somanuals.com