


The Biggest Thing in Small HD Monitors

**LCD-703HD
LCD-703HD1
LCD-703HD2
LCD-703HDL**



Back View



LCD-703HDL Unit in flush mount kit

Active Matrix 7" Color LCD Monitors

• HD compatible (supports 480p/i, 576p/i, 720p, 1080p/i)

NEW

• LED backlight provides longer life, uses less power and provides better color saturation

• RS-232 feature allows external devices to control the monitor through the serial port.

• Underscan capability


• Blue gun feature provides for easy adjustment of screen display

- Anti-glare treatment adds to viewing pleasure
- Displays either 16:9 or 4:3 aspect ratio
- Front controls for : menu, up, down, On/Off, mode
- IR remote control
- Case made of durable metal.
- A/C adaptor (Part No. AC-1000) included
- Built-in interface and proper cable exiting for wall or arm mounting VESA 75mm FPMPMI compliant
- Response time: 22mS (Rising), 35mS (Falling)
- Mounting pad with 1/4"-20 threaded socket

LCD-703HDL Flush mount kit (shown above)

Dimensions (WHD): 215 x 175 x 35mm / 8.5" x 6.9" x 1.4"
Installer's Cut-out (WH): 180 x 138mm / 7.1" x 5.4"

LCD-703HDLX - w/ no LEDs & no controls showing
- Special Order Only



Specifications subject to change without notice

P.23

Download from www.Somanuals.com. All Manuals Search And Download.

© 2008 TOTE VISION



LCD-703HD2 Dual Rack Mount Unit

LCD-703HD1 Single Rack Mount Unit

- Display: 7" TFT LCD active matrix
- Back Light: LED
- Input Signal: NTSC/PAL (auto sensing)
- Resolution: 800 (H) x 480 (V) dots
- Dot Pitch: 0.19(H) x 0.19(V)mm
- Brightness rating: 350 cd/m² (Nit)
- Contrast Ratio: 300 : 1
- Number of Pixels: 1.2 M
- Viewing angle L/R/T/B: 65/65/55/60 degrees
- Pixel Configuration: Stipe
- Power Requirements: 6~20 VDC, 500mA, + pin, - ground
- Power Consumption: 350mA@ 12 VDC (max)
- Video Input Level: 1.0 V P-P (positive) 75 Ohm
- LCD-703HD: Dimensions (WHD): 174 x 134 x 35mm / 6.9" x 5.3" x 1.4"
(Height including 5mm mounting pad: 134 + 5mm = 139mm)
- LCD-703HD1 / LCD-703HD2: Dimensions (WHD): 482 x 133.4 x 55mm / 19" x 5.25" x 2.2", 3RU
Actual visible screen size (WH): 152.4 x 91.4mm / 6" x 3.6"
- Operating temperature: 10 ~ 104°F / -12 ~ 40°C
- Storage temperature: -13 ~ 140°F / -25 ~ 60°C
- Rear inputs: BNC composite video IN/OUT, S-Video IN/OUT, BNC component IN/OUT RS-232, Tally, DVI-D, 2.1mm DC IN jack
- LCD-703HD: Weight: Net: 0.6 kg. / 1.35 lbs Gross: 0.86 kg. / 1.9 lbs.
- LCD-703HD2: Weight: Net: 2.5 kg. / 5.5 lbs Gross: 3.2 kg. / 7 lbs.
- LCD-703HDL: Weight: Net: 0.86 kg. / 1.9 lbs Gross: 1.1 kg. / 2.45 lbs

Field Monitor Kit

Order LCD-703HD KIT for unit with monitor, tote bag, and rechargeable 2600mAH battery pack (approx. 6 hours operation).

Optional Accessories

- | | |
|----------|---|
| HS-1 | Hot shoe mount |
| MB-3 | Desk stand |
| SS-703HD | Sun shield |
| TB-703 | Custom Tote bag with sun shield for LCD-703HD |
| WM-30 | Wall mount bracket (fixed) |

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

<http://www.totevision.com>



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>