

The Biggest Thing in Small HD Monitors

LCD-703HDA LCD-703HDV



LCD-703HDA Unit with Anton Bauer QRC - Gold mount



LCD-703HDV Unit with "V" lock mount for IDX batteries

Active Matrix 7" Color LCD Monitors

• **HD compatible (supports 480p/i, 576p/i, 720p, 1080p/i)**
Both component & DVI inputs accept 1080p/i.

NEW • **LED backlight provides longer life, uses less power and provides better color saturation**

• **RS-232 feature allows external devices to control the monitor through the serial port.**

• **Underscan capability**

• **Blue gun feature provides for easy adjustment of screen display**

- DVI-D input jacks accepts digital input.
- Anti-glare treatment adds to viewing pleasure
- Displays either 16:9 or 4:3 aspect ratio
- Front controls for : menu, up, down, On/Off, mode
- IR remote control
- Case made of durable metal.
- A/C adaptor (Part No. AC-1000) included
- Built-in interface and proper cable exiting for wall or arm mounting VESA 75mm FPMPMI compliant
- Response time: 22mS (Rising), 35mS (Falling)
- Mounting pad with ¼"-20 threaded socket (located at bottom and can be moved to top).
- Runs 16.5 hours on IDX Endura 7S battery.
- Runs 22 hours on Anton Bauer Dionic 90 battery.



Front View

Display: 7" TFT LCD active matrix
 Back Light: LED
 Input Signal: NTSC/PAL (auto sensing)
 Resolution: 800 (H) x 480 (V) dots
 Dot Pitch: 0.19(H) x 0.19(V)mm
 Brightness rating: 350 cd/m² (Nit)
 Contrast Ratio: 300 : 1
 Number of Pixels: 1.2 M
 Viewing angle L/R/T/B: 65/65/55/60 degrees
 Pixel Configuration: Stipe
 Power Requirements: 6~20 VDC, 500mA, + pin, - ground
 Power Consumption: 350mA@ 12 VDC (max)
 Video Input Level: 1.0 V P-P (positive) 75 Ohm
 LCD-703HDA/HDV: Dimensions (WH): 174 x 134 x 35mm / 6.9" x 5.3" x 1.4"
 (Height including 5mm mounting pad: 134 + 5mm = 139mm)
 Actual visible screen size (WH): 152.4 x 91.4mm / 6" x 3.6"
 Operating temperature: 10 ~ 104°F / -12 ~ 40°C
 Storage temperature: -13 ~ 140°F / -25 ~ 60°C
 Rear inputs: BNC composite video IN/OUT,
 S-Video IN/OUT, BNC component IN/OUT
 RS-232, Tally, DVI-D, 2.1mm DC IN jack
 LCD-703HDA / HDV: Weight: Net: 0.7 kg./ 1.5 lbs Gross: TBD

Custom Tote Bag

Order TB-703AV for nylon tote bag with sun shield.



**Metal Sun Shield
SS-703HD**

Optional Accessories

HS-1	Hot shoe mount
MB-3	Desk stand
SS-703HD	Sun shield
TB-703AV	Custom Tote bag with sun shield for LCD-703HDA and LCD-703HDV.
WM-30	Wall mount bracket (fixed)

GSA Schedule
GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

Download from www.semanuals.com. All Manuals Search And Download

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

<http://www.totevision.com>

**TOTE
VISION**

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>