

The Biggest Thing in Miniature Color CCD Cameras

MX-07WP



Digital Color Water-resistant Camera

Image Device: 1/4" interline transfer CCD (Sharp)
Camera mounting bracket: Included
Resolution: NTSC: 330 TV lines
Minimum Illumination: 1.0 lux
Gamma Characteristic: 0.45
Scanning System: EIA: 525 lines, 60 fields/sec. 2:1 interlace
Output Signal: Standard composite signal
1 Vpp composite video, 75 Ohm
Synchronization: Internal
Automatic Electronic Shutter: 1/60 ~ 1/100,000
Standard Lens 3.6mm (f2.0) (92° angle of view)
Power Requirements: 12 VDC +/- 10%, 100mA
Operating Temperature: 14 ~ 122° F or -10 ~ 50° C
Storage Temperature: -20 ~ 70°C/RHM 95% max.
S/N ratio: > 48dB
Gray Scale: 10 Shades
Housing: Aluminum
Cable: 500mm (19") w/ RCA /DC jacks
MX-07WP Dimensions (LWD): 81 x 26mm / 3.2" x 1.0"
Weight: 60.5 g. / 2.1 oz.

GSA Schedule
GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

2005 ToteVision

Available through:

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109
Tel: 206-623-6000 • FAX: 206-623-6609
E-mail: sales@totevision.com
<http://www.totevision.com>

**TOTE
VISION**

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>