


AO2500-3-P™ DATASHEET

2.4 GHz Omnidirectional Antenna

- High-gain, linear polarized antenna is ideal for point-to-multipoint applications.
- Uses custom connector that attaches directly to the Eagle Plus transmitter.
- Independent swivel for adjustable orientation.
- Dipole design for ground-plane independence.
- FCC Part 15 and DOC (Canada) compliant.



AO2500-3-P™ DATASHEET

AO2500-3-P Electrical Properties

FREQUENCY RANGE

2.4–2.5 GHz

IMPEDANCE

50Ω nominal

GAIN

3 dBi

RADIATION

omnidirectional

VSWR


< 2.0 : 1

ELECTRICAL WAVE

half-wave dipole, elevated feed

POLARIZATION

vertical



H-PLANE PATTERN

AO2500-3-P Mechanical Properties

LENGTH

9.5 inches or 241 mm

ANTENNA WHIP

polyurethane

SWIVEL MECHANISM

polycarbonate

CONNECTOR


reverse polarity male SMA plug

COLOR

black

OPERATING TEMPERATURE

-4°F to +149°F or -20°C to +65°C



E-PLANE PATTERN



+1 858-653-3900 • www.trangosys.com • 9939 Via Pasar, San Diego CA 92126 DS_AO2500.p65 01-06-12

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>