



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: MT-6PLUS

Isobar Surge Suppressor - Under-monitor surge, spike and line noise protection

Highlights

- 6 outlets / 10-ft. cord
- 1790 joule rating
- Under monitor housing
- Front panel switches
- Modem/fax surge protection
- \$100,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)



Description

Tripp Lite's MT 6PLUS (TouchMaster Plus) under-monitor console surge suppressor offers convenient AC and phone line computer power protection, individually controllable outlets and multiple power switches for remote control of connected equipment. High grade protection circuits utilize Tripp Lite's Isobar protection system with a generous combination of high quality components and unique noise filtration system. Robust surge suppression circuits with sine-wave tracking offer extreme levels of protection against the heaviest surge conditions exceeding IEEE 587 category A & B specifications. Isobar's unique protection system combines large toroidal chokes, HF/VHF capacitors and multiple layers of metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference. MT 6PLUS offers 6 outlets total, 4 individually controllable via front panel mounted switches, one completely unswitched and one controlled by the master switch. Surge suppression rated at 1790 joules prevents equipment damage due to transient surges. Diagnostic LEDs confirm power availability and protection status, plus offer indication of line fault, suppressor fault and low voltage conditions. Includes 10 foot AC line cord. Space-saving under-monitor design offers convenient protection and power control of computers and all system peripherals. Lifetime warranty with \$100,000 [Ultimate Lifetime connected equipment insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 6 NEMA5-15R/10-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping/1790 joules PHONE: Single line dialup protection starts at 260V

FORMAT: Corded console-style under monitor suppressor

Applications

- Ideal for premium protection of entire desktop computer systems with multiple peripherals, CAD/CAM/CAE workstations, internetworking accessories, audio/video and home theater systems

Package Includes

- MT 6PLUS Surge Suppressor
- RJ11 telephone cable
- Instruction manual with warranty information

Features

- MT 6PLUS console suppressors incorporate Tripp Lite's premium Isobar protection circuitry, the world's #1 selling premium suppressor series with more than 14 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine-wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B specifications
- Multi-component suppression circuits combine toroidal chokes, HF/VHF capacitors and multiple layers of metal oxide varistors for enhanced protection from EMI/RFI interference
- Includes 6 NEMA 5-15R output receptacles, 4 of which are individually controllable via front panel mounted switches, plus one completely unswitched and one controlled by the master switch
- Network grade surge suppression rated at 1790 joules
- Single phone line surge suppression protects modems, fax machines and cordless phones (2 wire, single line, RJ11 jacks)
- 4 LED indicators confirm suppressor operation and site wiring status, plus warning of suppressor or electrical fault conditions and low voltage conditions
- Lighted power switches confirm power on/off status for each individually controllable outlet
- 10 foot AC line cord
- Space-saving under-monitor console design offers convenient power protection and power control of entire desktop systems
- 120V AC, 50/60Hz electrical compatibility
- \$100,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only)
- Lifetime product warranty
- UL1449 listed - surge suppression (330V let-through), UL1283 listed - EMI protection, UL1363 listed - power tap, UL497A listed - communications suppression, cUL approved to Canadian standards, Complies with part 68 - FCC rules

Specifications

OVERVIEW	
Intended Application	Home/Office, Computer Networks
SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	6 NEMA 5-15R
INPUT	
Input connection type	NEMA 5-15P input plug
Input cord length (ft.)	10 ft.
Input cord length (m)	3.0
Recommended Electrical Service	120V (110-125V)
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	PROTECTION PRESENT (green), LINE FAULT (red), LOW VOLTAGE (yellow) and LINE OK (green)
Switches	Includes 5 front panel switches - MASTER SWITCH controls all output receptacles (except the one marked "unswitched"), INDIVIDUAL OUTLET switches control 4 individual output receptacles
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	1790 joules
Clamping voltage (RMS)	140V
AC suppression response time	NM = 0 ns. CM =
AC suppression surge current rating	132,000 amps

AC suppression components used	Metal oxide varistors, toroidal balanced chokes and VHF capacitors
Safe thermal fusing	Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences
UL1499 let through rating	330V - UL Verified
IEEE587 Cat. A ringwave let through	Less than 35 volts
EMI / RFI filtering	40-80 dB
Immunity	Conforms to IEE 587 / ANSI C62.41
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Unit Dimensions (HWD/in)	2 x 13.5 x 12.5
Unit Dimensions (HWD/cm)	5.1 x 34.3 x 31.8
Material of construction	Plastic
Form factors supported	Supports under monitor placement as a power control center for an entire PC system with peripherals
Receptacle Color	Black
AC line cord color	Black
Style	Under Monitor
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1283 (EMI Filter)	UL1283
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period	Lifetime
Connected Equipment Coverage	\$100,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=107.

©2009 Tripp Lite. All Rights Reserved.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>