

Optquest® Q19wb-2

19" WIDESCREEN LCD
WITH FAST 5MS VIDEO RESPONSE

Widescreen, multimedia display.

The Optquest Q19wb-2 19" widescreen LCD integrates high brightness and contrast ratios with super-fast video response. Enhance your productivity with this widescreen display that lets you work in two applications or documents side-by-side. Enjoy the crystal-clear, blur-free video and graphics delivered by broadcast-quality, 5ms video response. Built-in speakers deliver rich, stereo sound. The integrated power supply and VESA® wall-mount compliance reduce clutter and free up valuable desktop real estate. The OSD lock ensures your screen settings are secure and the Kensington® security port provides theft deterrence. Furnish your workplace in style with the budget-friendly, feature-rich Q19wb-2 LCD.



ELEGANCE AND PERFORMANCE IN AN AFFORDABLE DISPLAY

- > **Fast 5ms video response** delivers superior picture clarity
- > **High brightness and contrast ratio**
300-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > **1440x900 optimum resolution**
Incredible image detail for sharp text and graphics.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Full 19" viewable widescreen**
Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > **Multimedia enhanced**
Save desk and workspace and enjoy rich stereo sound with two built-in stereo speakers.
- > **Integrated power supply**
- > **VESA® 100mm wall-mount compliant**
- > **24/7 free technical and customer support***
- > **PC and Mac® compatible**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 
See the difference®

Optquest® Q19wb-2

19" WIDESCREEN LCD WITH FAST 5MS VIDEO RESPONSE



| | | |
|-------------------------------|------------------------|--|
| LCD | Type | 19" color TFT active matrix SXGA LCD |
| | Display Area | 16.1" horizontal x 10.0" vertical; 19.0" diagonal |
| | Optimum Resolution | 1440x900 |
| | Contrast Ratio | 700:1 (typ) |
| | Viewing Angles | 150° horizontal, 140° vertical @ contrast ratio > 10:1 |
| | Response Time | 5ms (typ) |
| | Light Source | Long life, 50,000 hrs. (typ) |
| | Brightness | 300 cd/m2 (typ) |
| | Panel Surface | Anti-glare |
| INPUT SIGNAL | Video | RGB analog (75 ohms, 0.7 Vp-p) |
| | Sync | H/V separated (TTL) |
| | Frequency | F _H : 31~81kHz, F _V : 50~75Hz |
| COMPATIBILITY | PC | VGA up to 1440x900 non-interlaced |
| | Mac*** | Power Mac™ G3/G4/G5 up to 1152x870 |
| CONNECTOR | Analog PC | 15-pin mini D-sub |
| | Power | 3-pin AC plug (CEE22) |
| POWER | Voltage | AC 100–240V (universal), 50/60Hz (auto switch) |
| | Consumption | 36W (typ) |
| AUDIO | Speakers | 2x1-watt |
| CONTROLS | Basic | Power, 2, up, down, 1 |
| | OnView® | Auto image adjust, brightness, contrast, ViewMatch® color adjust (sRGB, 9300K, 6500K, 5400K user color), H. position, V. position, H. size, resolution notice, OSD position, OSD timeout, OSD background, fine tune, sharpness, language, recall, volume, mute |
| OPERATING CONDITIONS | Temperature | 32–104°F (0–40°C) |
| | Humidity | 10–90% (non-condensing) |
| DIMENSIONS (W x H x D) | Physical with stand | 17.6" x 14.3" x 8.4" (446mm x 364mm x 213mm) |
| | Physical without stand | 17.6" x 11.5" x 2.6" (446mm x 292mm x 67mm) |
| WEIGHT | Net with stand | 9.7 lb. (4.4 kg) |
| | Net without stand | 8.8 lb. (4.0 kg) |
| | Gross with stand | 11.2 lb. (5.1 kg) |
| REGULATIONS | | UL, cUL, FCC-B, ENERGY STAR®, TCO'99, ICES-003B, RoHS, CB, CE, WEEE, ISO13406-2, TUV-S, NOM, GOST-R |
| POWER MANAGEMENT | | Meets TCO'99 and ENERGY STAR® standards |
| PACKAGE CONTENTS | | LCD display, power cable, video cable, audio cable, Quick Start Guide, Wizard CD-ROM |
| WARRANTY | | One-year limited warranty on parts and backlight |



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic®
See the difference®

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Excluding major U.S. holidays. **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14184-00B-10/08] Q19wb-2

For more product information, visit us on the web at ViewSonic.com

Download from Www.Somanuals.com. All Manuals Search And Download.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>