

ViewSonic®

PJ350 Projector



LiteBird™ Series

PJ350 3.3-pound micro-portable projector.

Feel confident walking into any presentation setting with the micro-portable ViewSonic PJ350. Weighing in at just 3.3 pounds, this high-performance projector is the ultimate choice for traveling business professionals who demand excellent image quality in a lightweight, easy-to-carry package. With XGA resolution, high brightness and contrast as well as full functionality this projector will make it easy for you to present a positive image anytime, anywhere. With Digital Keystone Correction, picture-in-picture and zoom functions this projector is flexible for any presentation setting. In addition, it is capable of displaying DVI-I and HDTV signals as well as other video and data sources.

- **Ultra lightweight 3.3 lb micro-portable projector**
Packs a lot of power in only 3.3 pounds.
- **Professional level 1100 lumens**
Get clear, bright presentations in any setting.
- **True 1024 x 768 XGA resolution**
Produces clear, crisp images.
- **Easy set-up and auto tuning**
One-touch setup button for fast, easy sync and sharp focus.
- **Digital Light Processing (DLP™) by Texas Instruments®**
Excellent color contrast, bright, vivid images and excellent video quality.
- **PersonalTheater™ projection for movies, sports and more**
- **Supports HDTV and DVI-I signals**
- **Digital Keystone Correction**
Squares up the picture when projecting at an angle.
- **Wireless remote control**
Gives you total control, flexibility and convenience.



ViewSonic®
See the difference!®



ViewSonic PJ350

PROJECTOR

MICRO-PORTABLE LITEBIRDPROJECTOR

DLP	Type	TI 0.7" XGADLP™
	Pixel Format	1024 Horizontal x 768 Vertical
	Lens	Manual zoom/focus F(2.2-2.4) f(28.51mm-14.21mm)
DISPLAY	Size	20" to 300" (measured diagonally)
	Focus Distance	1.0 to 12.0M
	Lamp	130W OSRAM P-VIP, 1500 hour rating
	Brightness	1100 Lumens
	Contrast Ratio	500:1
AUDIO	Speakers	40mm (W) x 28.2mm (H) x 11mm (D), Oval x1
	Power	2W (at 1KHz/0.5% THD)
INPUT SIGNAL	Video	RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, KI, L), HDTV
	Sync	Separated, Composite and Sync on Green (SOG)
	Frequency	F _H : 15-100kHz; F _V : 43-120Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA Digital: from VGA up to XGA
	Mac**	Analog: up to SXGA (may require Mac Adapter) Digital: up to XGA (may require Mac Adapter)
CONNECTOR	RGB	15-pin HD, D-sub (loop through – output only)
	DVI	High density 29-pin DVI-I
	Video	RCA
	S-Video	SVHS DIN Connector
	Audio	3.5mm Mini Stereo Plug
	Remote Mouse In	Din 8-pin
POWER	Voltage	100-240 VAC, 50-60Hz (universal)
	Consumption	180W (typ)
USER CONTROLS	Physical	Standby on/off, menu, enter/resync, source (data, video, and s-video), mute, volume (+, -)
	Remote	Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu
	OSD	Display [brightness, contrast, keystone correction, color temperature, zoom, menu location, tint (video only), sharpness (video only), color (video only), aspect ratio, tracking, frequency, horizontal position, vertical position, signal type (RGB, component, HDTV), reset] Language Audio [volume, bass, treble, mute, stereo/mono] Projection [front, rear, front ceiling, rear ceiling] Lamp [lamp reminder, lamp reset]
OPER. COND.	Temperature	50° F to 104° F (10° C to 40° C)
	Humidity	10% to 85% (non-condensation)
DIMENSIONS	Physical	223mm (W) x 175mm (D) x 52mm (H) (8.8" x 6.9" x 2.1")
WEIGHT	Net	1.5kg (3.3 lbs.)
REGULATIONS		UL, FCC-B, c-UL, FDA, CE, TUV/GS, CB, BSMI, VCCI, PSC PCT
WARRANTY		Two-year limited on parts and labor. 90-day on lamp.
OTHER		Remote range = 5m, front and rear projection, 10 user modes

- User-replaceable extended-life lamp

Extended lamp life up to 1,500 hours.

- Soft carry case included for easy travel

- Industry-leading 24/7 customer support

- Optional accessories

Executive carrying case

Replacement lamp

Ceiling/wall mount kit

Extended warranty

48-hour Express Exchange®

ViewSonic®
See The Difference!™

Headquarters:

381 Brea Canyon Road, Walnut,

CA 91789, U.S.A.

Tel: 1-909-869-7976 800-888-8583

Fax: 1-909-869-7958

Internet: <http://www.viewsonic.com>

Asia Pacific Sales:

9F, No. 192, Lien Chen Road, Chung Ho,

Taipei, Taiwan, R.O.C.

Tel: 886-2-2246-3456

Fax: 886-2-8242-3666

E-mail: vsitech@viewsonic.com.tw



ViewSonic®
See the difference!™

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>