

PJ106D

ULTRA-PORTABLE ONE- POUND DLP™ PROJECTOR

WITH DLP™ TECHNOLOGY

Palm-sized, perfect for travel.

ViewSonic's innovative one pound PJ106D is our smallest projector yet. Despite its diminutive size, the PJ106D delivers sharp images with the digital clarity of DLP™ technology and is IDEAL FOR VIEWING DIGITAL PHOTOS, WATCHING MOVIES OR GAMES. It includes support for HD signals, and both standard (4:3) and widescreen (16:9) aspect ratios. Multiple PC and video inputs and an SD card reader OFFER VERSATILE CONNECTIVITY OPTIONS FOR FLEXIBLE USAGE. The LED lamp boasts a long lamp life with virtually no heat output and nearly silent operation. The rechargeable battery lasts 2.5 hours. You're always on with the PJ106D projector.



MOBILE, VERSATILE, INNOVATIVE

> Palm-sized, perfect for travel

Only one pound (without battery) this palm-size portable projector travels nicely in those compact places.

> DLP™ Technology

Stunning digital clarity delivers lifelike color, sharp graphics and outstanding video.

> LED lamp for low power consumption

The low power consumption helps to deliver literally no operating noise and a longer lamp life.

> Ultimate video source flexibility

Connect a computer or add a video source for dynamic meetings and presentations.

> Supports HD signals including 720p and 1080i

Capable of displaying HDTV signals as well as other video and data sources*.

> OnView® controls for superior screen adjustability

Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic

the choice of professionals

PJ106D

ULTRA-PORTABLE 1-POUND DLP™ PROJECTOR WITH ADVANCED VIDEO PROCESSING



PROJECTOR	Type	0.55" SVGA, DLP™
	Pixel Format	800x600 SVGA
	Lens	Manual zoom/manual focus
	Zoom Factor	1.1
	Keystone	Vertical ± 15°
DISPLAY	Size	12"– 60" (diagonally)
	Throw Distance	16"– 79"
	Throw Ratio	1.64
	Lamp	Lumileds RGB Luxeon level-2
	Brightness	25 ANSI lumens
	Contrast Ratio	300:1
Aspect Ratio	4:3 (native), 16:9	
INPUT SIGNAL	Computer and Video	NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 576p, 720p, 1080i)
	Frequency	F _H : 31–80kHz; F _V : 50–85Hz
COMPATIBILITY	PC	Analog: from VGA up to UXGA (scaled)
	Mac®†	Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x1)
	Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Audio (input)	Stereo mini-jack (x1)
	Audio (output)	Mini-jack
	SD card slot	Card slot (x1)
	POWER	Voltage
	Consumption	19W (typ)
CONTROLS	Basic	Standby/On, input, menu
	OnView®	Brightness, contrast, gamma, white intensity, high brightness mode, saturation, tint, color temperature, keystone, aspect ratio, sharpness), H. position, V. position, management (projection ceiling, projection rear, source lock, lamp hour elapse, OSD transparency, reset), AV set (volume, mute, SD slide show, SD slide show delay, SD picture information).
OPERATING CONDITIONS	Temperature	41–95°F (5–35°C)
	Humidity	10–85% (non condensing)
NOISE LEVEL	Normal/Whisper mode	37 dB (typ); 30 dB (typ)
DIMENSIONS (W x H x D)	Physical (mm)	121mm x 47mm x 99mm
	Physical (in.)	4.76" x 1.85" x 3.9" (without battery)
WEIGHT	Net	1.0 lb. (without battery) (0.45 kg)
	Gross	3.6 lb. (1.6 kg)
REGULATIONS		UL, C-UL, FCC-B, TUV/GS, CCC, CB, CE, NOM, PSE, VCCI, BSMI
OTHER		Vertical digital keystone correction, progressive scan, 3:2 pull down, whisper mode
PACKAGE CONTENTS		Projector, Lithium-ION rechargeable battery, AC/DC adapter, composite video cable, power cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with user guide), soft case

ViewSonic®

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***See ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12722-00B-12/05] PJ106D-1

For more product information, visit us on the web at ViewSonic.com

Download from Www.Somanuals.com. All Manuals Search And Download.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>