

Product: DocuPrint 900 / 1300 IE/XE

PSDS No.: 0841
ISSUE DATE: 07/13/00
REV. DATE:

Section I - Product Identification

Manufacturer's Name
 Delphax a Xerox Company

Emergency No. EH&S Inquiries
 (585) 422-2177 (800) 828-6571

Manufacturer's Address
 5030 Timberlea Blvd
 Mississauga, Ontario L4W 2S5
 Canada

Product Designation
 DocuPrint 900 / 1300

Product Code
 N/A

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)	Branch Cir. Protection (Amps)
Printer: 230	40	60	60
Motor Drive: 230 3-phase	16	60	30
Fuser: 230, 3-phase	45	60	100

Post processing not included. It varies with equipment/vendor.

Line Cord/Plug Specification
 Line Cords not provided
 Hard wired to the branch circuits
 Post processing not included. Varies with equipment/vendor.

Power Consumption (Watts)*
 Running: 24,000
 Standby: 2,400

Agency Approval
 UL1950 + D3
 CUL C22.2 No. 950 + D3
 UL File Number E193942 Vol. 1, Sec. 1-Printer, Section 2 - Fuser

Section III - Supplies

	Xerox Part No.	Material Safety Data Sheet
CRU (Black Toner)	6R973	A-0626

Section IV - Environmental Information

Product Size	Heat Emission* (BTU/HR)	Environmental Limitations		
		Min	Max	
Configuration: (Centimeters/Inches) Minimum printer configuration Consists of 9 cabinets. Refer to Installation guide for dimensions	Running: 82,000 Standby: 8,200	Relative Humidity (%) Ambient Temp. (°C)	40 20	60 26

* Based on a five minute average

PRODUCT: DocuPrint 900 / 1300

PSDS No. 0841

Floor Space Requirements

(Meters / Feet)
15.85 X 5.3 / 52 x 17.5

Weight

(K Grams / Lbs.)
7,002 / 15,411

Section V - Emission/Exposure Information*

Light Source

Infrared light, not accessible to operator

Electromagnetic Emissions

US FCC: 47 CFR Part 15 Class A
Canada IC: ICES – 003 Class A

Audible Noise

			TLV**
			85 db (A)
		DocuPrint 900	DocuPrint 1300
Printing:	dB(A)	71 dB(A)	77 dB(A)
Standby:	dB(A)	55 dB(A)	58 dB(A)
Impulse	N/A – the noise source has been eliminated		
Report No. X9800261			
TUV Report No. E9973380.01/02			

Ozone

Concentration (printing at 1,300 images/minute)
Daily Volume 13,000 x 60 x 8 images
½ Air Room Change per Hour

<0.05 ppm (TWA)
(STEL) – not measured could be as high as 0.2 ppm near the source.

TLV

0.1 ppm

Total Dust

0.070 mg/m³

TLV

0.1 mg/m³

* Based on a five minute average

** **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time-Weighted Average) for a normal eight-hour workday.

07/13/00

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>