# **TECRA 8000**



**TOSHIBA** 

FRIEND

# **NEW POWER IN A STANDARD PLATFORM** The new Tecra series now features an improved power base.

with its 400Mhz Pentium® II processor. And we've given Tecra DVD facility and built in web ready attachments, so your next multimedia presentation can't fail to impress. What's more, Tecra offers a range of models to fit across all usage requirements.

†Notebooks Over Desktops: A TCO/Benefits Perspective. USA, September 22, 1998. MBS: SPA-05-7813.



## Tecra 8000 Series

Intel® Mobile Celeron™ Processor 333MHz or 400MHz - 128Kb internal L2 Cache

Intel® Mobile Pentium® II Processor - 366MHz (1.6V) - 256Kb internal L2 Cache - 400MHz (1.6V) - 256Kb internal L2 Cache 32KB primary L1 cache

64MB expandable to 256MB

66MHz Front Side Bus

Synchronous DRAM (SDRAM) 64-bit memory Two expansion memory slots (At least one slot is configured with standard memory)

#### System Archite PCI Bus V2.1

Intel® 440BX system chipset

**Storage Devices** 

Total storage capacity from 6 - 16 billion bytes Internal Primary 6.4 or 10 billion byte Enhanced IDE hard disk drive.

SelectBay™ Second or Backup 4, 6.4 billion byte Enhanced IDE hard disk drive

Hard Disk interfaces support Bus Master IDE and UltraDMA modes

Primary drive bay accomodates 17mm or 12.7mm height hard disk drive and 12.7mm height hard disk drive in SelectBay™ Internal SelectBay™ Max.24X-speed CD-ROM

Internal SelectBay  $^{\text{TM}}$  Max.2X-speed DVD-ROM and CD-ROM\*\* Internal SelectBay™ or external 1.44MB 3.5″

Windows '98 Hot Swap for SelectBay™ devices

NeoMagic NM2200 256-Bit display controller 2.5MB integrated SGRAM PCI local bus

# **Internal Display**

13.3" Active matrix TFT display at 1024 x 768 resolution 14.1" Active matrix TFT display at 1024 x 768 resolut

Simultaneous display of up to 16 million colours

# **External Display Support**

Simultaneous display up to 1200 x 1024 resolution. (15 Pin VGA connector) Software selectable PAL video out Multiple resolution support when using Win'98

# Keyboard

Full Function, standard key-spaced, 84 key sculptured keyboard Dedicated Windows keys Accupoint integrated pointing device

# Multimedia

Yamaha OPL3SA3 Sound Processor Two inbuilt stereo speakers CD-ROM drive or DVD-ROM drive \*\* Volume Control Integrated Microphone

Sound Blaster Pro compatible

\*\*DVD not available with Integrated Modem models Communications\*\*

Integrated V.90 56K DSVD modem - DAA RJ11 port on side of system with DAA models Integrated 10/100 Ethernet controller in optional Port Replicator

## Expansion

Two PC Card Slots supporting two Type II (5mm) PC Cards or 1 x Type III (10.5mm) 32-bit CardBus ready One Universal Serial Bus (USB) Port One 9 Pin RS-232C (16550 UART) Serial Port

Parallel Printer Port (ECP) Connector for external SVGA display Composite Video-out port (PAL/NTSC) Fast Infrared Port (Irda1.1 = 4Mbps)

PS/2 Keyboard or Mouse port (Y connector supported) Headphone jack Microphone jack

Line-In jack 240 pin docking connector

#### 10/100 Network Port Replicator PA2724U E

10/100Mbps RJ45 Fast Ethernet Port using Intel® 82558 LAN controller Wake and Alert on LAN system management Intel® LAN Desk Client Manager

One 9 Pin RS-232C (16550 UART) Serial Port 15 Pin Joystick Port Parallel Printer Port (ECP) Two Universal Serial Bus (USB) Ports

Connector for external SVGA display PS/2 Mouse Port PS/2 Keyboard Port

#### Headphone Microphone

Line in and Line out jack - 3.5mm **Enhanced Port Replicator II - PA2716U YN** 

#### Two PC Card Slots supporting two Type II (5mm) PC Cards or 2 x Type III (10.5mm)

32-bit CardBus ready One 9 Pin RS-232C (16550 UART) Serial Port 15 Pin Joystick Port Parallel Printer Port (ECP)

Connector for external SVGA display PS/2 Mouse Port PS/2 Keyboard Port Headphone Microphone

Line in and Line out jack - 3.5mm Kensington Lock AC Adapter

# Enhanced Port Replicator III - PA2717U YN / PA2721U

Two PC Card Slots supporting two Type II (5mm) PC Cards or 2 x Type III (10.5mm) 32-bit CardBus ready

One 9 Pin RS-232C (16550 UART) Serial Port Two USB ports

Floppy Drive Connector (not operational) 15 Pin Joystick Port Parallel Printer Port (ECP)

Connector for external SVGA display PS/2 Mouse Port PS/2 Keyboard Port Headphone

Microphone Line in and Line out jack - 3.5mm Kensington Lock and key security AC adapter

Tecra / Enhanced Port Replicator III Adapter - PA2721U

## **Power System**

Lightweight removable, rechargeable Li Ion battery (40.5Wh) Battery life 3+ hours\* Battery recharge 2.2+ hours Worldwide auto-sensing AC Adapter

# Security

Keyboard lock Hard Disk access password utility - available on request Power on password (2-level password)

Kensington cable lock slot

## Reliability

Carbon Reinforced ABS Plastic Internal structural bracing Vibration and corrosion proof Anodised Screws sealed with  $\mathsf{Loctite}^{\mathsf{TM}}$ Shock Proof mounting for Hard Disk and Display Active Thermal Management

# Compatibility

DMI 2.0 BIOS Support with Asset Tagging Wired for Management V1.1a, Wake On LAN, Alert On LAN, Remote Service Boot, ACPI power Management Year 2000 compliant

#### **Standard Packaging Includes** Tecra 8000 system

CD-ROM or DVD-ROM Drive\*\*

Choice of Windows '95 and Windows '98 or Windows NT4.0 operating system Windows '95, '98 and NT4.0 utilities for Toshiba enhanced capabilities. Recovery CD for Win'95 and Win'98 or Windows NT4.0 Intel® Lan Desk Client Manager Lithium Ion battery Integrated diskette drive Hard Disk Drive

Weight Saver Secondary Battery Holder AC adapter with power cord Tecra 8000 Series User Guide

## **Dimensions and Weight**

311mm (Width) x 42mm (Height) x 254mm (Depth) 2.9 kg including CD-ROM or DVD-ROM\*\*

3 Year domestic and international parts and

#### **Order Numbers**

labour warranty

PAT80AA-7963 Cel333MHz,13.3"TFT,64MB,6GB,CD,W95/98,DAA PAT80AA-796A Cel333MHz,13.3"TFT,64MB,6GB,CD,Win NT4,DAA PAT80AA-G963 Cel400MHz,14.1"TFT,64MB,6GB,CD,W95/98,DAA PATROAA-G96A Cel400MHz.14.1"TFT.64MB.6GB.CD.Win NT4.DAA PAT800A-K963 PII366MHz,14.1"TFT,64MB,6GB,CD,W95/98, DAA

PAT800A-K96A PII366MHz,14.1"TFT,64MB,6GB,CD,Win NT4, DAA PAT800A-KB63 PII366MHz,14.1"TFT,64MB,10GB,CD,W95/98, DAA

PAT800A-KB6A PII366MHz,14.1"TFT,64MB,10GB,CD,Win NT4, DAA PAT80AA-4B63 PII400MHz,14.1"TFT,64MB,10GB,CD,W95/98, DAA PAT80AA-4R64

PII400MHz,14.1"TFT,64MB,10GB,CD,Win NT4, DAA KTT8000/32 32MB SDRAM Memory

KTT8000/64 64MB SDRAM Memory KTT8000/128 128MB SDRAM Memory PA2724U E 10/100 Network Port Replicator PA2710E Deskstation V Plus PA2716U YN Enhanced Port Replicator II PA2717U YN Enhanced Port Replicator III

(requires Enhanced Port Rep III adapter) PA2721U Enhanced Port Rep III adapter PA2510U Battery Pack (primary Li-lon) Second Battery Pack for SelectBay™ (Li-lon) PA2451U

PA2509U Battery Charger PA2450U Y Universal AC Adapter PA2667U 4GB Primary or SelectBay™ HDD\*\*\* PA2668U 6GB Primary or SelectBay™ HDD\*\*\* PA2672U 10GB Primary HDD PA2666U \*\*\*SelectBay™ Adapter for HDD in SelectBay™

PA2665U 24X CD-ROM Drive Kit PA2664UB DVD Drive and MPEG Decoder Kit (Dealer Installable) DPS40/15 Auto Power Adapter Executive Style Koskin Carry Case Briefcase Friend Koskin Carry Bag Classic Leather Carry Bag

Hardcase

Toshiba Australia Information Systems Division 7/99

Metallic Hard Carry Case

Please direct all enquires to:



Toshiba (Australia) Pty. Limited ACN 001 320 421 NB: \*Battery Life depends on usage and is measured using PC Magazine BatteryMark. Specifications subject to change without notice. \*\* DVD MPEG Decoder and Integrated Modem cannot be installed together. Toshiba is not responsible for errors in typography or photography arks and are prop

respective owners. Battery is eligible for 12 months domestic warranty only

TOSHIBA

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com