

FlexWave™ MMW 110

Millimeter Wave Transmission System



FlexWave MMW 110 is a point-to-point millimeter wave transmission system that operates in the licensed 71 GHz to 86 GHz spectrum and provides fiber-speed wireless Line of Sight (LOS) communications links within a 1 – 6 km range. The MMW 110 features a 10" lens making the product suitable to mount on electric poles and any other medium without the restrictions of high pointing stability. The MMW 110 has the largest beam width allowed by the FCC in the 71-86 GHz band (1.2 deg.).

FlexWave MMW key features

- High Availability (99.999%)
- Best-in-class link performance
- High Capacity (3.072 Gbps)
- Reduced cost per bit due to the inherent cost- and data-efficiency of native Ethernet
- Same cost as microwave but with 10x higher bandwidth
- Simple and quick install

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891



FlexWave™ Millimeter Wave 110

1/08 • 105719AE FlexWave® Millimeter Wave 110

FlexWave MMW wireless links address the increasing shortage in metro access capacity by taking advantage of the recently allocated licensed 71-86 GHz spectrum. By using the unique propagation characteristics and the wide bandwidth of the spectrum, FlexWave MMW can support extremely high speed data transmission for short communication links.

FlexWave MMW provides fiber equivalent performance, 99.999% reliability and security, without the high installation costs and delays associated with inter-building fiber installations. FlexWave MMW can be engineered to operate in close proximity to other FlexWave MMW systems so that many links can co-exist in the same vicinity without causing interference to one another. FlexWave MMW is driving Ethernet beyond the office and into the metro enabling the move towards a single, scalable, end-to-end communications technology.

Applications

FlexWave MMW can be used for various access and backhaul applications.

Access

- Fiber Extension: Enterprise point-to-point, last mile and first mile connections
- Campus Connectivity
- Remote Storage Access
- Redundant Access / Network Diversity
- Metropolitan Area Networks (MAN)
- Disaster Recovery
- Homeland Security

Backhaul

- Mobile, WiMAX & Muni-Wi-Fi Backhaul
- Distributed Antenna Systems (DAS) / Remote Radio Head (RRH) Fronthaul

The MMW 110 features a 3.072 Gbps data-rate technology. To the network the MMW radios will look and feel just like traditional fiber optic cable. Since the MMW systems are Layer 1 and protocol agnostic, they will interoperate with most commercial off the shelf (COTS) switches, routers and encryption devices.

- MMW 110 radios have Web/Java based monitoring. Accessible data includes: Signal Strength via AGC (Automatic Gain Control), Environmental (Temperature, Power, etc), Fiber Status and Frame Error Counters.
- The MMW 110 uses SNMP v1 to v3 for link management.



FlexWave™ Millimeter Wave 110

Specifications

FlexWave® Millimeter Wave 110
1 / 0 8 • 1 0 5 7 1 9 A E

Frequency Band:	71 – 76 GHz; 81 – 86 GHz
RF Interface:	FDD
Modulation:	BPSK
Latency:	<50 microseconds
Forward Error Correction:	n/a
PHYSICAL	
Weight:	Radio + antenna + bracket: 20 kg (44 lbs)
Dimensions:	Radio + antenna: 14" diameter x 26" length (35.5 cm x 66 cm)
TRIBUTARY	
Data Rate:	3.072 Gbps full duplex Ethernet
Standards Compliance:	IEEE 802.3z
Interface:	Fiber, 1310nm SM and 850nm MM / LC connector
Optional Ethernet Interface:	1000Base-SX with RJ-45 connector
ELECTRICAL	
Input Voltage:	-48 VDC (-40.5 to -57VDC); 120 VAC 60 Hz (provided by external supply)
Power Consumption:	50 Watt
ENVIRONMENTAL	
Temperature Range:	-22° to +131°F (-30° to +55°C)
Altitude:	15,000 ft (4500 m)
Outdoor Unit:	All Weather
MANAGEMENT	
	Web/Java based monitoring EMS SNMP v1, v2c, v3
REGULATORY	
FCC:	1.1310 RF MPE limits part 101
ANTENNA	
	10" Lens >43 dBi <1.2°BW
MOUNTING OPTIONS	
	Fine adjust pole mount fitting 2.5" to 5" OD (6.4 cm x 12.7 cm) Wall-mount and tripod

Ordering Information

Description	Catalog Number
MMW System; Vertical polarization, -48 VDC, 10" Lens and Mounting Kit	
Any Rate Full Duplex up to 1.536 Gbps	
Singlemode fiber interface	MMW-100-VSD-SYS
Multimode fiber interface	MMW-100-VMD-SYS
Full Duplex 3.072 Gbps	
Singlemode fiber interface	MMW-110-VSD-SYS
Multimode fiber interface	MMW-110-VMD-SYS

*Product manufactured by LOEA Corporation.

SPEC SHEET



Website: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080
Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our website.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

105719AE 1/08 Original © 2008 ADC Telecommunications, Inc. All Rights Reserved

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>