

## Acer Monitors

	Value Line		Value Line - Wide Screen				
	V173B	V193	X153W	V193W	V203W	V223W	V243W
							
<b>Part Number</b>	ET.BV3RE.005	ET.CV3RE.005	ET.AX3WE.004	ET.CV3WE.005	ET.DV3WE.010	ET.EV3WE.010	ET.FV3WE.010
<b>Display Size</b>	17"	19"	15.6" wide	19" wide	20" wide	22" wide	24" Wide
<b>Display Dimensions</b>	338 x 270 mm	376 x 301mm	TBA	408 x 255mm	433 x 270 mm	473x296 mm	547x352mm
<b>Pixel Pitch</b>	0.264mm	0.294mm	0.258mm	0.284mm	0.258 mm	0.282 mm	0.270 mm
<b>Resolution</b>	1280 x 1024	1280 x 1024	1280x800	1440 x 900	1680 x 1050	1680x1050	1920 X 1200
<b>Brightness (typ.)</b>	300 cd/m2	300 cd/m2	200 cd/m2	300 nits (cd/m2)	300 cd/m2	300 cd/m2	300 cd/m2
<b>Contrast Ratio (typ.)</b>	2000:1 (ACM)	2000:1 (ACM)	400:1	2000:1 (ACM)	2500:1 (ACM)	2500:1 (ACM)	3000:1 (ACM)
<b>Max. Refresh Rate</b>	75Hz	75Hz	60Hz	75Hz	75Hz	75Hz	75MHz
<b>Viewing Angle (typ.)</b>	160° (H), 160° (V)	160° (H), 160° (V)	90°(H),50°(V)	160° (H), 160° (V)	160° (H), 160° (V)	160°(H), 160°(V)	160° / 160°
<b>Response Time (typ.)</b>	5ms	5ms	8ms	5ms	5ms	5ms	5ms
<b>Input Signal</b>	VGA (Analog D-sub)	VGA (Analog D-sub)	VGA (Analog D-sub)	VGA (Analog D-sub)	VGA (Analog D-sub), DVI Optional	VGA (Analog D-sub), DVI (optional)	Analog (VGA)
<b>Speaker</b>	No	No	No	No	No	No	No
<b>Power Adapter (100V-240V)</b>	Internal	Internal	Internal	Internal	Internal	Internal	Internal
<b>Power Consumption</b>	<35W	<35W	TBA	<37W	<39W	<45W	<90W
<b>Dimensions (WxHxD mm)</b>	370.2 x 376 x 160.2 mm	408 x 406.8 x 180.4 mm	377x320.5x159	441.8 x 360.1 x 161	471.5 x 376 x 108.3	506x399x180	562.4 x 368 x 210.3
<b>Weight (kg)</b>	3.75	3.91	2.73	4.3	5.5	5.2	6.55
<b>Kensington Lock</b>	Supported	Supported	Supported	Supported	Supported	Supported	Supported
<b>VESA Wall Mounting</b>	75 x 75 mm	75 x 75 mm	75 x 75 mm	75 x 75 mm	100 x 100 mm	100 x 100 mm	101 x 100 mm



## Acer Monitors – Premium Home Wide Screen

P193W



P203W



P223Wxd



P223W



P243WB








Part Number	ET.CP3WE.014	ET.CV3RE.005	ET.EP3WE.024	ET.EP3WE.024	ET.FP3WE.A01
Display Size	19" Wide	20" Wide	22" Wide	22" Wide	24" wide
Display Dimensions	408x255mm	433x270mm	473x296 mm	473x296 mm	547x352 mm
Pixel Pitch	0.284mm	0.258mm	0.282mm	0.282mm	0.270 mm
Resolution	1440x900	1680x1050	1680x1050	1680x1050	1920x1200
Brightness (typ.)	300 cd/m2	300 cd/m2	200 cd/m2	200 cd/m2	400 cd/m2
Contrast Ratio (typ.)	2000:1 (ACM)	2500:1 (ACM)	2500:1 (ACM)	2500:1 (ACM)	3000:1 (ACM)
Max. Refresh Rate	75Hz	75Hz	60Hz	60Hz	60Hz
Viewing Angle (typ.)	160° (H), 160° (V)	160° (H), 160° (V)	170°(H),160°(V)	170°(H),160°(V)	170° (H), 160° (V)
Response Time (typ.)	5ms	5ms	5ms	2ms	2ms GTG/5ms
Input Signal	VGA and DVI / HDCP	VGA and DVI / HDCP	VGA and DVI / HDCP	VGA and DVI / HDCP	VGA and DVI / HDCP
Speaker	No	No	No	No	No
Power Adapter (100V-240V)	Internal	Internal	Internal	Internal	Internal
Power Consumption	<37W	<49W	<45W	<45W	<39W
Dimensions (WxHxD mm)	454.3x359.2x163.7 mm	517.5x400.1x177.4 mm	517.5x400.1x177.4	517.5x400.1x177.4	572x431x190
Weight (kg)	4.4	5.25	5.25	5.25	7
Kensington Lock	Supported	Supported	Supported	Supported	Supported
VESA Wall Mounting	100 x 100 mm	100 x 100 mm	100 x 100 mm	100 x 100 mm	100 x 100 mm




## HP TFT Monitors – Essential Series

	17"	19" Wide	22" Wide
			
<b>Model Number</b>	<b>L1710</b>	<b>L1908w</b>	<b>L2208w</b>
<b>Product Number</b>	<b>GS917AA</b>	<b>GP536AA</b>	<b>GX007AA</b>
<b>Resolution</b>	1280x1024 @ 60Hz	1440 x 900 @ 60 Hz	1680 x 1050 @ 60 Hz
<b>Front Bezel Colours</b>	Carbon & Silver	Carbon & Silver	Carbon & Silver
<b>Response Rate</b>	5 ms	≤5 ms	5 ms
<b>Technology</b>	Active Matrix TFT	Wide-Aspect Active Matrix TFT	Wide-Aspect Active Matrix TFT
<b>Viewing Angle</b>	160/160	160/160	160/160
<b>Brightness</b>	300 nits	300 nits	300 nits
<b>Interface</b>	VGA	VGA	VGA
<b>TCO99/E-Star</b>	✓/✓	✓/✓	✓/✓
<b>Warranty</b>	3/3/3	3/3/3	3/3/3
<b>Dimensions</b>	<i>Unpacked</i> 38.6 x 37.7 x 19.2 cm <i>Packed</i> 43.7 x 44.8 x 17.5 cm	<i>Unpacked</i> 37.0 x 44.6 x 18.7 cm <i>Packed</i> 42.3 x 53.6 x 17.4 cm	<i>Unpacked</i> 41.46 x 51.48 x 19.2 cm <i>Packed</i> 48.1 x 59.5 x 19 cm
<b>Weight</b>	<i>Unpacked</i> 4.7 kg <i>Packed</i> 6.1 kg	<i>Unpacked</i> 5.63 kg <i>Packed</i> 6.45 kg	<i>Unpacked</i> 5.41 kg <i>Packed</i> 7.51 kg
<b>Speaker Bar Option</b>	<b>EE418AA</b>	<b>EE418AA</b>	<b>EE418AA</b>

## HP TFT Monitors – Performance Series

	19"	20"	24"	30"
				
<b>Model Number</b>	<b>LP1965</b>	<b>LP2065</b>	<b>LP2475w</b>	<b>LP3065</b>
<b>Product Number</b>	<b>RA374AA</b>	<b>EF227AA</b>	<b>KD911A4</b>	<b>EZ320A4</b>
<b>Resolution</b>	1280x1024 @ 60Hz	1600x1200 @ 60Hz	1920x1200 @ 60Hz	2560x1600 @ 60 Hz
<b>Response Rate</b>	6 ms	8 ms	6 ms (gray to gray); 12 ms (on/off)	12 ms
<b>Front Bezel Colours</b>	Carbon & Silver	Carbon & Silver	Carbon & Silver	Carbon & Silver
<b>Technology</b>	Active Matrix TFT	Active Matrix TFT	Wide Active Matrix TFT	Wide Active Matrix TFT
<b>Viewing Angle</b>	178/178	178/178	178/178	178/178
<b>Brightness</b>	300 nits	300 nits	400 nits	300 nits
<b>Interface</b>	Dual DVI-I	VGA/DVI-I	Dual DVI-I	3 x Dual Link DVI-D
<b>TCO99/E-Star</b>	✓/✓	✓/✓	✓/✓	✓/✓
<b>Warranty</b>	3/3/3	3/3/3	3/3/3	3/3/3
<b>Multimedia</b>	✓	✓	✓	✓
<b>USB Ports</b>	5	5	5	5
<b>Pitch</b>	0.294mm	0.255mm	0.270mm	0.250mm
<b>Dimensions</b>	<i>Unpacked</i> 39.8 x 48 x 23 cm <i>Packed</i> -	<i>Unpacked</i> 34.5 x 44.3 x 8.7 cm <i>Packed</i> 29.9 x 56.4 x 42.6 cm	<i>Unpacked</i> 42.16 to 52.16 x 55.64 x 25.3 cm <i>Packed</i> 35.2 x 67.2 x 46.4 cm	<i>Unpacked</i> 45.5 x 69.2 x 8.4 cm <i>Packed</i> 56.8 x 79.0 x 37.8 cm
<b>Weight</b>	<i>Unpacked</i> 7.06 kg <i>Packed</i> 9.27 kg	<i>Unpacked</i> 9.2 kg <i>Packed</i> 11.95 kg	<i>Unpacked</i> 9.1 kg <i>Packed</i> 12 kg	<i>Unpacked</i> 13.9 kg <i>Packed</i> -
<b>Speaker Bar Option</b>	<b>EE418AA</b>	<b>EE418AA</b>	<b>EE418AA</b>	<b>EE418AA</b>

## HP TFT Monitors – Advantage Series

	19"	22" Wide
		
<b>Model Number</b>	<b>L1950g</b>	<b>L2245w</b>
<b>Product Number</b>	<b>KR145AA</b>	<b>GX008AA</b>
<b>Resolution</b>	1280x1024 @ 75 Hz	1680 x 1050 @ 60Hz
<b>Response Rate</b>	5 ms	5 ms
<b>Front Bezel Colours</b>	Carbon & Silver	Carbon & Silver
<b>Technology</b>	Active Matrix TFT	Wide-Aspect Active Matrix
<b>Viewing Angle</b>	160/160	160/160
<b>Brightness</b>	300 nits	300 nits
<b>Interface</b>	VGA/DVI-I	VGA/DVI-D
<b>TCO99/E-Star</b>	✓/✓	✓/✓
<b>Warranty</b>	3/3/3	3/3/3
<b>USB Ports</b>	2	2
<b>Pitch</b>	0.294	0.282
<b>Dimensions</b>	<i>Unpacked</i> 37.8 x 41.4 x 30.1 cm <i>Packed</i> 56.5 x 42.0 x 22.6 cm	<i>Unpacked</i> 37.09 x 51.48 x 30.12 cm <i>Packed</i> 41.7 x 61.2 x 22.7 cm
<b>Weight</b>	<i>Unpacked</i> 7.3 kg <i>Packed</i> 9.1 kg	<i>Unpacked</i> 7.73 kg <i>Packed</i> 9.27 kg
<b>Speaker Bar Option</b>	<b>EE418AA</b>	<b>EE418AA</b>

## LG LCD Monitors - 4:3 format

### 4:3 Format

### Multi-Link Solution

17"



17"



19"



19"













20"W



	Code	LGL1734S-BN	LGL1719S-BF	LG1918S-BN	LG1919s-BF	LGL206WU-WF
<b>Colour</b>		Black	Black	Black	Black	Black and White
<b>Brightness</b>		300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)
<b>Contrast Ratio</b>		700:1 (typical)	5000:1 (DFC)	700:1 (typical)	5000:1 (DFC)	5000:1 (DFC)
<b>Response Time</b>		5ms	5ms	5ms	5ms	2ms
<b>Viewing Angle H/V</b>		170/170	170/170	160/160	170/170	170/170
<b>Supported Colours</b>		16.2M	16.2M	16.2M	16.2M	16.7M
<b>Resolution</b>		1280x1024(SXGA)	1280x1024(SXGA)	1280x1024(SXGA)	1280x1024(SXGA)	1680 x 1050
<b>Connector</b>		15pin D-Sub	15pin D-Sub	15pin D-Sub	15pin D-Sub	USB
<b>Dimension (WxHxD) (Box)</b>		420x132x378mm	376x180x380mm	478x131x429mm	469x116x394mm	557 x 244 x 379 mm
<b>Weight (Box)</b>		4Kg	6Kg	6Kg	5Kg	6Kg
<b>Special features</b>		Tilt, Wall Mount- (75x75)	Tilt, Wall Mount- (75x75)	Tilt, Wall Mount- (75x75)	Tilt, Wall Mount- (75x75)	F-engine, HDCP, 4:3 in wide, Pivot 90, height adjustment, Tilt Swivel, Vesa (100 x 100)



## LG LCD Monitors - Widescreen

	W42 Series			W52 Series	
	19" W	22"	19" W	19" W	22"
					
					
<b>Code</b>	LGW1934S-BN	LG-W2252WTQ-PF	LG-W1942S-PF	LGW1952TQ	LGW2252TQ-PF
<b>Colour</b>	Black	Black	Black	Black	Black
<b>Brightness</b>	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)	300 cd/m <sup>2</sup> (Typical)
<b>Contrast Ratio</b>	1000:1 (DFC)	8000:1 (DFC)	8000:1 (DFC)	10000:1 (DFC)	10000:1 (DFC)
<b>Response Time</b>	5ms	5ms	5ms	2ms	2ms
<b>Viewing Angle H/V</b>	170/170	170/170	170/170	170/170	170/170
<b>Supported Colours</b>	16.7M	16.7M	16.7M	16.7M	16.7M
<b>Resolution</b>	1440 x 900(WXGA+)	1680 x 1050(WSXGA+)	1440 x 900(WXGA+)	1440 x 900(WSXGA+)	1680 x 1050(WSXGA+)
<b>Connector</b>	15pin D-Sub	15pin D-Sub	15pin D-Sub	15pin D-Sub, DVI-D	15pin D-Sub, DVI-D
<b>Dimension (WxHxD) (Box)</b>	514 x 141x 380mm	574 x 127 x 407 mm	511 x 119 x 395 mm	511 x 140 x 395 mm	582 x 127 x 449mm
<b>Weight (Box)</b>	4Kg	6Kg	4Kg	4Kg	5Kg
<b>Special features</b>	4:3 in wide, Tilt, Wall Mount (75 x 75)	F-engine, HDCP, 4:3 in wide, Tilt, Wall Mount- (75 x 75)	F-engine, HDCP, 4:3 in wide, Tilt, Wall Mount- (75 x 75)	F-engine, HDCP, 4:3 in wide, ez-Zooming, Photo effect, Tilt	F-engine, HDCP, 4:3 in wide, ez-Zooming, Photo effect, Wall Mount- (100 x 100)

## Samsung Monitors

	632NW	720N	732NW	953BW	920NW	932GW	2053BW	2032GW
								
								
<b>Part Number</b>	LS16PENSF/ZAT	LS17MJVKS/ZAT	LS17PENSF/XSG	LS19AQWKFV/ZAT	LS19HANKSM/EDC	LS19PEJSFL/ZAT	LS20AQWJFV/ZAT	LS20PEJSFV/XSH
<b>Display</b>	Screen size 15.6" Wide Brightness 250 cd/m <sup>2</sup> Contrast Ratio Static 500:1 (DC 2000:1) Resolution 1360x768 Response Time 8ms Viewing Angle(Horizontal/Vertical) 90/65 (CR>10) Colour Supported 16.7Mil.	17" 300 cd/m <sup>2</sup> 700:1 1280x1024 5ms 170°/155°(CR>5)	17" Wide 250 cd/m <sup>2</sup> 600:1 1440x900 8ms 160°/160°	19" 300 cd/m <sup>2</sup> DC 8000:1(1000:1)(Typ.) 1440 x 900 5ms, 2ms(GTG) 170°/160° (CR>10)	19" wide 300 cd/m <sup>2</sup> 700:1 1440x900 5ms 160°/160° (CR>5)	19" Wide 300 cd/m <sup>2</sup> 1000:1 (DC 3000:1) 1440x900 2ms(GTG) 160°/160° (CR>10), 170°/170° (CR>5)	20" Wide 300 cd/m <sup>2</sup> DC 8000:1(1000:1) (Typ.) 1680x1050 5ms, 2ms(GTG) 170°/160° (CR>10)	20" Wide 300 cd/m <sup>2</sup> DC 3000:1 (1000:1) 1680x1050 2(GTG) 170°/170° (CR>5)
<b>Signal Input</b>	Video Signal Analog RGB Sync. Signal Separate H/V, Composite, SOG Connector 15pin D-sub	Analog RGB Separate H/V, Composite, SOG 15pin D-sub	Analog RGB Separate H/V, Composite, SOG 15pin D-sub	Analog RGB, DVI Separate H/V, Composite, SOG 15pin D-SUB, DVI-D	Analog RGB Separate H/V, Composite, SOG 15pin D-sub	Analog RGB, Digital Separate H/V, Composite, SOG 15pin D-sub, DVI-D	Analog RGB, DVI Separate H/V, Composite, SOG 15pin D-SUB, DVI-D	Analog RGB, DVI Separate H/V, Composite, SOG 15pin D-SUB, DVI-D
<b>Power</b>	Power consumption 18 Watt Stand by Power(DPMS) less than 1 watt Type Built-in Plug & Play DDC 2B	34 Watt (Max) <1W Built-in DDC CI	20 Watt (Max) <1W Built-in DDC 2B	34 Watt <1W Built-in DDC 2B	42 Watt (Max) <1W Built-in DDC 2B	42 Watt (Max) <1W Built-in DDC 2B	40 Watt <1W Built-in DDC 2B	50W <1W Built-in DDC 2B
<b>Features</b>	USB powered hub option ✓ Mac compatibility ✗ Multimedia Speakers ✓ Wall-Mount ✓ TCO -	✓ VESA 100mm TCO '99 -	✓ VESA 100mm TCO '99 -	✗ ✓ ✗ VESA 75mm -	✓ ✗ ✓ VESA 75mm TCO99 -	✗ ✓ ✗ ✗ ✗ -	✗ ✓ ✗ VESA 100mm -	✓ ✓ ✓ VESA 100mm -
	Cabinet Colour High Glossy Black	Silver	High Glossy Black	High Glossy Black	Silver	High Glossy Black	High Glossy Black	High Glossy Black
	Optional Accessories	Accessory, Signal Cable, Power Cord		DVI-D cable		DVI-D cable		DVI (HDCP), MagicBright3, High Glossy Black, Glare
	Special Features	MagicTune, MagicBright 3,	MagicBright	MagicTune, MagicBright2, Narrow Bezel	MagicWizard & MagicTune with AssetManagement, Windows Vista Premium, DVI with HDCP, Safe Mode (DownScaling in UXGA)	MagicBright2, Narrow Bezel	MagicTune, MagicBright3, Narrow Bezel	MagicWizard & MagicTune with AssetManagement, Windows Vista Premium, DVI with HDCP, Safe Mode (DownScaling in UXGA)
<b>Dimension</b>	Product Dimension (With Stand, Watt x H x D) mm 382 x 308 x 159 Product Dimension (Without Stand, Watt x H x D) mm 382 x 260 x 64 Shipment Dimension (Watt x H x D) mm 442 x 114 x 310	370 x 387.3 x 195 370 x 379 x 79 430 x 450 x 135	406 x 340 x 177 406 x 296 x 64 473 x 383 x 117	445.8 x 359.8 x 190 445.8 x 310 x 59.8 519 x 387 x 130	439 x 360.7 x 200 439 x 289 x 65.5 525 x 428 x 149	449 x 374 x 199 449 x 325 x 67 519 x 392 x 130	472.9 x 374.9 x 219 472.9 x 326.5 x 63 548 x 404 x 132	476 x 390 x 199 476 x 344 x 70 549 x 411 x 132
<b>Weight</b>	Product Weight 2.5 Shipment Weight 3.5	4.04kg (Net Weight) 5.05kg (Gross Weight)	2.8	3.9 kg 5.4 kg	4.7 6.3	4.1 5.4	4.4 kg 5.9 kg	4.74 kg 6.3 kg
<b>Stand</b>	Type Simple Function Tilt	Simple Tilt	Simple	Simple Tilt	Simple	Simple	Simple Swivel, Tilt	Simple Tilt

## Acer Projectors

**Acer X1160Z**



**Acer P1165**



**Acer P1265**



**Acer P3250**



	Acer X1160Z	Acer P1165	Acer P1265	Acer P3250
<b>Projection System</b>	DLP®	DLP®	DLP®	DLP®
<b>Resolution</b>	Native SVGA (800 x 600) Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)	Native SVGA (800 x 600) Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)	Native XGA (1,024 x 768) Maximum SXGA+ (1,400 x 1,050), WXGA+ (1,440 x 900)	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
<b>Computer Compatibility</b>	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
<b>Aspect Ratio</b>	4:3 (Native), 16:9	4:3 (Native), 16:9	4:3 (Native), 16:9	4:3 (Native), 16:9
<b>Contrast Ratio</b>	2000:1	2000:1	2000:1	2000:1
<b>Displayable Colours</b>	16.7 Million Colours	16.7 Million Colours	16.7 Million Colours	134 Million Colours
<b>Brightness</b>	2,000 ANSI Lumens	2,400 ANSI Lumens (Standard), 1,920 ANSI Lumens (ECO)	2,400 ANSI Lumens (Standard), 1,920 ANSI Lumens (ECO)	2,000 ANSI Lumens (Standard), 1,600 ANSI Lumens (ECO)
<b>Projection Lens</b>	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
<b>Projection Screen Size (Diagonal)</b>	23 (58cm) ~ 300 (762cm)	23 (58cm) ~ 300 (762cm)	23 (58cm) ~ 300 (762cm)	23 (58cm) ~ 300 (762cm)
<b>Projection Distance</b>	3.3' (1.0m) ~ 39.0' (11.9m)	3.3' (1.0m) ~ 39.0' (11.9m)	3.3' (1.0m) ~ 39.0' (11.9m)	3.3' (1.0m) ~ 39.0' (11.9m)
<b>Throw Ratio</b>	50@2m (1.95 ~ 2.15:1)	50@2m (1.95 ~ 2.15:1)	50@2m (1.95 ~ 2.15:1)	50@2m (1.95 ~ 2.15:1)
<b>Horizontal Scan Rate</b>	31k ~ 69k Hz	31.5 ~ 100 kHz	31.5 ~ 100 kHz	31.5 ~ 100 kHz
<b>Vertical Refresh Scan Rate</b>	50 ~ 85 Hz	56 ~ 85 Hz	56 ~ 85 Hz	56 ~ 85 Hz
<b>Lamp Type</b>	Osram 160 W user replaceable P-VIP lamp	Osram 180 W user replaceable P-VIP lamp	Osram 180 W user replaceable P-VIP lamp	Osram 165 W user replaceable P-VIP lamp
<b>Lamp Life</b>	4,000 Hours	3,000 Hours (Standard), 4,000 Hours (ECO)	3,000 Hours (Standard), 4,000 Hours (ECO)	3,000 Hours (Standard), 4,000 Hours (ECO)
<b>Keystone Correction</b>	+/-40 Degrees (Vertical)	+/-40 Degrees (Vertical)	+/-40 Degrees (Vertical)	+/-40 Degrees (Vertical)
<b>Projection Mode</b>	Front, Rear, Front-Ceiling, Rear-Ceiling	Front, Rear, Front-Ceiling, Rear-Ceiling	Front, Rear, Front-Ceiling, Rear-Ceiling	Front, Rear, Front-Ceiling, Rear-Ceiling
<b>Ceiling Mounting Capability</b>	Yes	Yes	Yes	N/A
<b>Audio</b>	N/A	One Internal Speaker with 2 watts Output	One Internal Speaker with 2 watts Output	One Internal Speaker with 2 watts Output
<b>Weight</b>	5 lbs (2.3 Kg)	6.6 lbs (3.0 Kg)	6.6 lbs (3.0 Kg)	2.6 lbs (1.2 Kg)
<b>Dimensions</b>	267 x 187 x 80 mm (10.5 x 7.4 x 3.1)	299 x 229 x 93 mm (11.8 x 9.0 x 3.7)	299 x 229 x 93 mm (11.8 x 9.0 x 3.7)	210 x 165 x 64 mm (8.3 x 6.5 x 2.5)
<b>Remote Control</b>	IR remote control	IR remote control with laser pointer & PgUp/PgDn functions	IR remote control with laser pointer & PgUp/PgDn functions	IR remote control
<b>Digital Zoom</b>	2X	2X	2X	2X
<b>PIP</b>	N/A	N/A	N/A	N/A
<b>Wireless</b>	N/A	N/A	N/A	N/A
<b>Power Supply</b>	AC input 100~240V auto-switching power supply	AC input 100~240V auto-switching power supply	AC input 100~240V auto-switching power supply	AC input 100~240V auto-switching power supply
<b>Power Consumption</b>	255 Watts (Operation), <8 Watts (Standby)	230 Watts (Operation), 10 Watts (Standby)	230 Watts (Operation), 10 Watts (Standby)	255 Watts (Operation), <5 Watts (Standby)
<b>Operating Temperature</b>	5°C ~ 35°C / 41°F ~ 95°F	5°C ~ 35°C / 41°F ~ 95°F	5°C ~ 35°C / 41°F ~ 95°F	5°C ~ 35°C / 41°F ~ 95°F
<b>Noise Level</b>	33 dBA	28 dBA (Standard mode), 24 dBA (ECO mode)	28 dBA (Standard mode), 24 dBA (ECO mode)	36 dBA (Standard mode), 33 dBA (ECO mode)
<b>Uniformity</b>	85%	90%	0.9	0.85
<b>Input Interface</b>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 1</li> <li>Composite Video (RCA) x 1</li> <li>S-Video (Mini DIN) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 1</li> <li>Composite Video (RCA) x 1</li> <li>S-Video (Mini DIN) x 1</li> <li>DVI (HDCP) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 1</li> <li>Composite Video (RCA) x 1</li> <li>S-Video (Mini DIN) x 1</li> <li>DVI (HDCP) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 1</li> <li>Composite Video (RCA) x 1</li> <li>S-Video (Mini DIN) x 1</li> <li>HDMI (Video, HDCP) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> </ul>
<b>Output Interface</b>		Analog RGB (D-sub) x 1 USB (Type B) x 1	Analog RGB (D-sub) x 1 USB (Type B) x 1	
<b>Control Interface</b>	USB (Type B) x 1	RS232 (Mini DIN) x 1	RS232 (Mini DIN) x 1	USB (Type B) x 1
<b>Standard Accessories</b>	<ul style="list-style-type: none"> <li>AC power cord; VGA cable; Composite video cable; Remote control; Battery for remote control; Lens cap; Carrying case; User's guide (CD-ROM); Quick start guide; Security card</li> </ul>	<ul style="list-style-type: none"> <li>AC power cord; VGA cable; Composite video cable; Remote control; Battery x 2 for remote control; Carrying case; User's guide (CD-ROM); Quick start guide; Security card</li> </ul>	<ul style="list-style-type: none"> <li>AC power cord; VGA cable; Composite video cable; Remote control; Battery x 2 for remote control; Carrying case; User's guide (CD-ROM); Quick start guide; Security card</li> </ul>	<ul style="list-style-type: none"> <li>AC power cord; VGA cable; Composite video cable; Remote control; Battery for remote control; Lens cap; Carrying case; User's guide (CD-ROM); Quick start guide; Security card</li> </ul>



## Acer Projectors

	Acer P5260i	Acer P7270i	Acer P7280
			
<b>Projection System</b>	DLP®	DLP®	DLP®
<b>Resolution</b>	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)	Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
<b>Computer Compatibility</b>	IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive), and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)	IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive), and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
<b>Aspect Ratio</b>	4:3 (Native), 16:9	4:3 (Native), 16:9	4:3 (Native), 16:9
<b>Contrast Ratio</b>	2000:1	2300:1	2300:1
<b>Displayable Colours</b>	134 Million Colours	1.07 Billion Colours	1.07 Billion Colours
<b>Brightness</b>	2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)	4,000 ANSI Lumens (Standard), 3,200 ANSI Lumens (ECO)	4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (ECO)
<b>Projection Lens</b>	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus	F = 2.52 ~ 2.79, f = 22.55mm ~ 27.06mm 1:1.2 Manual Zoom and Manual Focus	F = 2.52 ~ 2.79, f = 22.55mm ~ 27.06mm 1:1.2 Manual Zoom and Manual Focus
<b>Projection Screen Size (Diagonal)</b>	23 (58cm) ~ 300 (762cm)	31 (79cm) ~ 300 (762cm)	31 (79cm) ~ 300 (762cm)
<b>Projection Distance</b>	3.3 (1.0m) ~ 39.0 (11.9m)	3.9 (1.2m) ~ 31.4 (9.6m)	3.9 (1.2m) ~ 31.4 (9.6m)
<b>Throw Ratio</b>	50@2m (1.95 ~ 2.15:1)	63@2m (1.57 ~ 1.89:1)	63@2m (1.57 ~ 1.89:1)
<b>Horizontal Scan Rate</b>	31.5 ~ 100 kHz	27 ~ 92 kHz	27 ~ 92 kHz
<b>Vertical Refresh Scan Rate</b>	56 ~ 85 Hz	50 ~ 85 Hz	50 ~ 85 Hz
<b>Lamp Type</b>	Osram 200 W user replaceable P-VIP lamp	Osram 280 W user replaceable P-VIP lamp	Philips 330 W user replaceable P-VIP lamp
<b>Lamp Life</b>	3,000 Hours (Standard), 4,000 Hours (ECO)	2,000 Hours (Standard), 3,000 Hours (ECO)	2,000 Hours (Standard), 3,000 Hours (ECO)
<b>Keystone Correction</b>	+/-40 Degrees (Vertical)	+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal)	+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal)
<b>Projection Mode</b>	Front, Rear, Front-Ceiling, Rear-Ceiling	Front, Rear, Front-Ceiling, Rear-Ceiling	Front, Rear, Front-Ceiling, Rear-Ceiling
<b>Ceiling Mounting Capability</b>	Yes	Yes	Yes
<b>Audio</b>	One Internal Speaker with 2 watts Output	Two Internal Speaker with 3 watts Output	Two Internal Speaker with 3 watts Output
<b>Weight</b>	6.4 lbs (2.9 Kg)	11.9 lbs (5.4Kg)	12 lbs (5.4Kg)
<b>Dimensions</b>	299 x 229 x 93 mm (11.8 x 9.0 x 3.7)	404 x 315 x 120 mm (15.9 x 12.4 x 4.7)	404 x 315 x 120 mm (15.9 x 12.4 x 4.7)
<b>Remote Control</b>	IR remote control with laser pointer & PgUp/PgDn functions	IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions	IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions
<b>Digital Zoom</b>	2X	8X	8X
<b>PIP</b>	N/A	Yes	Yes
<b>Wireless</b>	Yes	Yes	N/A
<b>Power Supply</b>	AC input 100~240V auto-switching power supply	AC input 100~240V auto-switching power supply	AC input 100~240V auto-switching power supply
<b>Power Consumption</b>	275 Watts (Operation), 14 Watts (Standby)	360 Watts (Operation), 20 Watts (Standby)	410 Watts (Operation), 5 Watts (Standby)
<b>Operating Temperature</b>	5°C ~ 35°C / 41°F ~ 95°F	5°C ~ 35°C / 41°F ~ 95°F	5°C ~ 35°C / 41°F ~ 95°F
<b>Noise Level</b>	31 dBA (Standard mode), 25 dBA (ECO mode)	29 dBA (Standard mode), 27 dBA (ECO mode)- w/o dust filter	33 dBA (Standard mode), 29 dBA (ECO mode)- w/o dust filter
<b>Uniformity</b>	0.9	0.9	0.9
<b>Input Interface</b>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 1; Composite Video (RCA) x 1; S-Video (Mini DIN) x 1; DVI (HDCP) x 1; HDMI (Video, HDCP) x 1; PC Audio (Stereo mini jack) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 2; Composite Video (RCA) x 1; S-Video (Mini DIN) x 1; Component (3 RCA) x 1; HDMI (Video, Audio, HDCP) x 1; DVI (HDCP) x 1; PC Audio (Stereo mini jack) x 2</li> <li>Analog RGB (D-sub) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> <li>SPDIF Audio (RCA) x 1</li> <li>Network Audio (Stereo mini jack) x 1</li> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> <li>Wired remote control port (Mini jack) x 1</li> <li>802.11b/g wireless technology</li> <li>Ethernet port (RJ45) x 1</li> <li>Wireless antenna connector (SMA) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB/Component Video (D-sub) x 2; Composite Video (RCA) x 1; S-Video (Mini DIN) x 1; Component (3 RCA) x 1; HDMI (Video, Audio, HDCP) x 1; DVI (HDCP) x 1; PC Audio (Stereo mini jack) x 2</li> <li>Analog RGB (D-sub) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> <li>SPDIF Audio (RCA) x 1</li> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> <li>Wired remote control port (Mini jack) x 1</li> </ul>
<b>Output Interface</b>	<ul style="list-style-type: none"> <li>Analog RGB (D-sub) x 1</li> <li>Network Audio (Stereo mini jack) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB (D-sub) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> <li>SPDIF Audio (RCA) x 1</li> <li>Network Audio (Stereo mini jack) x 1</li> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> <li>Wired remote control port (Mini jack) x 1</li> </ul>	<ul style="list-style-type: none"> <li>Analog RGB (D-sub) x 1</li> <li>PC Audio (Stereo mini jack) x 1</li> <li>SPDIF Audio (RCA) x 1</li> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> <li>Wired remote control port (Mini jack) x 1</li> </ul>
<b>Control Interface</b>	<ul style="list-style-type: none"> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> </ul>	<ul style="list-style-type: none"> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> <li>Wired remote control port (Mini jack) x 1</li> <li>802.11b/g wireless technology</li> <li>Ethernet port (RJ45) x 1</li> <li>Wireless antenna connector (SMA) x 1</li> </ul>	<ul style="list-style-type: none"> <li>USB (Type B) x 1</li> <li>RS232 (Mini DIN) x 1</li> <li>Wired remote control port (Mini jack) x 1</li> </ul>
<b>Network Interface</b>	<ul style="list-style-type: none"> <li>802.11b/g wireless technology</li> <li>Ethernet port (RJ45) x 1</li> <li>Wireless antenna connector (SMA) x 1</li> </ul>	<ul style="list-style-type: none"> <li>802.11b/g wireless technology</li> <li>Ethernet port (RJ45) x 1</li> <li>Wireless antenna connector (SMA) x 1</li> </ul>	<ul style="list-style-type: none"> <li>802.11b/g wireless technology</li> <li>Ethernet port (RJ45) x 1</li> <li>Wireless antenna connector (SMA) x 1</li> </ul>
<b>Standard Accessories</b>	AC power cord; VGA cable; Composite video cable; DVI cable; Remote control; Battery x 2 for remote control; Detachable antenna; Wireless PnS token; PnS token holder; Carrying case; Users guide (CD-ROM); Quick start guide; Security card	AC power cord; VGA cable; Composite video cable; DVI cable; S-Video cable; Component cable; Remote control; Battery x 2 for remote control; Detachable antenna; Wireless PnS token; PnS token holder; Detachable cable holder; Duster filter x 2; Lens cap; Carrying case; Users guide (CD-ROM); Quick start guide; Security card	AC power cord; VGA cable; Composite video cable; DVI cable; S-Video cable; Component cable; Remote control; Battery x 2 for remote control; Detachable cable holder; Duster filter x 2; Lens cap; Carrying case; Users guide (CD-ROM); Quick start guide; Security card

## LG Projectors

	DX535	DX540	DX630	HS102	DX325	DX420	DS420	
<b>Code</b>	LGPRO-DX535	LGPRO-DX540	LGPRO-DX630	LGPRO-HS102	LGPRO-DX325	LGPRO-DX420	LGPRO-DS420	
<b>Projection System</b>	DLP	DLP	DLP	DLP	DLP	DLP	DLP	
<b>Display Technology</b>	0.7 DMD	0.7 DMD	0.55 DMD	0.55 DMD	0.55 DMD	0.55 DMD	0.55 DMD	
<b>Native Resolution</b>	XGA(1024x768)	XGA(1024x768)	XGA (1024 x 768)	SVGA ( 800 x 600 )	XGA(1024x768)	XGA(1024x768)	SVGA(800x600)	
<b>Brightness (ANSI-Lumens)</b>	3500	4000	3000	160	2500	2000	2000	
<b>Contrast Ratio (FIFO)</b>	2300:1	2800:1	2300:1	2000:1	2200:1	2000:1	2000:1	
<b>Noise</b>	High Brightness Economic	34dB 30dB	29dB 24dB	30dB 27dB	30dB 30dB	28dB	28dB	
<b>Uniformity (min) JBMA</b>	>90%	>90%	>95%	> 90 %	>90%	>90%	>90%	
<b>Color wheel</b>	4 segment(RGBW)	4 segment(RGBW)	4 segment(RGBW)	-	5 segment(RYGWB)	5 segment(RYGWB)	5 segment(RYGWB)	
<b>Projection</b>	Focus Zoom	Manual Manual 1.2x	Manual Manual 1.17x	Manual Fixed	Manual Manual 1.15x	Manual Manual 1.15x	Manual Fixed	
<b>Projection Lens</b>	Screen Size Standard Throw Ratio	40-300 100@3.2m 1.569	40-300 100@3.2m 1.569	40-250 100@4.0m 1.94/2.27(wide/tele)	15 ~ 80 40@1.1m 1.4	34-260 100@3.86m 1.9 ~ 2.2	23-255 50@2m 1.93-2.16	36 ~ 246 50@2m 2.0
<b>Lens Shift</b>	-	-	-	-	-	-	-	
<b>Projection Offset</b>	Type Lamp	230W 2000 Hr 2500 Hr	300W 2000 Hr 2500 Hr	115% 230W 2000 Hr 3000 Hr	100% LED RGB(Luminus PT39) 30,000 hours -	128% 200W 2000 Hrs 3000 Hrs	128% 180W 3000Hrs 4000Hrs	128% 180W 3000Hrs 4000Hrs
<b>Aspect Ratio Control</b>	Native 4:3, Support 16:9	Native 4:3, Support 16:9	Native 4:3, Support 16:9	4:3, 16:9	4:3; 16:9, Native, letter box	4:3; 16:9	4:3; 16:9	
<b>Sound</b>	-	-	-	1W Speaker	1W Speaker	1W speaker	1W speaker	
<b>Dimension (mm)</b>	346x263x109	346x263x109	302x271x95(Leg )	154x117x50	220x178x71	280x205x80mm	280x205x80mm	
<b>Weight (kg)</b>	4.4kg	4.5kg	3.4 kg	750 g	1.45kg	2.58kg	2.54kg	
<b>Power Consumption</b>	280W	100Vac : 380W, 240Vac : 350W Stand-By 5W under	290W / Stand-By 5W under	100 W / Stand-By 5W under	260 W / Stand-By 5W under	230W	230W	
<b>Power Supply</b>	AC 100-240V(Free Voltage), 50/60Hz	AC 100-240V(Free Voltage), 50/60Hz	AC 100 ~ 240V(Free Voltage), 50Hz/60Hz	AC DC Adaptor / 100 ~ 240 Hz, 50/60Hz	Typical@110Vac (100-240)±10%	AC 100 ~ 240V(Free Voltage)	AC 100 ~ 240V(Free Voltage)	
<b>Input Signal Compatibility</b>	Digital DIVX) RGB Component Video Composite Video (incl. S-Video)	1080i/720p/576p/480p, up to SXGA+(1400x1050@60Hz) 1080i/720p/576p/480p, up to SXGA+(1400x1050@60Hz) 1080i/720p/576p/576i/480p/480i 1080i/720p/576p/576i/480p/480i NTSC-M/NTSC 4.43/PAL/PAL-M/ PAL-N/SECAM 1 x RGB in / 1 x RGB out / 1 x S Video / 1 x Composite / 1 x Component(thru RGB) / 1 x HDMI / 1 x DVI / 1 x USB(Type B / SVC) 1 x RS-232C	1080i/720p/576p/480p, up to SXGA+(1400x1050@60Hz) 1080i/720p/576p/480p, up to SXGA+(1400x1050@60Hz) 1080i / 720p / 576P / 576i / 480p / 480i NTSC/PAL/SECAM/NTSC4.43/ PAL-M/PAL-N 1 x RGB in / 1 x RGB out / 1 x S Video / 1 x Composite 1 x Component(YpBPr) / 1 x HDMI / 1 x USB(SVC) 1 x RS-232C	Up to SXGA+(1400X1050@60Hz) USB 1080i/720p/576p/480p(50/60Hz) up to SXGA(1280x1024@60Hz) 1080i/720P/576P/576i/480P/480i 1080i/720P/576P/576i/480P/480i NTSC/PAL/SECAM/NTSC4.43/ M/N/60, SECAM 1 x RGB in / 1 x Composite / 1 x Component(thru RGB) 1 x USB	up to UXGA(1600x1200@60Hz) 1080i / 720p / 576P / 576i / 480p / 480i 1080i/720P/576P/576i/480P/480i NTSC/NTSC 4.43, PAL B/G/H/I/ M/N/60, SECAM 1 x RGB in / 1 x Audio(Mini Jack) / 1 x S Video 1 x Composite / 1 x Component(Thru RGB) 1 x USB(Type B / SVC)	Up to SXGA 1280x1024@75 Hz 1080i / 720p / 576P / 576i / 480p / 480i 1080i / 720p / 576P / 576i / 480p / 480i NTSC/NTSC 4.43, PAL B/G/H/I/ M/N/60, SECAM 1 x RGB in / 1 x Audio(Mini Jack) / 1 x S Video 1 x Composite / 1 x Component(Thru RGB) / 1 x USB(SVC)	Up to SXGA 1280x1024@75 Hz 1080i / 720p / 576P / 576i / 480p / 480i 1080i / 720p / 576P / 576i / 480p / 480i NTSC/NTSC 4.43, PAL B/G/H/I/ M/N/60, SECAM 1 x RGB in / 1 x Audio(Mini Jack) / 1 x S Video 1 x Composite / 1 x Component(Thru RGB) / 1 x USB(SVC)	
<b>Special Features</b>	Digital Keystone Correction / Picture Still	Digital Keystone Correction / Picture Still / Quick Power on/off / Auto Sleep / Smart Picture Mode Presentation Timer / Brilliant Color™ / Expert control VIDI™	Digital Keystone Correction / Picture Still / Quick Power on/off / Auto Sleep / Smart Picture Mode Auto Color ADJ / Presentation Timer Brilliant Color™ / Expert control	Digital Keystone Correction / Picture Still / Quick Power on / off (5 sec in between)	Digital Keystone Correction / Picture Still / Quick Power on/off / Auto Sleep Brilliant Color™ / Expert control	Digital Keystone Correction / Picture Still / Quick Power on/off / Digital Zoom Auto Sleep	Digital Keystone Correction / Picture Still / Quick Power on/off / Digital Zoom Auto Sleep	
<b>Accessory</b>	Power code/D-sub 15 pin cable Remote Control/Lens Cap/CD Manual AAA * 2EA Battery	Power code/D-sub 15 pin cable Remote Control/Quick setup Guide/ Lens Cap CD Manual/AAA * 2EA Battery	Power code/D-sub 15 pin cable Remote Control/Quick setup Guide/ Lens Cap CD Manual/AAA * 2EA Battery	Carry bag/Power code/D-sub 15 pin cable RGB to Component Adapter/Video cable CD Manual/AAA * 2EA Battery / Remote Control	Carry bag/Power code D-sub 15 pin cable/Remote Control CD Manual/Lens Cap	Carry bag/Power code D-sub 15 pin cable/Remote Control CD Manual/Lens Cap	Carry bag/Power code D-sub 15 pin cable/Remote Control CD Manual/Lens Cap	

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>