

## Wireless 802.11b Access Point

The **WP102** is an IEEE802.11b compliant Access Point, which provides a powerful high-speed wireless connection for compatible wireless-enabled devices into the network with the freedom to roam.

The WP102 provides 64/128 bit WEP encryption and IEEE802.1x which ensures a high level of security to protects users' data and privacy. The MAC Address filter prevents the unauthorized MAC Addresses from accessing your Wireless LAN. Your network security is therefore double assured. Plus, the web-based management is easy to use that your wireless network connection is ensured to be always solid and hassle free.



## **Features**

- ♦ Support DHCP client.
- ♦ Support DHCP relay.
- Support data rate automatic fallback.
- ♦ Automatic channel selection.
- ♦ Client access control.
- ♦ Support 802.1x/Radius client with EAP-MD5, TKIP, AES encryption.
- Support IAPP.
- Adjustable Tx power, Tx rate, and SSID broadcast.
- ♦ Allow WEP 64/128 bit.
- ♦ Support SNMP v1/v2.
- Web redirection for unauthorized clients.
- Web interface management.
- Support System event log and statistics.
- ♦ MAC filtering



## **Specifications**

Standards	IEEE 802.11b Wireless LAN	
	IEEE 802.3 10Base-T Ethernet	
	IEEE 802.3u 100Base-TX Fast Ethernet	
Ports	Two 10/100Mbps Ethernet LAN ports	
Data Rates	11/ 5.5/ 2/ 1 Mbps with Automatic Fallback	
Security Encryption	64/ 128 bit WEP encryption	
Media Access Control	CSMA/CA with ACK	
Frequency Range	2.412~2.4835GHz Direct Sequence Spread Spectrum (DSSS)	
Modulation Technology	CCK (for 5.5 &11Mbps)	
	DQPSK (for 2 Mbps)	
	DBPSK (for 1Mbps)	
Transmitter Output Power	$17.5\pm0.5~\mathrm{dBm}$	
External Antenna Type	2.0dBi 1/4 $\lambda$ dipole antenna with reverse SMA connector	
LED indicators	Power	Green for power on
	ErrStatus	Red for error
	Link/Act.	Green (flashing for activity)
	WEP	Orange
	Mac Ctrl	Orange
	Bridge	Orange
	LAN1	Green (flashing for activity)
	LAN2	Green (flashing for activity)
<b>Device Management</b>	Web-based configuration and management	
Power Input	DC 9V, 700mA	
<b>Physical Dimension</b>	129 x 90 x 27 mm <sup>3</sup> (W x D x H)	
Weight	175g	
Agency and Regulatory	FCC part 15 Class B, CE, DGT, BSMI	
Operating	-5°C to 55°C	
Temperature		
Operating Humidity	20~85% non-condensing	

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com