

Enlighten Your Bright Ideas Everywhere!



Acer XD1270D



Specifications	Acer XD1270D
Projection System	DLP™
Resolution	Native XGA (1.024 x 768), Maximum SXGA (1.280 x 1.024)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards SXGA, SVGA, VGA (resizing)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L),
, , , , , ,	HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2200:1
Displayable Colors	16.7 Million Colors
Brightness	2,300 ANSI Lumens (Standard), 1,840 ANSI Lumens (ECO)
Projection Lens	F/2.35 ~ 2.47, f = 21.83mm ~ 23.81mm
•	1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal)	23.1" (0.59m) ~ 302" (7.68m)
Projection Distance	3.28' (1m) ~ 39.4' (12m)
Throw Ratio	50.4"@2m
Horizontal Scan Rate	31.5 ~ 100 kHz
Vertical Refresh Scan Rate	56 ~ 85 Hz
Lamp Type	200 W User Replaceable UHP Lamp
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Keystone Correction	+/-16 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	Yes
Audio	One Internal Speaker with 2 watts Output
Weight	4.8 lbs (2.17Kg)
Dimension	230 x 238 x 123 mm (9.1" x 9.4" x 4.8")
IR Remote Control	Laser Pointer & Mouse function & PgUp/PgDn function
Digital Zoom	Yes
Picture in Picture	N/A
Wireless	N/A
Power Supply	AC Input 100~240V auto-switching power supply
Power Consumption	253 Watts (Operation), 14 Watts (Standby)
Operation Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	32 dBA (Standard mode), 28 dBA (ECO mode)
Uniformity	90%
Other Features	1. Empower Key
	A guick button on remote control or projector control panel for user easily to perform the following three Acer

utton on remote control or projector control panel for user easily to perform the following three Acer

Acer eView Management
 A feature which allows user easily to select the optimal display mode for specific display content.

3. Acer eTimer Management

A feature which allows user to enable a Timer function during the presentation. A digit clock will be displayed on the screen while the timer is in counting. A reminder on the screen and an alarm sound will be activated when time is up.

Acer eOpening Management
 A feature which allows user to customized their desired projector startup screen.

5. Auto Shutdown

A feature which allows the projector automatically turned off according to the setting time via OSD if the projector continuously no signal input

6. Alarm sound

A feature which enables the projector to play the alarm sound under various conditions described below: a) Projector turn on b) Projector turn off

Time is up for the eTimer function d) Projector function error

Quick Start
 The projector starts projecting within 15 seconds after power button being pressed

8. Quick Shutdown

The projector shuts down within 30 seconds after power button being pressed

Security

A feature which enables the password control capability of the projector. It prevents the projector from unauthorized usage. Also, it reduces the possibility of the projector's being stolen

Quick Detection

The projector can immediately detect signal as soon as any source input to the projector. No need

to waste your time to wait for the signal scanning.
 Advanced 5-Segment Color Wheel
 Utilize 5-segment color wheel with additional yellow segment offering great color correctness

 Dual VGA input supported
 Except for original D-Sub connector, the DVI-I connector can also supports analog VGA signal.

With the dual VGA input support, the projector offers better flexibility of connectivity

Computer Input:

• 1 HDB 15-Pin D-Sub (VGA/Component/HDTV)

• 1 3.5mm Audio Mini Jack

1 RS232 Connector
 1 29-pin DVI-I Connector (VGA/Component/HDTV/HDCP)

AV injut.
1 HDB 15-Pin D-Sub (VGA/Component/HDTV, same as above)
1 Composite Video RCA Jack

• 1 S-Video Mini DIN

1 3.5mm Audio Mini Jack (Same as above)
1 29-pin DVI-I Connector (the same one as the above)

Output:

1 15-Pin D-Sub for Monitor Loop Through
 1 USB Connector for Remote Computer Control
 AC Power Cord

VGA Cable (15pin D-Sub) Composite Video Cable (RCA) DVI Cable

S-Video Cable VGA (D-Sub) to Component / HDTV Adapter

USB Cable

Audio Cable (Mini to Mini Phone Jack)
Remote Control with Laser Pointer & Mouse & PgUp/PgDn function
Batteries x 2 for Remote Controller

User's Guide (CD-ROM) Quick Start Card Lens Cap

Carrying Case



หลอดภาพรับประกัน 1 ปี หรือ 1.000 ชั่วโมง



I/O Connectors

Standard Accessories

บริษัท เอเซอร์ คอมพิวเตอร์ จำกัด

0-2685-4311 www.acer.co.th

191/62-63 ชั้น 16 อาคารซีที่ไอ ทาวเวอร์ ถ.รัชดาภิเษกคลองเตย กรุงเทพฯ 10110 โทรศัพท์ 0-2661-9700 โทรสาร 0-2661-9721

Free Manuals Download Website

http://myh66.com

http://usermanuals.us

http://www.somanuals.com

http://www.4manuals.cc

http://www.manual-lib.com

http://www.404manual.com

http://www.luxmanual.com

http://aubethermostatmanual.com

Golf course search by state

http://golfingnear.com

Email search by domain

http://emailbydomain.com

Auto manuals search

http://auto.somanuals.com

TV manuals search

http://tv.somanuals.com